						1/2	
IDENTITY (As Used on Label and L							
SUZUKI SUPER COOLAN		space must be marked to indicate that.					
Section							
Manufacture's Name			Telephone Number				
CCI CORPORATION	0575-24-4744  Data Prepared						
Address (Number, Street, City, State 12 Shinhazama, Seki, Gifu	2008						
12 Shirinazama, Seki, Gilu	JAPAN	301-3923	September 20	J, 2006			
Section - Product Identity In	formatior	1					
Components					% (optio	nal)	
Ethylene glycol						47 3	
Corrosion inhibitors, Antiform, Dye							
Water					50		
Total 100							
Section - Hazardous Ing	edients	Identity Inf/ OSHA		Other Limits			
Hazardous Components (Specific Chemical Identity; Comm	%(optional	l)					
Ethylene glycol					47		
Section - Physical / Cher	nical Ch	aracteristics					
Boiling Point	moar On	108	Density (20 )		1.0	75	
Vapor Pressure (mmHg.)		NE	Melting Point		N		
Vapor Density (AIR=1)		NE		Evaporation Rate (Butyl Acetate=1)			
Vapor Density (AIR=1)  NE Evaporation Rate (Butyl Acetate=1)  NE Solubility in Water							
Adequate							
Appearance and Odor							
Blue, clear liquid, mild odo	ſ						
Section - Fire and Explos	sion Haz	ard Data					
Flash Point (Method Used)			Flammable Limits	LEL	UEL		
None(ASTM D92)				NE NE	NE		
Extinguishing Media Water spray, dry chemical,	carbon	diovide or fo	nam				
Special Fire Fighting Procedures	Carbon	dioxide of ic	Jaiii				
Avoid inhalation of smoke							
Unusual Fire and Explosion Hazard	3						
None							
Section - Reactivity Data							
Stability Unstable		Conditions to					
Stable	×	Keep av	way from flame				
Incompatibility (Materials to Avoid)							
Strong acid or oxidizing ag							
Hazardous Decomposition or Bypro		20 CO 222					
Incomplete combustion ma	y produc	be CO yas.					
Hazardous May Occur		Conditions to	o Avoid				
Polymerization Will Not Occur	×	NA					

Section - Health Hazard Data						
Route(s) of Entry:	Inhalation?	Skin?	Ingestion?			
	×	×	×			

Health Hazards (Acute and Chronic)

May cause skin, eye and mucous membrane irritation. Inhalation of high concentrations of mist or vapors may cause nausea, CNS depression, lethargy.

Carcinogenicity: NTP?

IARC Monographs? OSHA Regulated?

Signs and Symptoms of Exposure

Skin, eye and mucous membrane irritation, lethargy, nausea, defatting of skin, CNS depression Medical Conditions. Generally Aggravated by Exposure.

**Emergency and First Aid Procedures** 

In case of skin and eye contact, flush thoroughly with water and go to hospital. If swallowed, induce vomiting, call a physician.

## Section - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled

Eliminate all sources of ignition in vicinity the spilled or released fluid.

Waste Disposal Method

Use absorbent material such as cloths. Clean up spill and dispose of contaminated material in approved disposal site or incinerator.

Precautions to Be Taken in Handling and Storing

Store with container closed in a dry place away from excessive heat and open flame.

Other Precautions

Use normal precautions in handling any liquid chemicals.

## **Control Measures** Section Respiratory Protection (Specify Type) Not necessary Ventilation Local Exhaust Special Not necessary Not necessary Mechanical (General) Normal ventilation Not necessary Protective Gloves Eye Protection Necessarv Safety goggles

Other Protective Clothing or Equipment

None

Work / Hygienic Practices

## Section - Transport Information

**UN Number: Not Classified** 

IATA: Not regulated (Non Hazardous)

PACK GR: None.

IMDG Code: Not regulated (Non Hazardous)

NA: Not Applicable NE: Not Established

The information presented herein is believed to be factual as it has been derived from the works and options of persons believed to be qualified experts; however, nothing contained in this information is to be taken as a warranty or representation for which CCI bears legal responsibility. The user should review any recommendation in the specific context of the intended use to determine whether they are appropriate.