

MATERIAL SAFETY DATA SHEET

DATE OF PRINTING: 11/13/97

PAGE 1 OF 5

DISTRIBUTOR: GOLD SHIELD DISTRIBUTORS
3111 DEPOT ROAD
HAYWARD, CA 94545

TELEPHONE: (510) 782-2040

TRADE NAME: SOLVENT

PRODUCT CODE: 01-1361

PRODUCT CLASS: PETROLEUM DISTILLATES, N.O.S., (NAPHTHA),

DOT HAZARD CLASSIFICATION: COMBUSTIBLE LIQUID, DOT-E CFR 49 173.150 (F)(2)

ERG #: 128

EMERGENCY TELEPHONE NUMBER (CHEMTREC) 1-800-424-9300

SECTION I - HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT BY WEIGHT	TLV/PEL	UNITS	AGENCY	TYPE
MINERAL SPIRITS	100	100	PPM	OSHA	TWA
CAS NUMBER: 64742-88-7					
*A COMPLEX COMBINATION OF PREDOMINANTLY C9-C12 HYDROCARBONS; EXACT COMPOSITION WILL VARY.					

ACUTE ORAL LD50	ACUTE DERMAL LD50	ACUTE INHALATION LC50
>25 ML/KG (RAT)	>4 ML/KG (RAT)	>3670 PPM/8H (RAT)
4.7 G/KG (RAT)	>4 ML/KG (RAT)	

SECTION II - EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT:

FLUSH EYES WITH PLENTY OF WATER FOR 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION.

SKIN CONTACT:

REMOVE CONTAMINATED CLOTHING/SHOES. FLUSH SKIN WITH WATER. FOLLOW BY WASHING WITH SOAP AND WATER. IF IRRITATION OCCURS, GET MEDICAL ATTENTION. DO NOT REUSE CLOTHING UNTIL CLEANED.

INHALATION:

REMOVE VICTIM TO FRESH AIR AND PROVIDE OXYGEN IF BREATHING IS DIFFICULT. GIVE ARTIFICIAL RESPIRATION IF NOT BREATHING.

INGESTION:

DO NOT INDUCE VOMITING. IF VOMITING OCCURS SPONTANEOUSLY. KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION OF LIQUID INTO THE LUNGS. GET MEDICAL ATTENTION.

NOTE TO PHYSICIAN:

IF MORE THAN 2.0 ML PER KG HAS BEEN INGESTED AND VOMITING HAS NOT OCCURRED, EMESIS SHOULD BE INDUCED WITH SUPERVISION. KEEP VICTIM'S HEAD BELOW HIPS TO PREVENT ASPIRATION. IF SYMPTOMS SUCH AS LOSS OF GAG REFLEX, CONVULSIONS OR UNCONSCIOUSNESS OCCUR BEFORE EMESIS, GASTRIC LAVAGE USING A CUFFED ENDOTRACHEAL TUBE SHOULD BE CONSIDERED.

=====

SECTION III - HEALTH HAZARD DATA

EYE CONTACT:

THIS MATERIAL IS PRACTICALLY NONIRRITATING TO THE EYES. HIGH VAPOR CONCENTRATIONS MAY BE IRRITATING.

SKIN CONTACT:

LIQUID IS SLIGHTLY IRRITATING TO THE SKIN. PROLONGED OR REPEATED LIQUID CONTACT CAN RESULT IN DEFATTING AND DRYING OF THE SKIN WHICH MAY RESULT IN SKIN IRRITATION AND DERMATITIS.

INHALATION (BREATHING):

VAPORS MAY CAUSE IRRITATION TO NOSE, THROAT, AND RESPIRATORY TRACT. HIGH VAPOR CONCENTRATIONS MAY RESULT IN CNS DEPRESSSION.

INGESTION (SWALLOWING):

INGESTION OF PRODUCT MAY RESULT IN VOMITING; ASPIRATION (BREATHING) OF VOMITUS INTO THE LUNGS MUST BE AVOIDED AS EVEN SMALL QUANTITIES MAY RESULT IN ASPIRATION PNEUMONITIS.

SIGNS AND SYMPTOMS:

IRRITATION AS NOTED ABOVE. EARLY TO MODERATE CNS (CENTRAL NERVOUS SYSTEM) DEPRESSION MAY BE EVIDENCED BY GIDDINESS, HEADACHE, DIZZINESS AND NAUSEA; IN EXTREME CASES, UNCONSCIOUSNESS AND DEATH MAY OCCUR. ASPIRATION PNEUMONITIS MAY BE EVIDENCED BY COUGHING, LABORED BREATHING AND CYANOSIS (BLUISH SKIN); IN SEVERE CASES DEATH MAY OCCUR.

AGGRAVATED MEDICAL CONDITIONS:

PREEXISTING EYE, SKIN, AND RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

SUPPLEMENTAL HEALTH INFORMATION:

MALE RATS EXPOSED FOR 90 DAYS BY INHALATION TO VAPORS OF SIMILAR SOLVENTS SHOWED EVIDENCE OF KIDNEY DAMAGE. THE RELEVANCE OF THIS EFFECT TO MAN IS UNKNOWN. IN OF OF THE STUDIES A LOW GRADE ANEMIA WAS ALSO OBSERVED.

=====

SECTION IV - SPECIAL PROTECTION INFORMATION

VENTILATION:

IF CURRENT VENTILATION PRACTICES ARE NOT ADEQUATE TO MAINTAIN AIRBORNE CONCENTRATIONS BELOW ESTABLISHED EXPOSURE LIMITS (SEE SECTION I), ADDITIONAL VENTILATION OR EXHAUST SYSTEMS MAY BE REQUIRED. WHERE EXPLOSIVE MIXTURES MAY BE PRESENT, ELECTRICAL SYSTEMS SAFE FOR SUCH LOCATIONS MUST BE USED.

RESPIRATORY PROTECTION:

THE USE OF RESPIRATORY PROTECTION IS ADVISED WHEN CONCENTRATIONS EXCEED THE ESTABLISHED EXPOSURE LIMITS, (SEE SECTION I). DEPENDING ON THE AIRBORNE CONCENTRATION, USE A RESPIRATOR OR GAS MASK WITH APPROPRIATE CARTRIDGES AND CANISTERS (NIOSH APPROVED, IF AVAILABLE) OR SUPPLIED AIR EQUIPMENT.

PROTECTIVE GLOVES:

THE USE OF GLOVES IMPERMEABLE TO THE SPECIFIC MATERIAL HANDLED IS ADVISED TO PREVENT SKIN CONTACT AND POSSIBLE IRRITATION.

EYE PROTECTION:

APPROVED EYE PROTECTION TO SAFEGUARD AGAINST POTENTIAL EYE CONTACT, IRRITATION OR INJURY IS RECOMMENDED.

OTHER PROTECTIVE EQUIPMENT:

IT IS SUGGESTED THAT A SOURCE OF CLEAN WATER BE AVAILABLE IN THE WORK AREA FOR FLUSHING EYES AND SKIN. IMPERVIOUS CLOTHING SHOULD BE WORN AS NEEDED.

=====

SECTION V - REACTIVITY DATA

STABILITY:

STABLE

INCOMPATIBILITY (MATERIALS TO AVOID):

THIS PRODUCT FORMS COMBUSTIBLE AND/OR EXPLOSIVE MIXTURES WITH AIR AND/OR OXYGEN.

THIS PRODUCT IS INCOMPATIBLE WITH:

STRONG ACIDS OR BASES
OXIDIZING AGENTS
SELECTED AMINES

HAZARDOUS DECOMPOSITION PRODUCTS:

THERMAL DECOMPOSITION IN THE PRESENCE OF AIR MAY YIELD CARBON MONOXIDE AND/OR CARBON DIOXIDE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

=====

SECTION VI - SPILL OR LEAK PROCEDURES

PRECAUTIONS IN CASE OF RELEASE OR SPILL:

CAUTION. COMBUSTIBLE. *** LARGE SPILLS*** ELIMINATE POTENTIAL SOURCES OF IGNITION. WEAR APPROPRIATE RESPIRATOR AND OTHER PROTECTIVE CLOTHING. SHUT OFF SOURCE OF LEAK ONLY IF SAFE TO DO SO. DIKE AND CONTAIN. REMOVE WITH VACUUM TRUCKS OR PUMP TO STORAGE/SALVAGE VESSELS. SOAK UP RESIDUE WITH AN ABSORBENT SUCH AS CLAY, SAND, OR OTHER SUITABLE MATERIAL; PLACE IN NON-LEAKING CONTAINERS AND SEAL TIGHTLY FOR PROPER DISPOSAL. FLUSH AREA WITH WATER TO REMOVE TRACE RESIDUE; DISPOSE OF FLUSH SOLUTION AS ABOVE. ***SMALL SPILLS*** TAKE UP WITH AN ABSORBENT MATERIAL AND PLACE IN NON-LEAKING CONTAINERS FOR PROPER DISPOSAL.

UNDER EPA - RCRA (40 CFR 261.21), IF THIS PRODUCT BECOMES A WASTE MATERIAL, IT WOULD BE IGNITABLE HAZARDOUS WASTE, HAZARDOUS WASTE NUMBER D001. REFER TO LATEST EPA OR STATE REGULATIONS REGARDING PROPER DISPOSAL.

=====

SECTION VII - STORAGE AND SPECIAL PRECAUTIONS

HANDLING AND STORAGE PRECAUTIONS:

KEEP LIQUID AWAY FROM HEAT, SPARKS AND FLAME. SURFACES THAT ARE SUFFICIENTLY HOT MAY IGNITE EVEN LIQUID PRODUCT IN THE ABSENCE OF SPARKS OR FLAME. SURFACES THAT ARE SUFFICIENTLY HOT MAY IGNITE EVEN LIQUID PRODUCT IN THE ABSENCE OF SPARKS OR FLAME. EXTINGUISH PILOT LIGHTS, CIGARETTES AND TURN OFF OTHER SOURCES OF IGNITION PRIOR TO USE AND UNTIL ALL VAPORS ARE GONE. VAPORS MAY ACCUMULATE AND TRAVEL TO IGNITION SOURCES DISTANT FROM THE HANDLING SITE, FLASH-FIRE CAN RESULT. KEEP CONTAINERS CLOSED WHEN NOT IN USE. USE WITH ADEQUATE VENTILATION. CONTAINERS, EVEN THOSE THAT HAVE BEEN EMPTIED, CAN CONTAIN EXPLOSIVE VAPORS. DO NOT CUT, DRILL, GRIND, WELD OR PERFORM SIMILAR OPERATIONS ON OR NEAR CONTAINERS. STATIC ELECTRICITY MAY ACCUMULATE AND CREATE A FIRE HAZARD. GROUND FIXED EQUIPMENT. BOND AND GROUND TRANSFER CONTAINERS AND EQUIPMENT.

=====

SECTION VIII - FIRE AND EXPLOSION HAZARD DATA

		HAZARD RANKING
NFPA	HEALTH HAZARD: 2	0 - LEAST
HAZARD	FLAMMABILITY: 2	1 - SLIGHT
CLASS	REACTIVITY: 0	2 - MODERATE
		3 - HIGH
		4 - EXTREME
		* - LONG TERM HEALTH EFFECT

FLASH POINT: 108 TAG CLOSED CUP

LEL: 1

UEL: 7.0

VOC: 175 GR/LTR

EXTINGUISHING MEDIA:

USE WATER FOG, FOAM, DRY CHEMICAL OR CO2. DO NOT USE A DIRECT STREAM OF WATER. PRODUCT WILL FLOAT AND CAN BE REIGNITED ON SURFACE OF WATER.

FIRE AND EXPLOSION HAZARDS:

CONTAINERS EXPOSED TO INTENSE HEAT FROM FIRES SHOULD BE COOLED WITH WATER TO PREVENT VAPOR PRESSURE BUILDUP WHICH COULD RESULT IN CONTAINER RUPTURE. CONTAINER AREAS EXPOSED TO DIRECT FLAME CONTACT SHOULD BE COOLED WITH LARGE QUANTITIES OF WATER AS NEEDED TO PREVENT WEAKENING OF CONTAINER STRUCTURE.

FIRE FIGHTING PROCEDURES:

CAUTION. COMBUSTIBLE. DO NOT ENTER CONFINED FIRE SPACE WITHOUT FULL BUNKER GEAR (HELMET WITH FACE SHIELD, BUNKER COATS, GLOVES AND RUBBER BOOTS), INCLUDING A POSITIVE PRESSURE NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED CONTAINERS WITH WATER.

=====

SECTION IX - PHYSICAL DATA

BOILING RANGE: 320 - 372

VAPOR DENSITY: 5.3

SPECIFIC GRAVITY (60F/60F): .78

PERCENT VOLATILE BY VOLUME: 100

RELATIVE EVAP. RATE: .07

VAPOR PRESSURE: <5 @ 100 DEG F

% SOLUBILITY IN WATER: .1

ODOR: CHARACTERISTIC

APPEARANCE: CLEAR, LITTLE IF ANY COLOR

THE INFORMATION IN THIS DOCUMENT IS BELIEVED TO BE CORRECT AS OF THE DATE ISSUED. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THIS INFORMATION, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED T

REFERENCE DATE: 11/13/97

ADDENDUM TO MATERIAL SAFETY DATA SHEET

PERSUANT TO THE REQUIREMENTS OF CALIFORNIA PROPOSITION 65, THE SAFE DRINKING WATER AND TOXICS ENFORCEMENT ACT, THE FOLLOWING WARNINGS ARE REQUIRED FOR THIS PRODUCT:

1 WARNING THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

2 WARNING THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM