

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: July 07, 2017

Revision: July 07, 2017

1 Identification

- **Product identifier**
- **Trade name:** Vulcanizing Cement
- **Article number:** 14-004, 14-008, 14-009, 14-020, 14-032, 14-041, 14-511, 14-512, 15-026
- **Recommended use and restriction on use**
- **Recommended use:** Tire maintenance.
- **Restrictions on use:** No relevant information available.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
31 Incorporated
100 Enterprise Dr.
Newcomerstown, OH 43832
Phone: (740) 498-8324
- **Emergency telephone number:**
ChemTel Inc.
(800)255-3924 (North America)
+1 (813)248-0585 (International)

2 Hazard(s) identification

- **Classification of the substance or mixture**
Flam. Liq. 2 H225 Highly flammable liquid and vapor.
Skin Irrit. 2 H315 Causes skin irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H336 May cause drowsiness or dizziness.
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:



GHS02 GHS07 GHS08

· Signal word: Danger

· Hazard statements:

H225 Highly flammable liquid and vapor.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.
H304 May be fatal if swallowed and enters airways.

· Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.

(Cont'd. on page 2)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: July 07, 2017

Revision: July 07, 2017

Trade name: Vulcanizing Cement

(Cont'd. of page 1)

P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing mist, vapors, or spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing must not be allowed out of the workplace.
P280	Wear protective gloves / eye protection / face protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P331	Do NOT induce vomiting.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use for extinction: CO ₂ , powder or water spray.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Components:

142-82-5	heptane	 Flam. Liq. 2, H225  Asp. Tox. 1, H304  Skin Irrit. 2, H315; STOT SE 3, H336	>70%
9006-04-6	natural rubber latex	 Skin Sens. 1B, H317	10-20%

· Additional information:

For the wording of the listed Hazard Statements refer to section 16.

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.

4 First-aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air; consult doctor in case of complaints.

Provide oxygen treatment if affected person has difficulty breathing.

In case of irregular breathing or respiratory arrest provide artificial respiration.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately remove any clothing soiled by the product.

(Cont'd. on page 3)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: July 07, 2017

Revision: July 07, 2017

Trade name: Vulcanizing Cement

(Cont'd. of page 2)

Immediately wash with water and soap and rinse thoroughly.

If skin irritation or rash occurs: Get medical advice/attention.

· **After eye contact:**

Rinse opened eye for several minutes under running water.

Remove contact lenses if worn, if possible.

Seek medical treatment in case of complaints.

· **After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

A person vomiting while lying on their back should be turned onto their side.

· **Most important symptoms and effects, both acute and delayed:**

Headache

Breathing difficulty

Coughing, dizziness, if inhaled.

Gastric or intestinal disorders when ingested.

Irritant to skin and mucous membranes.

Allergic reactions

Disorientation

· **Danger:**

Danger of impaired breathing.

Vapours may cause drowsiness and dizziness.

May be fatal if swallowed and enters airways.

· **Indication of any immediate medical attention and special treatment needed:**

If swallowed, gastric irrigation with added, activated carbon.

If necessary oxygen respiration treatment.

If swallowed or in case of vomiting, danger of entering the lungs.

Later observation for pneumonia and pulmonary edema.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fire with alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water stream.

· **Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

· **Advice for firefighters**

· **Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

· **Additional information:** Eliminate all ignition sources if safe to do so.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

(Cont'd. on page 4)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: July 07, 2017

Revision: July 07, 2017

Trade name: Vulcanizing Cement

(Cont'd. of page 3)

Ensure adequate ventilation.

Keep away from ignition sources.

Protect from heat.

· **Environmental precautions**

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

· **Methods and material for containment and cleaning up**

Allow to solidify. Pick up mechanically.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· **Handling**

· **Precautions for safe handling:**

Use only outdoors or in a well-ventilated area.

Prevent formation of aerosols.

Avoid splashes or spray in enclosed areas.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Flammable gas-air mixtures may be formed in empty containers/receptacles.

· **Conditions for safe storage, including any incompatibilities**

· **Storage**

· **Requirements to be met by storerooms and receptacles:**

Store in cool, dry conditions in well sealed receptacles.

Provide ventilation for receptacles.

Avoid storage near extreme heat, ignition sources or open flame.

· **Information about storage in one common storage facility:**

Store away from foodstuffs.

Store away from oxidizing agents.

· **Further information about storage conditions:** Keep containers tightly sealed.

· **Specific end use(s)** No relevant information available.

8 Exposure controls/personal protection

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

142-82-5 heptane

PEL (USA)

Long-term value: 2000 mg/m³, 500 ppm

(Cont'd. on page 5)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: July 07, 2017

Revision: July 07, 2017

Trade name: Vulcanizing Cement

(Cont'd. of page 4)

REL (USA)	Long-term value: 350 mg/m ³ , 85 ppm Ceiling limit value: 1800* mg/m ³ , 440* ppm *15-min
TLV (USA)	Short-term value: 2050 mg/m ³ , 500 ppm Long-term value: 1640 mg/m ³ , 400 ppm
EL (Canada)	Short-term value: 500 ppm Long-term value: 400 ppm
EV (Canada)	Short-term value: 2045 mg/m ³ , 500 ppm Long-term value: 1635 mg/m ³ , 400 ppm
LMPE (Mexico)	Short-term value: 500 ppm Long-term value: 400 ppm

9006-04-6 natural rubber latex

TLV (USA)	Long-term value: 0.0001* mg/m ³ Skin; DSEN, RSEN; * inh. fraction
EL (Canada)	Long-term value: 0.001 mg/m ³ inhalable, Skin; S
EV (Canada)	Long-term value: 0.001 mg/m ³ as total proteins, inhalable, Skin
LMPE (Mexico)	Long-term value: 0.0001* mg/m ³ SEN, PIEL, *fracción inhalable

· Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· Engineering controls:

Take precautionary measures against static discharge.

Do not expose to temperatures exceeding 50 °C/122°F.

Store in a well-ventilated place.

· Breathing equipment:

Wear appropriate NIOSH respirator when ventilation is inadequate and occupational exposure limits are exceeded.

For spills, respiratory protection may be advisable.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Cont'd. on page 6)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: July 07, 2017

Revision: July 07, 2017

Trade name: Vulcanizing Cement

(Cont'd. of page 5)

· Eye protection:



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

· Body protection: Protective work clothing

· Limitation and supervision of exposure into the environment

No relevant information available.

· Risk management measures No relevant information available.

9 Physical and chemical properties

· Information on basic physical and chemical properties

· Appearance:

Form: Liquid

Color: Cloudy

· Odor: Solvent-like

· Odor threshold: Not determined.

· pH-value: Not determined.

· Melting point/Melting range: Not determined.

· Boiling point/Boiling range: 93 °C (199 °F)

· Flash point: 0 °C (32 °F)

· Flammability (solid, gaseous): Not applicable.

· Auto-ignition temperature: 215 °C (419 °F)

· Decomposition temperature: Not determined.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits

Lower: 1.1 Vol %

Upper: 6.7 Vol %

· Oxidizing properties: Not determined.

· Vapor pressure at 20 °C (68 °F): 48 hPa (36 mm Hg)

· Density at 20 °C (68 °F): 0.77 g/cm³ (6.426 lbs/gal)

· Relative density: Not determined.

· Vapor density: Not determined.

· Evaporation rate: Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

(Cont'd. on page 7)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: July 07, 2017

Revision: July 07, 2017

Trade name: Vulcanizing Cement

(Cont'd. of page 6)

- **Viscosity**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
- **Other information** No relevant information available.

10 Stability and reactivity

- **Reactivity:** No relevant information available.
- **Chemical stability:**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Possibility of hazardous reactions**
Flammable.
Reacts violently with oxidizing agents.
Used empty containers may contain product gases which form explosive mixtures with air.
Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.
Toxic fumes may be released if heated above the decomposition point.
- **Conditions to avoid**
Keep away from heat and direct sunlight.
Keep ignition sources away - Do not smoke.
Store away from oxidizing agents.
- **Incompatible materials** Oxidizing agents
- **Hazardous decomposition products** Carbon monoxide and carbon dioxide

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

142-82-5 heptane

Oral	LD50	> 5000 mg/kg (rat)
Inhalative	LC50/4h	103 mg/l (rat)

- **Primary irritant effect:**
- **On the skin:** Irritant to skin and mucous membranes.
- **On the eye:** Based on available data, the classification criteria are not met.
- **Sensitization:** Contains natural rubber latex. May produce an allergic reaction.

- **IARC (International Agency for Research on Cancer):**

None of the ingredients are listed.

- **NTP (National Toxicology Program):**

None of the ingredients are listed.

- **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

(Cont'd. on page 8)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: July 07, 2017

Revision: July 07, 2017

Trade name: Vulcanizing Cement

(Cont'd. of page 7)

- **Probable route(s) of exposure:**
 - Ingestion.
 - Inhalation.
 - Eye contact.
 - Skin contact.
- **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.
- **Carcinogenicity:** Based on available data, the classification criteria are not met.
- **Reproductive toxicity:** Based on available data, the classification criteria are not met.
- **STOT-single exposure:** May cause drowsiness or dizziness.
- **STOT-repeated exposure:** Based on available data, the classification criteria are not met.
- **Aspiration hazard:** May be fatal if swallowed and enters airways.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity** Toxic for aquatic organisms
- **Persistence and degradability** No relevant information available.
- **Bioaccumulative potential:** No relevant information available.
- **Mobility in soil:** No relevant information available.
- **Additional ecological information**
- **General notes:**
 - Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.
 - Do not allow product to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 - The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.
- **Uncleaned packagings**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1206

(Cont'd. on page 9)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: July 07, 2017

Revision: July 07, 2017

Trade name: Vulcanizing Cement

(Cont'd. of page 8)

· UN proper shipping name

· DOT, ADR, IMDG, IATA

HEPTANES

· Transport hazard class(es)

· DOT



· Class

3 Flammable liquids

· Label

3

· ADR



· Class

3 (F1) Flammable liquids

· Label

3

· IMDG, IATA



· Class

3 Flammable liquids

· Label

3

· Packing group

· DOT, ADR, IMDG, IATA

II

· Environmental hazards

Product contains environmentally hazardous substances: heptane

· Marine pollutant:



Yes

· Special precautions for user

Warning: Flammable liquids

· Danger code (Kemler):

33

· EMS Number:

F-E,S-D

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code

Not applicable.

(Cont'd. on page 10)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: July 07, 2017

Revision: July 07, 2017

Trade name: Vulcanizing Cement

(Cont'd. of page 9)

· Transport/Additional information:

· DOT



Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L each.

Labeling as a Marine Pollutant is only required for bulk single package shipments. Bulk packaging consists of a maximum capacity of greater than 450 L (119 gallons) for a liquid and a maximum net mass greater than 400 kg (882 pounds) for a solid. (See 171.4(c))

· ADR



Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L each.

Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to provisions relevant to marine pollutants. (See 5.2.8.1)

· IMDG



Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L each.

Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to provisions relevant to marine pollutants. (See 2.10.2.7)

· IATA



Limited Quantity for packages less than 30 kg gross and inner packagings less than 0.5 L each / 1 L net.

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· United States (USA)

· SARA

· Section 302 (extremely hazardous substances):

None of the ingredients are listed.

· Section 355 (extremely hazardous substances):

None of the ingredients are listed.

(Cont'd. on page 11)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: July 07, 2017

Revision: July 07, 2017

Trade name: Vulcanizing Cement

(Cont'd. of page 10)

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients are listed.

· **TSCA (Toxic Substances Control Act)**

All ingredients are listed.

· **Proposition 65 (California)**

· **Chemicals known to cause cancer:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency):**

142-82-5 heptane

D

· **IARC (International Agency for Research on Cancer):**

None of the ingredients are listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health):**

None of the ingredients are listed.

· **Canadian Domestic Substances List (DSL):**

All ingredients are listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Date of preparation / last revision** July 07, 2017 / -

· **Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bio-accumulable, Toxique

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety & Health Administration

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

(Cont'd. on page 12)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: July 07, 2017

Revision: July 07, 2017

Trade name: Vulcanizing Cement

(Cont'd. of page 11)

· Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor_internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com