

NAPA PENETRATING LUBRICANT

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 01/19/2017

Supersedes:06/03/2015

Version: 1.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : NAPA PENETRATING LUBRICANT
Product code : 6300

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Lubricating Spray

1.3. Details of the supplier of the safety data sheet

Automotive Redistribution Center, Balkamp Incorporation
2601 Stout Heritage Parkway
Plainfield, IN 46168 - USA
T 1-800-468-6832

1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Aerosol 1 H222
Compressed gas H280
Asp. Tox. 1 H304

Full text of H statements : see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS02



GHS04



GHS08

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H222 - Extremely flammable aerosol
H280 - Contains gas under pressure; may explode if heated
H304 - May be fatal if swallowed and enters airways

Precautionary statements (GHS-US) : P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking
P211 - Do not spray on an open flame or other ignition source
P251 - Pressurized container: Do not pierce or burn, even after use
P301+P310 - If swallowed: Immediately call a poison control center, doctor, physician,
P331 - Do NOT induce vomiting
P405 - Store locked up
P410+P403 - Protect from sunlight. Store in a well-ventilated place
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

2.3. Other hazards

Other hazards not contributing to the classification : Contains gas under pressure; may explode if heated. None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Distillates (Petroleum), Hydrotreated Light	(CAS No) 64742-47-8	>= 95	Asp. Tox. 1, H304
Carbon Dioxide, Liquefied, Under Pressure	(CAS No) 124-38-9	1 - 5	Compressed gas, H280
Oleic Acid	(CAS No) 112-80-1	1 - 5	Not classified

The exact percentage is a trade secret.

NAPA PENETRATING LUBRICANT

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Cough. Allow victim to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
First-aid measures after eye contact	: Direct contact with the eyes is likely to be irritating. Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: If you feel unwell, seek medical advice.
Symptoms/injuries after inhalation	: Shortness of breath.
Symptoms/injuries after skin contact	: May cause slight irritation . May cause moderate irritation. Red skin.
Symptoms/injuries after eye contact	: May cause slight eye irritation . May cause severe irritation. Redness of the eye tissue. Inflammation/damage of the eye tissue.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. DO NOT fight fire when fire reaches explosives. Evacuate area.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: Aerosol level 3.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: No open flames. No smoking. Isolate from fire, if possible, without unnecessary risk. Remove ignition sources. Use special care to avoid static electric charges.
------------------	---

6.1.1. For non-emergency personnel

Protective equipment	: Gloves. Safety glasses.
Emergency procedures	: Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Dam up the liquid spill. Plug the leak, cut off the supply. Contain released substance, pump into suitable containers.
Methods for cleaning up	: Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Hazardous waste due to potential risk of explosion. Pressurized container: Do not pierce or burn, even after use.
-----------------------------------	---

NAPA PENETRATING LUBRICANT

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not spray on an open flame or other ignition source.
- Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not eat, drink or smoke when using this product. Wash affected areas thoroughly after handling. Wash contaminated clothing before reuse. Always wash hands after handling the product. Separate working clothes from town clothes. Launder separately. Remove contaminated clothes.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.
- Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use. Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place.
- Incompatible products : Strong bases. Strong acids.
- Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.
- Storage area : Store in a well-ventilated place.

7.3. Specific end use(s)

Follow Label Directions.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Carbon Dioxide, Liquefied, Under Pressure (124-38-9)		
USA ACGIH	ACGIH TWA (mg/m ³)	9000 mg/m ³
USA ACGIH	ACGIH TWA (ppm)	5000 ppm (Carbon dioxide; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
USA ACGIH	ACGIH STEL (mg/m ³)	54000
USA ACGIH	ACGIH STEL (ppm)	30000 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	9000 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	5000 ppm
Distillates (Petroleum), Hydrotreated Light (64742-47-8)		
USA ACGIH	ACGIH TWA (ppm)	200 ppm 8 Hours

8.2. Exposure controls

- Appropriate engineering controls : Local exhaust ventilation, vent hoods . Ensure good ventilation of the work station.
- Personal protective equipment : Gloves. Safety glasses. Avoid all unnecessary exposure.



- Materials for protective clothing : GIVE EXCELLENT RESISTANCE:
- Hand protection : Wear protective gloves.
- Eye protection : Chemical goggles or safety glasses.
- Skin and body protection : Wear suitable protective clothing.
- Respiratory protection : Wear respiratory protection.
- Consumer exposure controls : Avoid contact during pregnancy/while nursing.
- Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Gas
- Appearance : Liquid.
- Color : Colourless to light yellow.
- Odor : Kerosene.
- Odor threshold : No data available
- pH : No data available
- Relative evaporation rate (butyl acetate=1) : 0.19
- Melting point : No data available
- Freezing point : No data available

NAPA PENETRATING LUBRICANT

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Boiling point	: 222 - 247 °C
Flash point	: 94.7 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: 0.013 kPa
Relative vapor density at 20 °C	: 4.5
Relative density	: 0.805
Solubility	: Insoluble in water. Water: 1.5 g/l
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: 1.92 cSt @ 40 deg C
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

9.2. Other information

VOC content	: 0 %
Gas group	: Compressed gas

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Oleic Acid (112-80-1)	
LD50 oral rat	> 19200 mg/kg (Rat)
Distillates (Petroleum), Hydrotreated Light (64742-47-8)	
LD50 oral rat	> 5000 mg/kg body weight
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5.28 mg/l/4h Based on lack of mortality and systemic effects

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.

NAPA PENETRATING LUBRICANT

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: Shortness of breath.
Symptoms/injuries after skin contact	: May cause slight irritation . May cause moderate irritation. Red skin.
Symptoms/injuries after eye contact	: May cause slight eye irritation . May cause severe irritation. Redness of the eye tissue. Inflammation/damage of the eye tissue.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Oleic Acid (112-80-1)	
LC50 fish 2	205 mg/l (LC50; 96 h; Pimephales promelas)
Carbon Dioxide, Liquefied, Under Pressure (124-38-9)	
LC50 fish 1	35 mg/l (LC50; 96 h; Salmo gairdneri)

12.2. Persistence and degradability

NAPA PENETRATING LUBRICANT	
Persistence and degradability	Not established.
Oleic Acid (112-80-1)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Adsorbs into the soil. Photodegradation in the air.
Chemical oxygen demand (COD)	2.25 g O ₂ /g substance
ThOD	2.89 g O ₂ /g substance
BOD (% of ThOD)	> 0.5 (5 days; Literature study)
Carbon Dioxide, Liquefied, Under Pressure (124-38-9)	
Persistence and degradability	Biodegradability: not applicable. Not applicable (gas).
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
Distillates (Petroleum), Hydrotreated Light (64742-47-8)	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

NAPA PENETRATING LUBRICANT	
Bioaccumulative potential	Not established.
Oleic Acid (112-80-1)	
Log Pow	5.24 - 7.18 (QSAR)
Bioaccumulative potential	Not established.
Carbon Dioxide, Liquefied, Under Pressure (124-38-9)	
Log Pow	0.83 (Experimental value)
Bioaccumulative potential	Bioaccumulation: not applicable.
Distillates (Petroleum), Hydrotreated Light (64742-47-8)	
Bioaccumulative potential	Not established.

12.4. Mobility in soil

Oleic Acid (112-80-1)	
Surface tension	0.033 N/m (20 °C)

12.5. Other adverse effects

Other information	: Avoid release to the environment.
-------------------	-------------------------------------

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.
Additional information	: Flammable vapors may accumulate in the container.
Ecology - waste materials	: Avoid release to the environment. Hazardous waste due to toxicity.

NAPA PENETRATING LUBRICANT

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

US DOT (ground):	UN1950, Aerosols, 2.1, Limited Quantity
ICAO/IATA (air):	UN1950, Aerosols, 2.1, Limited Quantity
IMO/IMDG (water):	UN1950, Aerosols, 2.1, Limited Quantity
Special Provisions:	N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols

14.2. UN proper shipping name

Proper Shipping Name (DOT)	: Aerosols Flammable, (each not exceeding 1 L capacity)
Class (DOT)	: 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
Hazard labels (DOT)	: 2.1 - Flammable gas



DOT Special Provisions (49 CFR 172.102)	: N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Packaging Non Bulk (49 CFR 173.xxx)	: None
DOT Packaging Bulk (49 CFR 173.xxx)	: None

14.3. Additional information

Other information	: No supplementary information available.
-------------------	---

Overland transport

No additional information available

Transport by sea

DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel
DOT Vessel Stowage Other	: 48 - Stow "away from" sources of heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

Air transport

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg

SECTION 15: Regulatory information

15.1. US Federal regulations

NAPA PENETRATING LUBRICANT	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Immediate (acute) health hazard Fire hazard Sudden release of pressure hazard
Oleic Acid (112-80-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Carbon Dioxide, Liquefied, Under Pressure (124-38-9)	
SARA Section 311/312 Hazard Classes	Sudden release of pressure hazard Immediate (acute) health hazard
Distillates (Petroleum), Hydrotreated Light (64742-47-8)	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard

15.2. International regulations

CANADA

NAPA PENETRATING LUBRICANT	
WHMIS Classification	Class B Division 5 - Flammable Aerosol

NAPA PENETRATING LUBRICANT

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Oleic Acid (112-80-1)	
Listed on the Canadian DSL (Domestic Substances List)	
Distillates (Petroleum), Hydrotreated Light (64742-47-8)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria

EU-Regulations

Oleic Acid (112-80-1)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)- Directive 79/831/EEC, sixth Amendment of Directive 67/548/EEC (dangerous substances)	

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

15.2.2. National regulations

Oleic Acid (112-80-1)	
Listed on the AICS (Australian Inventory of Chemical Substances)	
Listed on the Korean ECL (Existing Chemicals List)	

15.3. US State regulations

NAPA PENETRATING LUBRICANT				
U.S. - California - Proposition 65 - Carcinogens List		No		
U.S. - California - Proposition 65 - Developmental Toxicity		No		
U.S. - California - Proposition 65 - Reproductive Toxicity - Female		No		
U.S. - California - Proposition 65 - Reproductive Toxicity - Male		No		
Oleic Acid (112-80-1)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
Carbon Dioxide, Liquefied, Under Pressure (124-38-9)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
Distillates (Petroleum), Hydrotreated Light (64742-47-8)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	


SECTION 16: Other information

Other information : None.

Full text of H-phrases:

H222	Extremely flammable aerosol
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.



NAPA PENETRATING LUBRICANT

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA fire hazard	: 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in air and will burn readily.
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.

HMIS III Rating

Health	: 2 Moderate Hazard - Temporary or minor injury may occur
Flammability	: 4 Severe Hazard
Physical	: 1 Slight Hazard
Personal Protection	: B

SDS US (GHS HazCom 2012) - TCC

The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.