

**SAFETY DATA SHEET**

Revision Date: 06/16/2016

Print Date: 10/6/2016

SDS Number: R0296767

Version: 1.1

BMW/ MINI/ MOTORRAD ANTIFREEZE/ COOLANT

811877

29 CFR 1910.1200 (OSHA HazCom 2012)

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : BMW/ MINI/ MOTORRAD ANTIFREEZE/ COOLANT

Product code : 82 14 1 467 704, 82 14 0 031 133, 82 14 2 209 769, 81 22 0 049 923

Company : BMW of North America,LLC., BMW Motorrad USA  
300 Chestnut Ridge Road  
Woodcliff Lake, NJ 07677

Telephone : Telephone: 201-307-4000.8:00 am. 5:00 pm. EST

Telefax: 201-307-4095

Emergency Info : For 24-hour emergency assistance, call: the 3E Company at 1-877-472-1724.  
Please provide product tracking code: 9457.

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Acute toxicity (Oral) : Category 4

Reproductive toxicity : Category 1B

Specific target organ systemic toxicity - repeated exposure (Oral) : Category 2 (Kidney, Liver)

**GHS label elements**

Hazard pictograms :



Signal Word : Danger

Hazard Statements : Harmful if swallowed.  
May damage fertility or the unborn child.  
May cause damage to organs (Kidney, Liver) through prolonged or repeated exposure if swallowed.

Precautionary Statements : **Prevention:**  
Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.

**SAFETY DATA SHEET**

Revision Date: 06/16/2016

Print Date: 10/6/2016

SDS Number: R0296767

Version: 1.1

BMW/ MINI/ MOTORRAD ANTIFREEZE/ COOLANT

811877

Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.  
 Wash skin thoroughly after handling.  
 Do not eat, drink or smoke when using this product.  
 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

IF exposed or concerned: Get medical advice/ attention.

**Storage:**

Store locked up.

**Disposal:**

Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**Hazardous components**

Chemical name	CAS-No.	Classification	Concentration (%)
ETHYLENE GLYCOL	107-21-1	Acute Tox. 4; H302 STOT RE 2; H373	93.3307
DIETHYLENE GLYCOL	111-46-6	Acute Tox. 4; H302 STOT RE 2; H373	4.6608
2-ETHYLHEXANOIC ACID, SODIUM SALT	19766-89-3	Repr. 2; H361	3.0072
DISODIUM TETRABORATE ANHYDROUS	1330-43-4	Repr. 1B; H360	0.7658

**SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.  
 Call a POISON CENTRE or doctor/physician if exposed or you feel unwell.  
 Show this safety data sheet to the doctor in attendance.  
 Do not leave the victim unattended.

**SAFETY DATA SHEET**

Revision Date: 06/16/2016

Print Date: 10/6/2016

SDS Number: R0296767

Version: 1.1

BMW/ MINI/ MOTORRAD ANTIFREEZE/ COOLANT

811877

- If inhaled : If unconscious place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.  
Protect unharmed eye.  
If eye irritation persists, consult a specialist.
- If swallowed : Obtain medical attention.  
Rinse mouth with water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Effects of acute ethylene glycol poisoning appear in three fairly distinct stages. The initial stage occurs shortly after exposure, lasts 6-12 hours, and is characterized by central nervous system effects (transient exhilaration, nausea, vomiting, and in severe cases, coma, convulsions, and possible death). The second stage lasts from 12-36 hours after exposure and is initiated by the onset of coma. This phase is characterized by tachypnea, tachycardia, mild hypotension, cyanosis, and in severe cases, pulmonary edema, bronchopneumonia, cardiac enlargement, and congestive failure. The final stage occurs 24-72 post-exposure and is characterized by renal failure, ranging from a mild increase in blood urea nitrogen and creatinine followed by recovery, to complete anuria with acute tubular necrosis that can lead to death. Oxaluria is found in most cases. The most significant laboratory finding in ethylene glycol intoxication is severe metabolic acidosis.

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:

stomach or intestinal upset (nausea, vomiting, diarrhea)  
irritation (nose, throat, airways)

Cough

pain in the abdomen and lower back

cyanosis (causes blue coloring of the skin and nails from lack of oxygen)

lung edema (fluid buildup in the lung tissue)

acute kidney failure (sudden slowing or stopping of urine production)

Convulsions

Harmful if swallowed.

May damage fertility or the unborn child.

<b>SAFETY DATA SHEET</b>	Revision Date: 06/16/2016
	Print Date: 10/6/2016
	SDS Number: R0296767
BMW/ MINI/ MOTORRAD ANTIFREEZE/ COOLANT	Version: 1.1
811877	

Notes to physician : This product contains ethylene glycol. Ethanol decreases the metabolism of ethylene glycol to toxic metabolites. Ethanol should be administered as soon as possible in cases of severe poisoning since the elimination half-life of ethylene glycol is 3 hours. If medical care will be delayed several hours, give the patient three to four 1-ounce oral "shots" of 86-proof or higher whiskey before or during transport to the hospital. Fomepizole (4-methylpyrazole) is an effective antagonist of alcohol dehydrogenase, and as such, may be used as an antidote in the treatment of ethylene glycol poisoning. Hemodialysis effectively removes ethylene glycol and its metabolites from the body.

---

## SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Water spray  
Foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Alcohols  
Aldehydes  
carbon dioxide and carbon monoxide  
ethers  
toxic fumes  
Hydrocarbons  
various hydrocarbons  
Sodium oxides
- Specific extinguishing methods :  
  
Product is compatible with standard fire-fighting agents.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

---

## SECTION 6. ACCIDENTAL RELEASE MEASURES

**SAFETY DATA SHEET**

Revision Date: 06/16/2016

Print Date: 10/6/2016

SDS Number: R0296767

Version: 1.1

BMW/ MINI/ MOTORRAD ANTIFREEZE/ COOLANT

811877

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.
- Other information : Comply with all applicable federal, state, and local regulations.

**SECTION 7. HANDLING AND STORAGE**

- Advice on safe handling : Do not breathe vapours/dust.  
Do not smoke.  
Container hazardous when empty.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
Smoking, eating and drinking should be prohibited in the application area.  
For personal protection see section 8.  
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Observe label precautions.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ETHYLENE GLYCOL	107-21-1	Ceiling	100 mg/m3 Aerosol.	ACGIH
		TWA	10 mg/m3 Inhalable fraction and vapor	ACGIHLIS_P
				ACGIH
		TWA	10 mg/m3	ACGIHLIS_P
		TWA	25 ppm	ACGIHLIS_P
		STEL	50 ppm	ACGIHLIS_P

**SAFETY DATA SHEET**

Revision Date: 06/16/2016

Print Date: 10/6/2016

SDS Number: R0296767

Version: 1.1

BMW/ MINI/ MOTORRAD ANTIFREEZE/ COOLANT

811877

		Ceiling	50 ppm 125 mg/m3	Z1A
DIETHYLENE GLYCOL	111-46-6	TWA	10 mg/m3	WEEL
		ST ESL	50 µg/m3	TX ESL
		ST ESL	400 µg/m3	TX ESL
		AN ESL	5 µg/m3	TX ESL
		AN ESL	40 µg/m3	TX ESL
DISODIUM TETRABORATE ANHYDROUS	1330-43-4	REL	1 mg/m3	NIOSH/GUID E
				ACGIH
		TWA	10 mg/m3	TN OEL
		TWA	2 mg/m3 Inhalable fraction.	ACGIH
		STEL	6 mg/m3 Inhalable fraction.	ACGIH

Hazardous components without workplace control parameters

**Engineering measures** : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

**Personal protective equipment**

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

Hand protection

Remarks

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection

: Wear as appropriate:  
Impervious clothing  
Safety shoes  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures

: Wash hands before breaks and at the end of workday.

**SAFETY DATA SHEET**

Revision Date: 06/16/2016

Print Date: 10/6/2016

SDS Number: R0296767

Version: 1.1

BMW/ MINI/ MOTORRAD ANTIFREEZE/ COOLANT

811877

When using do not eat or drink.  
When using do not smoke.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Physical state	: liquid
Colour	: blue
Odour	: mild
Odour Threshold	: No data available
pH	: Average 7.2
Melting point/freezing point	: No data available
Boiling point/boiling range	: 387.1 °F / 197.3 °C Calculated Phase Transition Liquid/Gas
Flash point	: > 121 °C
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: 15.3 %(V) GLP: Calculated Explosive Limit
Lower explosion limit	: 3.2 %(V) GLP: Calculated Explosive Limit
Vapour pressure	: 3 hPa (25 °C) Calculated Vapor Pressure
Relative vapour density	: No data available
Relative density	: No data available
Density	: 1.1213 g/cm <sup>3</sup> (15.6 °C)
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Thermal decomposition	: No data available

**SAFETY DATA SHEET**

Revision Date: 06/16/2016

Print Date: 10/6/2016

SDS Number: R0296767

Version: 1.1

BMW/ MINI/ MOTORRAD ANTIFREEZE/ COOLANT

811877

Viscosity  
 Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Conditions to avoid : excessive heat

Incompatible materials : Acids  
 Aldehydes  
 Alkali metals  
 Alkaline earth metals  
 Bases  
 strong alkalis  
 Strong oxidizing agents  
 Sulphur compounds

Hazardous decomposition products : Alcohols  
 Aldehydes  
 carbon dioxide and carbon monoxide  
 ethers  
 Hydrocarbons  
 Organic acids  
 ketones  
 various hydrocarbons

**SECTION 11. TOXICOLOGICAL INFORMATION**

Information on likely routes of exposure : Inhalation  
 Skin contact  
 Eye Contact  
 Ingestion

**Acute toxicity**

Harmful if swallowed.

**Product:**

Acute oral toxicity :  
 Remarks: Ingestion of medications contaminated with diethylene glycol has caused kidney failure and death in



<b>SAFETY DATA SHEET</b>	Revision Date: 06/16/2016
	Print Date: 10/6/2016
	SDS Number: R0296767
BMW/ MINI/ MOTORRAD ANTIFREEZE/ COOLANT	Version: 1.1
811877	

humans. Products containing diethylene glycol should be considered toxic by ingestion.

Acute dermal toxicity : Remarks: Skin absorption of this material (or a component) may be increased through injured skin.

**Components:**

**ETHYLENE GLYCOL:**

Acute oral toxicity : LD 50 (Rat): 6,140 mg/kg

LD50 (Human): Estimated 1.56 g/kg

Assessment: The component/mixture is classified as acute oral toxicity, category 4.

Acute inhalation toxicity : LC 50 (Rat): 10.9 mg/l  
Exposure time: 1 h  
Test atmosphere: dust/mist  
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD 50 (Rabbit): 9,530 mg/kg

**DIETHYLENE GLYCOL:**

Acute oral toxicity : LD50 (Human): Expected 1,120 mg/kg  
Target Organs: Kidney

Acute inhalation toxicity : LC50 (Rat): > 4.6 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD 50 (Rabbit): 13,300 mg/kg

**2-ETHYLHEXANOIC ACID, SODIUM SALT:**

Acute oral toxicity : LD 50 (Rat): 2,043 mg/kg  
Remarks: Information given is based on data obtained from similar substances.

Acute inhalation toxicity : Assessment: Not classified as acutely toxic by inhalation under GHS.  
Remarks: Information given is based on data obtained from similar substances.

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Assessment: Not classified as acutely toxic by dermal absorption under GHS.  
Remarks: Information given is based on data obtained from similar substances.

**DISODIUM TETRABORATE ANHYDROUS:**

<b>SAFETY DATA SHEET</b>	Revision Date: 06/16/2016
	Print Date: 10/6/2016
	SDS Number: R0296767
BMW/ MINI/ MOTORRAD ANTIFREEZE/ COOLANT	Version: 1.1
811877	

Acute inhalation toxicity : LC50 (Rat): > 2.03 mg/l  
 Exposure time: 4 h  
 Test atmosphere: dust/mist  
 Method: OECD Test Guideline 403  
 Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD 50 (Rabbit): > 2,000 mg/kg  
 Assessment: No adverse effect has been observed in acute dermal toxicity tests.

#### **Skin corrosion/irritation**

Not classified based on available information.

#### **Components:**

ETHYLENE GLYCOL:

Result: Mildly irritating to skin

DIETHYLENE GLYCOL:

Species: Human

Result: Slightly irritating to skin

2-ETHYLHEXANOIC ACID, SODIUM SALT:

Species: Rabbit

Result: Slightly irritating to skin

Remarks: Information given is based on data obtained from similar substances.

DISODIUM TETRABORATE ANHYDROUS:

Species: Rabbit

Result: No skin irritation

#### **Serious eye damage/eye irritation**

Not classified based on available information.

#### **Product:**

Remarks: Unlikely to cause eye irritation or injury.

#### **Components:**

ETHYLENE GLYCOL:

Result: Possibly irritating to eyes

DIETHYLENE GLYCOL:

Species: Rabbit

Result: Slightly irritating to eyes

2-ETHYLHEXANOIC ACID, SODIUM SALT:

Species: Rabbit

Result: Slightly irritating to eyes

Remarks: Information given is based on data obtained from similar substances.

DISODIUM TETRABORATE ANHYDROUS:

Result: Slightly irritating to eyes

#### **Respiratory or skin sensitisation**

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

<b>SAFETY DATA SHEET</b>	Revision Date: 06/16/2016
	Print Date: 10/6/2016
	SDS Number: R0296767
BMW/ MINI/ MOTORRAD ANTIFREEZE/ COOLANT	Version: 1.1
811877	

**Components:****DIETHYLENE GLYCOL:**

Test Type: Maximisation Test

Species: Guinea pig

Method: Directive 67/548/EEC, Annex V, B.6.

Result: Did not cause sensitisation on laboratory animals.

**2-ETHYLHEXANOIC ACID, SODIUM SALT:**

Test Type: Maximisation Test

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Does not cause skin sensitisation.

**DISODIUM TETRABORATE ANHYDROUS:**

Test Type: Buehler Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

**Germ cell mutagenicity**

Not classified based on available information.

**Components:****DIETHYLENE GLYCOL:**

Genotoxicity in vitro

: Test Type: Ames test

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

GLP: yes

: Test species: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 479

Result: negative

GLP: yes

Genotoxicity in vivo

: Test Type: In vivo micronucleus test

Test species: Mouse

Method: OECD Test Guideline 474

Result: negative

GLP: yes

**2-ETHYLHEXANOIC ACID, SODIUM SALT:**

Genotoxicity in vitro

: Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

Remarks: Information given is based on data obtained from similar substances.

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

<b>SAFETY DATA SHEET</b>	Revision Date: 06/16/2016
	Print Date: 10/6/2016
	SDS Number: R0296767
BMW/ MINI/ MOTORRAD ANTIFREEZE/ COOLANT	Version: 1.1
811877	

May damage fertility or the unborn child.

**Components:**

2-ETHYLHEXANOIC ACID, SODIUM SALT:

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

DISODIUM TETRABORATE ANHYDROUS:

Reproductive toxicity - Assessment : Clear evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

Not classified based on available information.

**Components:**

ETHYLENE GLYCOL:

Exposure routes: Ingestion

Target Organs: Kidney, Liver

Assessment: May cause damage to organs through prolonged or repeated exposure.

DIETHYLENE GLYCOL:

Exposure routes: Ingestion

Target Organs: Kidney

Assessment: May cause damage to organs through prolonged or repeated exposure.

**Aspiration toxicity**

Not classified based on available information.

**Experience with human exposure**

**Components:**

DIETHYLENE GLYCOL:

Liver

**Further information**

**Product:**

Remarks: No data available

**Carcinogenicity:**

**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

<b>SAFETY DATA SHEET</b>	Revision Date: 06/16/2016
	Print Date: 10/6/2016
	SDS Number: R0296767
	Version: 1.1
BMW/ MINI/ MOTORRAD ANTIFREEZE/ COOLANT	
811877	

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

#### Components:

##### ETHYLENE GLYCOL:

Toxicity to fish : LC 50 (Bluegill (*Lepomis macrochirus*)): 27,540 mg/l  
 Exposure time: 96 h  
 Method: Static  
 Remarks: Mortality

LC 50 (Fathead minnow (*Pimephales promelas*)): 8,050 mg/l  
 Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC 50 (Water flea (*Daphnia magna*)): > 10,000 mg/l  
 Exposure time: 48 h  
 Test Type: static test

##### DIETHYLENE GLYCOL:

Toxicity to fish : LC 50 (Fathead minnow (*Pimephales promelas*)): 75,210 mg/l  
 Exposure time: 96 h  
 Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates : LC 50 (Water flea (*Daphnia magna*)): > 10,000 mg/l  
 Exposure time: 24 h  
 Test Type: static test  
 Method: DIN 38412

##### 2-ETHYLHEXANOIC ACID, SODIUM SALT:

Toxicity to fish : LC50 (*Oryzias latipes* (Japanese medaka)): > 100 mg/l  
 Exposure time: 96 h  
 Test Type: semi-static test  
 Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): 910 mg/l  
 Exposure time: 48 h  
 Method: OECD Test Guideline 202

Toxicity to algae : EC50 (*Desmodesmus subspicatus* (green algae)): 49.3 mg/l  
 End point: Growth inhibition  
 Exposure time: 72 h  
 Test Type: static test  
 Remarks: Information given is based on data obtained from similar substances.

##### DISODIUM TETRABORATE ANHYDROUS:

Toxicity to fish : LC50 (*Pimephales promelas* (fathead minnow)): 79.7 mg/l  
 Exposure time: 96 h

<b>SAFETY DATA SHEET</b>		Revision Date: 06/16/2016
		Print Date: 10/6/2016
		SDS Number: R0296767
		Version: 1.1
BMW/ MINI/ MOTORRAD ANTIFREEZE/ COOLANT		
811877		

Remarks: Information refers to the main component.

Toxicity to algae : NOEC (Pseudokirchneriella subcapitata (green algae)): 17.5 mg/l  
 End point: Growth inhibition  
 Exposure time: 72 h  
 Test Type: static test  
 Method: OECD Test Guideline 201  
 Remarks: Information refers to the main component.

Toxicity to fish (Chronic toxicity) : NOEC (Danio rerio (zebra fish)): 5.6 mg/l  
 Exposure time: 34 d  
 Test Type: semi-static test  
 Method: OECD Test Guideline 210  
 Remarks: Information refers to the main component.

#### **Persistence and degradability**

##### **Components:**

##### **DIETHYLENE GLYCOL:**

Biodegradability : Result: Readily biodegradable  
 Biodegradation: 70 - 80 %  
 Exposure time: 28 d  
 Method: OECD Test Guideline 301B

##### **2-ETHYLHEXANOIC ACID, SODIUM SALT:**

Biodegradability : Result: Readily biodegradable  
 Biodegradation: > 70 %  
 Exposure time: 28 d  
 Method: OECD Test Guideline 301E  
 Remarks: Information given is based on data obtained from similar substances.

##### **DISODIUM TETRABORATE ANHYDROUS:**

Biodegradability : Result: The methods for determining biodegradability are not applicable to inorganic substances.

No data available

#### **Bioaccumulative potential**

##### **Components:**

##### **ETHYLENE GLYCOL:**

Bioaccumulation : Species: Crayfish (Procambarus)  
 Bioconcentration factor (BCF): 0.27  
 Exposure time: 61 d  
 Concentration: 1000 mg/l  
 Method: Flow through

Partition coefficient: n-octanol/water : log Pow: -1.36

##### **DIETHYLENE GLYCOL:**

Bioaccumulation : Species: Leuciscus idus (Golden orfe)  
 Bioconcentration factor (BCF): 100

Partition coefficient: n- : log Pow: -1.47

<b>SAFETY DATA SHEET</b>	Revision Date: 06/16/2016
	Print Date: 10/6/2016
	SDS Number: R0296767
BMW/ MINI/ MOTORRAD ANTIFREEZE/ COOLANT	Version: 1.1
811877	

octanol/water

2-ETHYLHEXANOIC ACID, SODIUM SALT:  
 Partition coefficient: n- : log Pow: 1.3  
 octanol/water

No data available

**Mobility in soil**

**Components:**

No data available

**Other adverse effects**

No data available

**Product:**

Additional ecological : No data available  
 information

**Components:**

---

## SECTION 13. DISPOSAL CONSIDERATIONS

**Disposal methods**

General advice : Do not dispose of waste into sewer.  
 Do not contaminate ponds, waterways or ditches with  
 chemical or used container.  
 Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and  
 federal regulations.

Contaminated packaging : Empty remaining contents.  
 Dispose of as unused product.  
 Empty containers should be taken to an approved waste  
 handling site for recycling or disposal.  
 Do not re-use empty containers.

---

## SECTION 14. TRANSPORT INFORMATION

**International transport regulations**

**REGULATION**

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

**U.S. DOT - ROAD**

Not dangerous goods

**CFR\_RAIL\_C**

Not dangerous goods

**SAFETY DATA SHEET**

Revision Date: 06/16/2016

Print Date: 10/6/2016

SDS Number: R0296767

Version: 1.1

BMW/ MINI/ MOTORRAD ANTIFREEZE/ COOLANT

811877

**U.S. DOT - INLAND WATERWAYS**

Not dangerous goods

**TDG\_ROAD\_C**

Not dangerous goods

**TDG\_RAIL\_C**

Not dangerous goods

**TDG\_INWT\_C**

Not dangerous goods

**INTERNATIONAL MARITIME DANGEROUS GOODS**

Not dangerous goods

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO**

Not dangerous goods

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER**

Not dangerous goods

**MX\_DG**

Not dangerous goods

**\*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant

no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

**SECTION 15. REGULATORY INFORMATION****EPCRA - Emergency Planning and Community Right-to-Know Act****CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ETHYLENE GLYCOL	107-21-1	5000	5357.294009

**SARA 311/312 Hazards** : Acute Health Hazard  
Chronic Health Hazard



**SAFETY DATA SHEET**

Revision Date: 06/16/2016

Print Date: 10/6/2016

SDS Number: R0296767

Version: 1.1

BMW/ MINI/ MOTORRAD ANTIFREEZE/ COOLANT

811877

**SARA 313 Component(s)**

ETHYLENE GLYCOL 107-21-1 93.33 %

**California Prop 65**

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

ETHYLENE GLYCOL 107-21-1

**The components of this product are reported in the following inventories:**

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : Not in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

NZIOC : Not in compliance with the inventory

**Inventories**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

**SECTION 16. OTHER INFORMATION****Further information**

Revision Date: 06/16/2016

**NFPA:****HMIS III:**

**SAFETY DATA SHEET**

Revision Date: 06/16/2016

Print Date: 10/6/2016

SDS Number: R0296767

Version: 1.1

BMW/ MINI/ MOTORRAD ANTIFREEZE/ COOLANT

811877

	<table border="1"> <tr> <td style="background-color: blue; color: white;"><b>HEALTH</b></td> <td style="text-align: center;"><b>2</b></td> </tr> <tr> <td style="background-color: red; color: white;"><b>FLAMMABILITY</b></td> <td style="text-align: center;"><b>1</b></td> </tr> <tr> <td style="background-color: yellow; color: black;"><b>PHYSICAL HAZARD</b></td> <td style="text-align: center;"><b>0</b></td> </tr> </table> <p>0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	<b>HEALTH</b>	<b>2</b>	<b>FLAMMABILITY</b>	<b>1</b>	<b>PHYSICAL HAZARD</b>	<b>0</b>
<b>HEALTH</b>	<b>2</b>						
<b>FLAMMABILITY</b>	<b>1</b>						
<b>PHYSICAL HAZARD</b>	<b>0</b>						

**NFPA Flammable and Combustible Liquids Classification**

Combustible Liquid Class IIIB

**Full text of H-Statements**

H302	Harmful if swallowed.
H360	May damage fertility or the unborn child.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure if swallowed.

Sources of key data used to compile the Safety Data Sheet

Supplier internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

**SAFETY DATA SHEET**

Revision Date: 06/16/2016

Print Date: 10/6/2016

SDS Number: R0296767

Version: 1.1


BMW/ MINI/ MOTORRAD ANTIFREEZE/ COOLANT

811877

ICAO : International Civil Aviation Organization  
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"  
 IMDG : International Maritime Code for Dangerous Goods  
 ISO : International Organization for Standardization  
 logPow : octanol-water partition coefficient  
 LCxx : Lethal Concentration, for xx percent of test population  
 LDxx : Lethal Dose, for xx percent of test population.  
 ICxx : Inhibitory Concentration for xx of a substance  
 Ecxx : Effective Concentration of xx  
 N.O.S.: Not Otherwise Specified  
 OECD : Organization for Economic Co-operation and Development  
 OEL : Occupational Exposure Limit  
 P-Statement : Precautionary Statement  
 PBT : Persistent , Bioaccumulative and Toxic  
 PPE : Personal Protective Equipment  
 STEL : Short-term exposure limit  
 STOT : Specific Target Organ Toxicity  
 TLV : Threshold Limit Value  
 TWA : Time-weighted average  
 vPvB : Very Persistent and Very Bioaccumulative  
 WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act  
 DOT : Department of Transportation  
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act  
 HMIRC : Hazardous Materials Information Review Commission  
 HMIS : Hazardous Materials Identification System  
 NFPA : National Fire Protection Association  
 NIOSH : National Institute for Occupational Safety and Health  
 OSHA : Occupational Safety and Health Administration  
 PMRA : Health Canada Pest Management Regulatory Agency  
 RTK : Right to Know  
 WHMIS : Workplace Hazardous Materials Information System

122875  
246918



DIE CUT DIMENSIONS +/- .007"

	<b>CUSTOMER DESCRIPTION:</b>				<p><b>SEE JOB TICKET</b></p>
	<b>CUSTOMER:</b> Kem Krest		<b>PROOF DATE:</b> 9/19/2016		
	<b>CUSTOMER P/N:</b> 122875		<b>STOCK:</b>		
	<b>ITEM NUMBER:</b> 246918	<b>PROOF VERSION:</b> v2	<b>ARTIST:</b> logan	<b>IN. REV.:</b> A	
	<b>SO NUMBER:</b> 544041	<b>SIZE:</b> 4.500" x 3.250"	<b>CORNER RADIUS:</b> .125		
	<b>APPROVED</b> <input type="checkbox"/> <b>NEW PROOF NEEDED</b> <input type="checkbox"/>		<b>AUTHORIZED SIGNATURE:</b>		

**Ink Colors:** Due to color printer and monitor differences, swatches on this proof do not represent exact color. Pantone, similar ink books, or supplied samples will be used for color matching on press.



This proof has been prepared based on your specifications and our minimum press requirements. It is your responsibility to review and approve this proof. After review, please check the appropriate box, sign and date where indicated and return a copy of this proof or an email to your Customer Service Representative acknowledging your approval of this Proof Version with this Proof Version number and the Item Number included in the subject line of your email to FORTIS SOLUTIONS GROUP, LLC, or its applicable subsidiary or affiliate ("FORTIS"), for production or reproofing. By failing to expressly reject this proof and notify FORTIS of the rejection, you agree that the proof is in accordance with your specifications.

All sales of products are subject to the Fortis Solutions Group Standard Terms and Conditions of Sale set forth at [FortisSolutionsGroup.com](http://FortisSolutionsGroup.com) as of the date hereof (the "Standard Terms"), which Standard Terms are incorporated herein by reference. Without in any way limiting the Standard Terms, FORTIS is not responsible for the scannability of barcodes below the recommended print size and quiet zone, and FORTIS shall have no liability for the content within the Nutrition Facts Panel and Drug and Supplemental Facts Panel including claims, omissions, incorrect values or deviations from legal size requirements within the panels. In order to keep our files current and provide high quality art and service, FORTIS will bill for artwork and/or proofs that have not gone to print within thirty days of submittal to the customer.

122876  
246919

**BMW Motorrad**

**WARNING!** HARMFUL OR FATAL IF SWALLOWED OR INHALED. MAY DAMAGE FERTILITY OR HARM THE UNBORN CHILD. MAY CAUSE KIDNEY, LIVER AND NERVOUS SYSTEM DAMAGE. Do not inhale vapor or mist. Do not swallow or ingest antifreeze or antifreeze solutions. Use with adequate ventilation. **FIRST AID:** For skin or eye contact, flush with water for at least 15 minutes while removing contaminated clothing. If inhaled, remove victim to fresh air. If ingested, call physician immediately.  
SDS available to professional user upon request.

**DIRECTIONS:** Refer to the proper vehicle service manual for use and recommended dilutions. Dispose of properly. Do not discard into storm sewers, septic systems, or onto the ground. Do not reuse this container or store in unlabeled containers. **CONTAINS:** Ethylene Glycol (107-21-1) and Diethylene Glycol (111-46-6). **WARNING:** This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.  
KEEP OUT OF REACH OF CHILDREN AND ANIMALS.

**FULL STRENGTH - MUST BE DILUTED**

PROTECTION CHART		
% Antifreeze	Freezing Point, °F / °C	Boiling Point, °F / °C
60	-62 / -52	272 / 134
50	-34 / -37	265 / 130

Do not exceed an antifreeze percentage of 60%

**Made in USA.**  
Distributed by BMW of North America, LLC., BMW Motorrad USA  
Woodcliff Lake, NJ 07677  
For 24-hour emergency assistance, call the 3E Company at  
1-877-472-1724. Please provide product tracking code: 9457.

81 22 0 049 923

THE ULTIMATE PRODUCTS  
FOR YOUR RIDING MACHINE

↑ 4.5000 in ↓

← 3.2500 in →

WEB DIRECTION

DIE CUT DIMENSIONS +/- .007"

<div style="display: flex; flex-direction: column; align-items: center;"> <div style="width: 20px; height: 20px; background-color: cyan; margin-bottom: 5px;"></div> C           </div> <div style="display: flex; flex-direction: column; align-items: center;"> <div style="width: 20px; height: 20px; background-color: black; margin-bottom: 5px;"></div> K           </div> <div style="display: flex; flex-direction: column; align-items: center;"> <div style="width: 20px; height: 20px; background-color: magenta; margin-bottom: 5px;"></div> DIE           </div>	<b>CUSTOMER DESCRIPTION:</b>			
	<b>CUSTOMER:</b> Kem Krest		<b>PROOF DATE:</b> 9/19/2016	<b>UNWIND POSITION:</b>
	<b>CUSTOMER P/N:</b> 122876		<b>STOCK:</b>	<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">             Wound Out 3         </div> <div style="font-size: 2em; font-weight: bold;">OR</div> <div style="text-align: center;">             Wound Out 4         </div> </div> <p style="font-weight: bold; margin-top: 5px;">SEE JOB TICKET</p>
	<b>ITEM NUMBER:</b> 246919	<b>PROOF VERSION:</b> v2	<b>ARTIST: IN. REV.:</b> logan A	
	<b>SO NUMBER:</b> 544041	<b>SIZE:</b> 4.500" x 3.250"	<b>CORNER RADIUS:</b> .125	
	<b>APPROVED</b> <input type="checkbox"/> <b>NEW PROOF NEEDED</b> <input type="checkbox"/>		<b>AUTHORIZED SIGNATURE:</b>	<b>DATE:</b>

**Ink Colors:** Due to color printer and monitor differences, swatches on this proof do not represent exact color. Pantone, similar ink books, or supplied samples will be used for color matching on press.



This proof has been prepared based on your specifications and our minimum press requirements. It is your responsibility to review and approve this proof. After review, please check the appropriate box, sign and date where indicated and return a copy of this proof or an email to your Customer Service Representative acknowledging your approval of this Proof Version with this Proof Version number and the Item Number included in the subject line of your email to FORTIS SOLUTIONS GROUP, LLC, or its applicable subsidiary or affiliate ("FORTIS"), for production or reproofing. By failing to expressly reject this proof and notify FORTIS of the rejection, you agree that the proof is in accordance with your specifications.

All sales of products are subject to the Fortis Solutions Group Standard Terms and Conditions of Sale set forth at [FortisSolutionsGroup.com](http://FortisSolutionsGroup.com) as of the date hereof (the "Standard Terms"), which Standard Terms are incorporated herein by reference. Without in any way limiting the Standard Terms, FORTIS is not responsible for the scannability of barcodes below the recommended print size and quiet zone, and FORTIS shall have no liability for the content within the Nutrition Facts Panel and Drug and Supplemental Facts Panel including claims, omissions, incorrect values or deviations from legal size requirements within the panels. In order to keep our files current and provide high quality art and service, FORTIS will bill for artwork and/or proofs that have not gone to print within thirty days of submittal to the customer.