Version 2.6 Revision Date 10/01/2023 Print Date 07/15/2024

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name	ZEP 40 NON-STREAKING CLEANER 201	V18 12CT
Material number	: 0000000000014401	
Manufacturer or supplier's	tails	
Company	: Zep Inc.	
Address	: 350 Joe Frank Harris Parkway, SE Emerson, GA 30137	
Telephone	: Compliance Services - 877-428-9937	

Emergency telephone numbers			
For SDS Information	:	Compliance Services - 877-428-9937	
For a Medical Emergency	:	877-541-2016 Toll Free - All Calls Recorded	
For a Transportation Emergency	:	CHEMTREC: 800-424-9300 - All Calls Recorded. In the District of Columbia 202-483-7616	

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	colourless, clear
Odour	alcohol-like, slight

GHS Class	ssification
------------------	-------------

Gases under pressure Eye irritation	: Liquefied gas : Category 2A
GHS label elements	
Hazard pictograms	: Gas cy linder Gas cy linder Exclamation mark
Signal word	: Warning
Hazard statements	: H280 Contains gas under pressure; may explode if heated. H319 Causes serious eye irritation.
Precautionary statements	 Prevention: P264 Wash skin thoroughly after handling. P280 Wear eye protection/ face protection. Response: P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

Version 2.6

Revision Date 10/01/2023

Print Date 07/15/2024

easy to do. Continue rinsing. P337 + P313 If eye irritation persists: Get medical advice/ attention. **Storage:** P403 Store in a well-ventilated place. P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
ethanol	64-17-5	>= 10 - < 20
butane	106-97-8	>= 3 - < 5
2-butoxyethanol	111-76-2	>= 1 - < 3
propane	74-98-6	>= 1 - < 3

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice	Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.	
If inhaled	If unconscious, place in recovery position and s advice. If symptoms persist, call a physician.	seek medical
In case of skin contact	Wash off immediately with plenty of water for a minutes. If skin irritation persists, call a physician.	t least 15
In case of eye contact	Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. If in eyes, rinse with water for 15 minutes.	
If swallowed	Keep respiratory tract clear. Never give anything by mouth to an unconsciou If symptoms persist, call a physician. DO NOT induce vomiting unless directed to do physician or poison control center.	
Most important symptoms and effects, both acute and delayed	Effects are immediate and delayed. Symptoms may include irritation, redness, pain Causes serious eye irritation. Review section 2 of SDS to see all potential ha	

ersion 2.6		Revision Date 10/01/2023	Print Date 07/15/2024
Notes to physician	:	Treat symptomatically. Symptoms	may be delayed.
CTION 5. FIREFIGHTING MEAS	SUI	RES	
Suitable extinguishing media	:	Water spray jet Carbon dioxide (CO2) Alcohol-resistant foam Dry chemical	
Unsuitable extinguishing media	:	High volume water jet	
Specific hazards during firefighting	:	Do not allow run-off from fire fightin courses.	g to enter drains or water
Hazardous combustion products	:	Carbon dioxide (CO2) Carbon monoxide Smoke	
Specific extinguishing methods	:	Use extinguishing measures that an circumstances and the surrounding	
Further information	:	Collect contaminated fire extinguish must not be discharged into drains. Fire residues and contaminated fire be disposed of in accordance with	extinguishing water must

Special protective equipment : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Refer to protective measures listed in sections 7 and 8. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains, inform respective authorities.
Methods and materials for containment and cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal.

SECTION 7. HANDLING AND STORAGE

Version 2.6	Revision Date 10/01/2023	Print Date 07/15/2024
Advice on safe handling	 Avoid contact with skin and eyes. For personal protection see section Smoking, eating and drinking shoul application area. Always replace cap after use. Dispose of rinse water in accordance regulations. Avoid exposure - obtain special ins Take precautionary measures agai Do not breathe vapours or spray measures 	Id be prohibited in the ce with local and national structions before use. nst static discharges.
Conditions for safe storage	 BEWARE: Aerosol is pressurized. exposure and temperatures over 50 or throw into fire even after use. Do red-hot objects. Observe label precautions. Keep in a dry, cool and well-ventilat Electrical installations / working ma the technological safety standards. 	0 °C. Do not open by force o not spray on flames or ted place.
Materials to avoid	: Do not freeze. Strong oxidizing agents	

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components	CAS-No.	Value type	Control	Basis
Components	0/10/110.	(Form of	parameters /	Dasis
		exposure)	Permissible	
		, ,	concentration	
ethanol	64-17-5	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,900 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,900 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,900 mg/m3	OSHA P0
		STEL	1,000 ppm	ACGIH
		PEL	1,000 ppm 1,900 mg/m3	CAL PEL
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
		PEL	800 ppm 1,900 mg/m3	CAL PEL
		STEL	1,000 ppm	ACGIH
2-butoxyethanol	111-76-2	TWA	20 ppm	ACGIH
		TWA	5 ppm 24 mg/m3	NIOSH REL
		TWA	50 ppm 240 mg/m3	OSHA Z-1
		TWA	25 ppm 120 mg/m3	OSHA P0
		PEL	20 ppm	CAL PEL

Components with workplace control parameters

Version 2.6

Revision Date 10/01/2023

Print Date 07/15/2024

			97 mg/m3	
propane	74-98-6	TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
		PEL	1,000 ppm 1,800 mg/m3	CAL PEL

Biological occupational exposure limits

Component	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
2-BUTOXYETHANOL	111-76-2	Butoxyacetic	Urine	End of	200.mg/g	ACGIH BEI
		acid (BAA)		shift (As	Creatinine	
				soon as		
				possible		
				after		
				exposure		
				ceases)		

Engineering measures	effective ventilation in all processing areas	
Personal protective equipme	t	
Respiratory protection	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrate that exposures are within recommended exposure guidelines	
Hand protection Material Remarks	Protective gloves The suitability for a specific workplace should be discussed with the producers of the protective gloves.	
Eye protection	Tightly fitting safety goggles	
Skin and body protection	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place	·-
Hygiene measures	When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Aerosol containing a liquefied gas
Colour	: colourless, clear
Odour	: alcohol-like, slight
Odour Threshold	: No data available

Version 2.6	Revision Date 10/01/2023	Print Date 07/15/2024
рН	: 10.5 - 11.5	
Melting point/freezing point	: Not applicable	
Boiling point	: Not applicable	
Flash point	: Not applicable	
Evaporation rate	: 1 n-Butyl Acetate = 1.0	
Flammability (solid, gas, liquid)	: The product is not flammable.	
Upper explosion limit	: Not applicable	
Lower explosion limit	: Not applicable	
Vapour pressure	: No data available	
Relative vapour density	: No data available	
Density	: 1.1 g/cm3	
Solubility(ies)		
Water solubility	: soluble	
Solubility in other solvents	: not determined	
Partition coefficient: n- octanol/water	: No data available	
Auto-ignition temperature	: not determined	
Thermal decomposition	: No data available	
Viscosity		
Viscosity, kinematic	: Not applicable	
Heat of combustion	: 7.94 kJ/g	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

Version 2.6

Revision Date 10/01/2023

Print Date 07/15/2024

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition	: None known.
Symptoms of Overexposure	 Effects are immediate and delayed. Symptoms may include irritation, redness, pain, and rash. Causes serious eye irritation. Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.
Carcinogenicity:	
IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed
ACGIH	human carcinogen by IARC. Confirmed animal carcinogen with unknown relevance to humans ethanol 64-17-5
06/14	2-butoxyethanol 111-76-2
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
Acute toxicity	
Product:	
Acute oral toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method
Acute inhalation toxicity	: Acute toxicity estimate : 60 mg/l
	Exposure time: 4 h Test atmosphere: dust/mist
	Method: Calculation method
Acute dermal toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method
Components:	
ethanol:	
Acute oral toxicity	: LD50 Oral Rat: 7,060 mg/kg
Acute inhalation toxicity	: LC50 Rat: 124.7 mg/l
	Exposure time: 4 h Test atmosphere: vapour

Version 2.6	Revision Date 10/01/2023	Print Date 07/15/2024
2-butoxyethanol:		
Acute oral toxicity	: LD50 Oral Rat: 880 mg/kg	
Acute dermal toxicity	: LD50 Dermal Rabbit: 1,060 mg/kg	
Skin corrosion/irritation		
Product:		
Remarks: May cause skin i	rritation and/or dermatitis.	
Serious eye damage/eye irrita	tion	
Product:		
Remarks: Severe eye irritat	ion	
Respiratory or skin sensitisation	on	
lo data available		
Serm cell mutagenicity		
lo data available		
Carcinogenicity		
lo data available		
Reproductive toxicity		
lo data available		
STOT - single exposure		
lo data available		
STOT - repeated exposure		
lo data available		
Aspiration toxicity		
lo data available		
Further information		
Product:		
Remarks: No data availa	ble	

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Version 2.6	Revision Date 10/01/2023	Print Date 07/15/2024
Persistence and degradability		
No data available Bioaccumulative potential		
Product:		
Partition coefficient: n- octanol/water <u>Components:</u> ethanol :	: Remarks: No data available	
Partition coefficient: n- octanol/water butane :	: Remarks: No data available	
Partition coefficient: n- octanol/water	: Pow: 2.89	
Mobility in soil		
No data available		
Other adverse effects		
No data available <u> Product:</u>		
Regulation	40 CFR Protection of Environmer Stratospheric Ozone - CAA Secti Substances	,
Remarks	This product neither contains, no with a Class I or Class II ODS as Clean Air Act Section 602 (40 CF + B).	defined by the U.S.
Additional ecological information	: An environmental hazard cannot event of unprofessional handling aquatic life.	

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of in accordance with local regulations.
Contaminated packaging	 Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):

Version 2.6

Revision Date 10/01/2023

Print Date 07/15/2024

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IATA (Cargo Air): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list

: No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
ammonia, aqueous solution	1336-21-6	1000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	:	Gases under pressure Serious eye damage or eye irritation	
SARA 302	:	No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.	
SARA 313	:	The following components are subject to reporting levelsestablished by SARA Title III, Section 313:2-butoxyethanol111-76-2	2.5 %
California Prop. 65			

Version 2.6

Revision Date 10/01/2023

Print Date 07/15/2024

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

DSLAll components of this product are on the Canadian DSLTSCAOn TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

Version 2.6

Revision Date 10/01/2023

Print Date 07/15/2024

Further information

NFPA:



0 = not significant, 1 =Slight,

2 = Moderate, 3 = High


4 = Extreme

HMIS III:



0 = not significant, 1 =Slight,

- 2 = Moderate, 3 = High 4 = Extreme, * = Chronic



Version:	2.6	
Revision Date:	10/01/2023	

Version 2.6

Revision Date 10/01/2023

Print Date 07/15/2024

Print Date: 07/15/2024

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.