

SAFETY DATA SHEET

BJ1178 TOY EFITANK ADDITIVE 289-EFI34 - 6.76 FL OZ

Version 1.1

Revision Date 10/01/2023

Print Date 10/03/2023

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : BJ1178 TOY EFI TANK ADDITIVE 289-EFI34 - 6.76 FL OZ

Material number : 000000000500202000

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE
Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation
Emergency : CHEMTREC: 800-424-9300 - All Calls Recorded.
In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	liquid
Colour	light yellow
Odour	aromatic, hydrocarbon-like

GHS Classification

Flammable liquids : Category 4
Skin sensitisation : Category 1
Serious eye damage/eye irritation : Category 1
Skin irritation : Category 2
Acute toxicity : Category 5
Carcinogenicity : Category 2
Specific target organ toxicity - repeated exposure : Category 2 (Eyes, Blood, Liver)
Specific target organ toxicity - single exposure : Category 1 (Blood, Eyes, respiratory tract irritation)
Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :



Signal word : Warning

SAFETY DATA SHEET

BJ1178 TOY EFITANK ADDITIVE 289-EFI34 - 6.76 FL OZ

Version 1.1

Revision Date 10/01/2023

Print Date 10/03/2023

Hazard statements : H227 Combustible liquid.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H351 Suspected of causing cancer.
H371 May cause damage to organs.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
Response:
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
P331 Do NOT induce vomiting.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
Storage:
P403 + P235 Store in a well-ventilated place. Keep cool.
Disposal:
P501 Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
Alcohols, C12-14-secondary, ethoxylated	84133-50-6	>= 30 - < 50
Solvent naphtha (petroleum), heavy arom.	64742-94-5	>= 5 - < 10

SAFETY DATA SHEET

BJ1178 TOY EFITANK ADDITIVE 289-EFI34 - 6.76 FL OZ

Version 1.1

Revision Date 10/01/2023

Print Date 10/03/2023

2-(2-butoxyethoxy)ethanol	112-34-5	>= 5 - < 10
trimethylbenzene	25551-13-7	>= 1 - < 3
1,2,4-trimethylbenzene	95-63-6	>= 1 - < 3
naphthalene	91-20-3	>= 1 - < 3

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
Consult a physician after significant exposure.
- In case of skin contact : If skin irritation persists, call a physician.
Wash off immediately with plenty of water for at least 15 minutes.
If on clothes, remove clothes.
- In case of eye contact : Rinse immediately with plenty of water for at least 15 minutes.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
DO NOT induce vomiting unless directed to do so by a physician or poison control center.
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Chronic effects are delayed and symptoms may not be observed during an exposure.
Effects are dependent on exposure (dose, concentration, contact time).
Aspiration may cause pulmonary oedema and pneumonitis.
Symptoms may include shortness of breath, dry cough, and irritation of the nose, eyes, lips, mouth, and throat.
May be fatal if swallowed and enters airways.
Suspected of causing cancer.
Review section 2 of SDS to see all potential hazards.
- Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO2)
Dry chemical
- Unsuitable extinguishing : High volume water jet

SAFETY DATA SHEET

BJ1178 TOY EFITANK ADDITIVE 289-EFI34 - 6.76 FL OZ

Version 1.1

Revision Date 10/01/2023

Print Date 10/03/2023

media

- | | | |
|---|---|---|
| Specific hazards during firefighting | : | Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products | : | Carbon dioxide (CO ₂)
Carbon monoxide
Smoke
Nitrogen oxides (NO _x) |
| Specific extinguishing methods | : | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Further information | : | Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers. |
| Special protective equipment for firefighters | : | Wear self-contained breathing apparatus for firefighting if necessary. |

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | | |
|---|---|---|
| Personal precautions, protective equipment and emergency procedures | : | Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. |
| Environmental precautions | : | Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains, inform respective authorities. |
| Methods and materials for containment and cleaning up | : | Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). |

SECTION 7. HANDLING AND STORAGE

- | | | |
|-------------------------|---|---|
| Advice on safe handling | : | Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours or spray mist.
Dispose of rinse water in accordance with local and national |
|-------------------------|---|---|

SAFETY DATA SHEET**BJ1178 TOY EFITANK ADDITIVE 289-EFI34 - 6.76 FL OZ**

Version 1.1

Revision Date 10/01/2023

Print Date 10/03/2023

regulations.

Conditions for safe storage : No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Store and keep away from, oxidizing agents and acids.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
2-(2-butoxyethoxy)ethanol	112-34-5	TWA (Inhalable fraction and vapor)	10 ppm	ACGIH
trimethylbenzene	25551-13-7	TWA	25 ppm	ACGIH
		TWA	25 ppm 125 mg/m ³	OSHA P0
		PEL	25 ppm 125 mg/m ³	CAL PEL
1,2,4-trimethylbenzene	95-63-6	TWA	25 ppm 125 mg/m ³	NIOSH REL
naphthalene	91-20-3	TWA	10 ppm	ACGIH
		STEL	15 ppm	ACGIH
		TWA	10 ppm 50 mg/m ³	NIOSH REL
		ST	15 ppm 75 mg/m ³	NIOSH REL
		TWA	10 ppm 50 mg/m ³	OSHA Z-1
		TWA	10 ppm 50 mg/m ³	OSHA P0
		STEL	15 ppm 75 mg/m ³	OSHA P0
		PEL	0.1 ppm 0.5 mg/m ³	CAL PEL

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

SAFETY DATA SHEET

BJ1178 TOYEFITANK ADDITIVE 289-EFI34 - 6.76 FL OZ

Version 1.1

Revision Date 10/01/2023

Print Date 10/03/2023

Hand protection Remarks	: The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	: Ensure that eyewash stations and safety showers are close to the workstation location. Safety glasses
Skin and body protection	: Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: light yellow
Odour	: aromatic, hydrocarbon-like
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Boiling point	: > 180 °C
Flash point	: 79 °C
Upper explosion limit	: 7 %(V)
Lower explosion limit	: 0.6 %(V)
Vapour pressure	: No data available
Density	: 0.938 g/cm ³ (15 °C)
Solubility(ies)	
Water solubility	: insoluble
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: > 400 °C
Viscosity	
Viscosity, kinematic	: 18.5 mm ² /s (40 °C)

SAFETY DATA SHEET

BJ1178 TOY EFITANK ADDITIVE 289-EFI34 - 6.76 FL OZ

Version 1.1

Revision Date 10/01/2023

Print Date 10/03/2023

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Acids Strong oxidizing agents
Hazardous decomposition products	: Carbon dioxide (CO ₂) Carbon monoxide Amines Hydrocarbons Smoke

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition	: None known.
Symptoms of Overexposure	: Chronic effects are delayed and symptoms may not be observed during an exposure. Effects are dependent on exposure (dose, concentration, contact time). Aspiration may cause pulmonary oedema and pneumonitis. Symptoms may include shortness of breath, dry cough, and irritation of the nose, eyes, lips, mouth, and throat. May be fatal if swallowed and enters airways. Suspected of causing cancer. Review section 2 of SDS to see all potential hazards. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC	Group 2B: Possibly carcinogenic to humans	
ACGIH	naphthalene	91-20-3
	Confirmed animal carcinogen with unknown relevance to humans	
	naphthalene	91-20-3
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.	
NTP	Reasonably anticipated to be a human carcinogen	

SAFETY DATA SHEET

BJ1178 TOY EFITANK ADDITIVE 289-EFI34 - 6.76 FL OZ

Version 1.1

Revision Date 10/01/2023

Print Date 10/03/2023

naphthalene

91-20-3

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : 4,292 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : > 200 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Components:

Alcohols, C12-14-secondary, ethoxylated:

Acute oral toxicity : LD50 Oral Rat: > 3,000 mg/kg

Acute dermal toxicity : LD50 Dermal Rabbit: > 2,000 mg/kg

Skin corrosion/irritation

Product:

Remarks: May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

SAFETY DATA SHEET

BJ1178 TOY EFITANK ADDITIVE 289-EFI34 - 6.76 FL OZ

Version 1.1

Revision Date 10/01/2023

Print Date 10/03/2023

No data available

Further information

Product:

Remarks: Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

Product:

Partition coefficient: n-octanol/water : Remarks: No data available

Components:

Solvent naphtha (petroleum), heavy arom. :

Partition coefficient: n-octanol/water : log Pow: 4.2

2-(2-butoxyethoxy)ethanol :

Partition coefficient: n-octanol/water : Pow: 1

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

BJ1178 TOY EFITANK ADDITIVE 289-EFI34 - 6.76 FL OZ

Version 1.1

Revision Date 10/01/2023

Print Date 10/03/2023

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of in accordance with local regulations.
- Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):

UN3082, Environmentally hazardous substance, liquid, n.o.s., (POLYETHER AMINE), 9, III - Limited quantity

Transportation Regulation: IMDG (Vessel):

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (POLYETHER AMINE), 9, III, MP: (SOLVENT NAPHTHA, PETROLEUM, HEAVY AROM. (RH)) - Limited quantity

Transportation Regulation: IATA (Cargo Air):

UN3082, Environmentally hazardous substance, liquid, n.o.s., (POLYETHER AMINE), 9, III - Limited quantity

Transportation Regulation: IATA (Passenger Air):

UN3082, Environmentally hazardous substance, liquid, n.o.s., (POLYETHER AMINE), 9, III - Limited quantity

Transportation Regulation: TDG (Canada):

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (POLYETHER AMINE), 9, III - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list

: No substances are subject to a Significant New Use Rule.

The following substance(s) is/are subject to TSCA 12(b) export notification requirements:

naphthalene

91-20-3

SAFETY DATA SHEET

BJ1178 TOY EFITANK ADDITIVE 289-EFI34 - 6.76 FL OZ

Version 1.1

Revision Date 10/01/2023

Print Date 10/03/2023

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
naphthalene	91-20-3	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Skin corrosion or irritation
Serious eye damage or eye irritation
Carcinogenicity
Specific target organ toxicity (single or repeated exposure)

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

2-(2-butoxyethoxy)ethanol	112-34-5	6 %
1,2,4-trimethylbenzene	95-63-6	1.55 %
naphthalene	91-20-3	1.05 %

California Prop. 65



WARNING: This product can expose you to chemicals including naphthalene, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL
TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

SAFETY DATA SHEET

BJ1178 TOY EFITANK ADDITIVE 289-EFI34 - 6.76 FL OZ

Version 1.1

Revision Date 10/01/2023

Print Date 10/03/2023

Further information

NFPA:

HEALTH	3
FLAMMABILITY	2
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme

HMIS III:

HEALTH	2*
FLAMMABILITY	2
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms



Signal word

Hazard statements

Precautionary statements

: **Warning:**
: Combustible liquid. Causes skin irritation. Causes serious eye damage. Suspected of causing cancer. May cause damage to organs. May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.

: **Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment.

: **Response:** IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. If skin irritation or rash occurs: Get

SAFETY DATA SHEET

BJ1178 TOYEFITANK ADDITIVE 289-EFI34 - 6.76 FL OZ

Version 1.1

Revision Date 10/01/2023

Print Date 10/03/2023

medical advice/ attention. IF IN EYES: Rinse cautiously w ith water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/ attention. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage: Store in a well-ventilated place. Keep cool.

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	1.1
Revision Date:	10/01/2023
Print Date:	10/03/2023

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes.

This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.