

# SAFETY DATA SHEET

Per OSHA HCS

PAGE 1

Date SDS Printed & Reviewed: 04/27/15

Last Formula Revision Date: 12/01/05

APF

## SECTION 1: IDENTIFICATION

### PRODUCT IDENTIFIER:

VALUGARD  
UNDERCOATING  
VG-104A

OTHER MEANS OF IDENTIFICATION: (FOR CHEMTREC) FORMULA # 19N001N12A

RECOMMENDED USE OF THE CHEMICAL: AEROSOL SPRAY

### SUPPLIER DETAILS: MANUFACTURED BY:

Custom-Pak Products Inc.  
N118 W18981 Bunsen Drive  
Germantown, WI 53022  
(262) 251-6180

### MANUFACTURED FOR:

AUTOMOTIVE INTERNATIONAL INC.  
8855 BLUE ASH RD.  
CINCINNATI, OH 45242  
800-543-7156

### EMERGENCY TELEPHONE NUMBERS:

Chemtrec 24-hour Emergency Phone: (800) 424-9300

Chemtrec Foreign Emergency Phone: (703) 527-3887

## SECTION 2: HAZARDS IDENTIFICATION

### CLASSIFICATION OF THE SUBSTANCE OF MIXTURE:

Flammable Aerosols, Category 1  
Gasses Under Pressure, Category Compressed Liquid  
Skin Corrosion/Irritation, Category 2  
Serious Eye Damage/Eye Irritation, Category 2A  
Germ Cell Mutagenicity, Category 1A,1B  
Carcinogenicity, Category 1A,1B

### HAZARD PICTOGRAMS:

GHS02 Flame, GHS04 Gas Cylinder, GHS07 Exclamation Mark, GHS08 Health Hazard

### SIGNAL WORD: DANGER

### HAZARD STATEMENTS:

H222 Extremely flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H340 May cause genetic defects.  
H350 May cause cancer.

### PRECAUTIONARY STATEMENTS:

#### GENERAL & PREVENTION:

P102 Keep out of reach of children.  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/sparks/open flames. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Pressurized container: Do not pierce or burn, even after use.  
P264 Wash hands thoroughly after handling.  
P280 Wear eye protection.

### RESPONSE:

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

CONTINUED-->

**PRODUCT IDENTIFIER:**

VALUGARD  
UNDERCOATING  
VG-104A

**SECTION 2: HAZARDS IDENTIFICATION****RESPONSE:**

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

**STORAGE:**

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 degrees C/122 degrees F.

**DISPOSAL:**

P501 Dispose of contents/container in accordance with local/regional/national regulations.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

#	COMPONENT	CAS#	% by WT.
1	PETROLEUM SOLVENT	64742-47-8	37.1
2	PETROLEUM ASPHALT	8052-42-4	30.4
3	PROPANE	74-98-6	17.0
4	N-BUTANE	106-97-8	8.0
5	HEPTANE	64742-49-0	7.5

**SECTION 4 - FIRST AID MEASURES**

**Inhalation:** If inhaled: Remove victim to fresh air and keep comfortable for breathing

**Skin Contact:** If on skin: Wash with plenty of soap and water. Call a poison center/doctor if you feel unwell.  
Remove contaminated clothing and wash before reuse.

**Eye Contact:** If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

**Ingestion:** If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting unless directed to do so by medical personnel.

**MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:**

See Section 11 Information on toxicological effects.

**INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT REQUIRED:**

Treat symptomatically.

**SECTION 5 - FIRE-FIGHTING MEASURES**

**Suitable Extinguishing Media:** CO2 (Carbon Dioxide), dry chemical, or water fog.

**Unsuitable Extinguishing Media:** Water spray may be unsuitable. However, if water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible explosion when exposed to extreme heat.

**Specific Hazards Arising From the Chemical:** Closed containers exposed to heat from fire may build pressure and explode. Products of combustion may include, and are not limited to: oxides of carbon.

**Special Protective Equipment and Precautions for Fire-Fighters:** Full protective equipment including self-contained breathing apparatus should be used.

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

**Personal Precautions:** Use personal protection recommended in Section 8.

**Environmental Precautions:** None known.

**Methods of Containment:** Absorb spilled liquid in suitable material.

**Methods for Clean-Up:** Use spark-proof tools to sweep or scrape up and containerize.

**Other Information:** Ensure adequate ventilation.

CONTINUED--&gt;

# SAFETY DATA SHEET Per OSHA HCS

PAGE 3

## PRODUCT IDENTIFIER:

VALUGARD  
UNDERCOATING  
VG-104A

---

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

### Other Information:

## SECTION 7 - HANDLING AND STORAGE

### Precautions for Safe Handling:

Vapors may ignite explosively. Prevent buildup of vapors. Keep from sparks, heat, flame or other heat sources. Do not smoke. Turn off pilot lights, heaters, electric motors and other sources of ignition during use and until all vapors are gone. do not puncture or incinerate/burn container.

### Conditions for Safe Storage, Including Any Incompatibilities:

Protect from sunlight. Do not expose to temperatures exceeding 50 degrees C / 122 degrees F.  
Store in a well-ventilated place. Keep container tightly closed when not in use.

## SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

### CONTROL PARAMETERS

#	COMPONENT	ACGIH TLV-STEL	ACGIH TLV-TWA	OSHA PEL-TWA
1	PETROLEUM SOLVENT	N/E	N/E	400 ppm
2	PETROLEUM ASPHALT	N/E	N/E	N/E
3	PROPANE	1800 ppm	2500 ppm	1000 ppm
4	N-BUTANE	N/E	800 ppm	800 ppm
5	HEPTANE	500 ppm	400 ppm	500 ppm

**APPROPRIATE ENGINEERING CONTROLS:** Provide adequate ventilation to keep air contamination below OSHA permissible exposure limits and ACGIH TLV exposure levels.

**EYE/FACE PROTECTION:** Wear safety glasses with side shields. Have eye wash facilities immediately available.

**SKIN PROTECTION:** Chemical resistant gloves if contact is likely.

**RESPIRATORY PROTECTION:** Use NIOSH-approved air-purifying respirator with organic cartridge or canister if exposure cannot be controlled within applicable limits with ventilation.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

**PHYSICAL STATE:** Aerosol - Pressurized Liquid  
**COLOR:** See product identification  
**ODOR:** SOLVENT ODOR  
**ODOR THRESHOLD:** No data available  
**pH:** No data available  
**FREEZING POINT:** Not Established (mixture)  
**BOILING POINT:** N.A. (Pressurized mixture)  
**FLASH POINT:** <-18C (-0.4F) C.C.  
**EVAPORATION RATE:** Faster than ether  
**UPPER FLAMMABILITY LIMIT:** Not Established (mixture)  
**LOWER FLAMMABILITY LIMIT:** Not Established (mixture)  
**VAPOR PRESSURE:** Approximately 50 psig @ 10 C (70 F)  
**SPECIFIC GRAVITY:** 0.786  
**SOLUBILITY (WATER):** Negligible  
**VOC PERCENT BY WEIGHT:** 69.63  
**HAPS PERCENT BY WEIGHT:** 0  
**MIR NUMBER (EPA AND CA):**

## SECTION 10: STABILITY AND REACTIVITY

CONTINUED-->

# SAFETY DATA SHEET Per OSHA HCS

**PRODUCT IDENTIFIER:**

VALUGARD  
UNDERCOATING  
VG-104A

**SECTION 10: STABILITY AND REACTIVITY**

**CHEMICAL STABILITY:** Stable under normal conditions.  
**POSSIBILITY OF HAZARDOUS REACTIONS:** Will not occur.  
**CONDITIONS TO AVOID:** Keep away from heat, sparks, and flames.  
**INCOMPATIBLE MATERIALS:** Strong oxidizing agents.  
**HAZARDOUS DECOMPOSITION PRODUCTS:** by fire - Carbon Dioxide and Carbon Monoxide

**SECTION 11: TOXICOLOGICAL INFORMATION**

**LIKELY ROUTES OF ENTRY:** Skin contact, Inhalation, Eye contact, Ingestion  
**SIGNS AND SYMPTOMS OF EXPOSURE:**  
**Skin Contact:** Signs/symptoms may include localized redness, itching, drying and cracking of skin.  
**Inhalation:** Intentional concentration and inhalation may be harmful or fatal.  
**Eye Contact:** Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.  
**Ingestion:** Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.  
**TARGET ORGANS POTENTIALLY AFFECTED BY EXPOSURE:**  
Central nervous system, Kidneys, Lungs, Liver, Eyes, Respiratory Tract, Skin

**TOXICOLOGICAL DATA:**

#	COMPONENT	LD50 ORAL	LD50 DERMAL
1.	PETROLEUM SOLVENT	N/E	N/E
2.	PETROLEUM ASPHALT	N/E	N/E
3.	PROPANE	1000	1800
4.	N-BUTANE	N/E	N/E
5.	HEPTANE	N/E	N/E

\* May cause cancer.

**SECTION 12: ECOLOGICAL INFORMATION**

No data available.

**SECTION 13: DISPOSAL CONSIDERATIONS**

Dispose of contents/container in accordance with local/regional/national regulations. Do not puncture, incinerate, or place container in trash compactor.

**SECTION 14: TRANSPORTATION INFORMATION****GROUND (D.O.T./49 CFR):**

**UN NUMBER:** UN1950  
**Proper Shipping Name:** AEROSOLS ("FLAMMABLE" is optional to add after AEROSOLS)  
**Transport Hazard Class(es):** 2.1  
**Packing Group:** - (not applicable)  
**Hazard Label:** Limited Quantity (LTD QTY) label -- see 49 CFR 172.315  
**Shipping Papers Format:** UN1950, AEROSOLS, FLAMMABLE, 2.1 LTD QTY

**AIR (IATA):**

**UN NUMBER:** UN1950  
**Proper Shipping Name:** AEROSOLS, FLAMMABLE  
**Transport Hazard Class(es):** 2.1  
**Packing Group:** - (not applicable)  
**Hazard Labels:** LTD QTY label with "Y" in it, and Flammable Gas Label

CONTINUED--&gt;

**PRODUCT IDENTIFIER:**

VALUGARD  
UNDERCOATING  
VG-104A

=====

**SECTION 14: TRANSPORTATION INFORMATION**

**WATER (IMDG):**

**UN NUMBER:** UN1950  
**Proper Shipping Name:** AEROSOLS  
**Transport Hazard Class(es):** 2.1  
**Hazard Label:** LTD QTY label (see IMDG 3.4.5.1)  
**Packing Instruction:** P003, LP02  
**Ems:** F-D, S-U  
**Stowage and Segregation:** Category A  
**Shipping Papers format:** UN1950, AEROSOLS, 2.1, (-18 C c.c.), LTD QTY  
**Environmental Hazards:** No component of this product is a listed Marine Pollutant (49 CFR 172,101,Appendix B).

**SECTION 15: REGULATORY INFORMATION**

**International Chemical Inventory**

All components of this product are listed on or exempt from the following inventories:

TSCA (United States), CEPA/DSL (Canada), AICS (Australia), IECSC (China)

**SECTION 16: OTHER INFORMATION**

**REVISION DATE:** 12/01/05

**HMIS & NFPA Hazard Scale:**

0=minimal, 1=slight, 2=moderate, 3=serious, 4=severe

HMIS (American Coatings Association's Hazardous Material Identification System):

Health = 2      Flammability = 4      Physical Hazard = 1

NFPA 704 (National Fire Protection Association's Hazard Identification Ratings System):

Health = 2      Flammability = 4      Instability = 1

This SDS is based on information believed to be reliable and accurate. Because of changing reporting requirements and other variables it is impossible to guarantee the accuracy of the information contained in this document. It is the responsibility of the user to determine proper personal protection based on actual condition of use and to comply with all Federal, State and Local laws and regulations.

