# MATERIA SAFETY DATA SHEET OSHA'S HAZARD COMMUNICATION STANDARD U.S. DEPARTMENT OF LABOR

29 CFR 1910.1200

OMB NO. 1218-0072

IDENTITY NO: 6504 NAME: GLARE Micro-Finish

**SECTION 1** 

MANUFACTURE'S NAME: ULTRA 2000 MFG. CO. INC.

ADDRESS: 350 South Center street #500 Reno, Nevada 89501-2161

DATE PREPARED 12-19-2001 CONTACT PERSON: PERRY

**STEVENS Tel: (1-866-37-GLARE)** 

SETION 2-HAZARDOUS INGREDIENTS/IDENTITY **INFORMATION** 

HAZARDOUS COMPONENTS CAS# OSHA PEL **ACGIH TLV WEIGHT %** PETROLIEUM DISTALLATES 64741-65-7 100PPM .5

**VOC CONTENT-245.1G/L** 

SECTION 4- FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 155 F

FLAMMABLE LIMITS-NOT TESTED

LEL: NOT TESTED

**UEL: NOT TESTED** 

PH: 6.0-9.0

**DOT# NONE** 

NFPA HAZARD RATING- H F R S (0-least, 4-EXTREME) : 2 2 0 0

**EXTINGUISHING MEDIA: CO2, DRY FOAM** SPECIAL FIRE FIGHTING PROCDEDURES: NONE

UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE

**SECTION 5-REACTIVITY DATA** 

**STABILITY - STABLE** 

**CONDITIONS TO AVOID - NONE** 

INCOMPATIBLE MATERIALS TO AVOID: OXIDIZERS

HAZARDOUS DECOMPOSITION OR BY PRODUCTS: NONE

HAZARDOUS POLYMERIZATION: NONE

PAGE 2 (CONTINUED FROM PAGE 1)

CONDITIONS TO AVOID: NONE

### SECTION 6 - HEALTH HAZARD DATA

ROUTES OF ENTRY
INHALATION? - POSSIBLE
INGESTION? POSSIBLE
HEALTH HAZARDS - SAM AS SIGNS AND SYMPTOMS OF EXPOSURE.

NOTE - ALL CHEMICALS INCORPORATED INTO THIS PRODUCT ARE FOUND ON THE TSCA INVENTORY LIST.
OSHA CARCINOGENCITY? NONE: NTP? - IARC
MONOGRAPHS? - NONE.
SIGNS AND SYMPTOMS OF OVER EXPOSURE
EYES - BURNING IRRITATION:

SKIN: IRRITATION INGESTION: Toxic

INHALATION: DIZZINESS/HEADACHE

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE - SAME AS SIGNS AND SYMPTOMS OF OVER EXPOSURE.

## **EMERGENCY AND FIRST AID PROCEEDURES**

EYES - FLUSH WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS, CALL PHYSICIAN.

INGESTION: DO NOT INDUCE VOMITING. WILL CAUSE CHEMICAL PNEUMONIA. CALL PHYSICIAN AT ONCE.

INHALATION: MOVE PERSON TO FRESH AIR. IF UNCONSCIOIUS, CONTACT PHYSICIAN.

#### SECTION 7- PRCAUSTIONS FOR SAFE HANDLING AND USE.

STEPS TO BE TAKEN IN CASE MATERIAL IS RELASED OR SPILLED - SOAK UP WITH INERT, ABSORBENT MATERIAL. SCOOP UP AND PLACE IN A PROPER WASTE DISPOSAL CONTAINER..

WASTE DISPOSAL METHOD - DISPOSE OF IN ACCORDANCE WITH STATE AND LOCAL REGULATIONS. PRECAUSTIONS TO BE TAKEN IN HANDLING AND STORING - STORE IN A COOL, DRY PLAXE OUT OF DIRECT SUNLIGHT. DO NOT FREEZE OR HEAT ABOVE 110 F.

OTHER PRECAUTIONS- KEEP OUT OF REACH OF CHILDREN. FOLLOW DIRECTIONS ON THE CONTAINER FOR PROPER USE OF THIS PRODUCT.

## PAGE 3 (CONTINUED FROM PAGE 2)

## **SECTION 8-CONTROL MEASURES**

RESPIRATORY PROTECTION - OPEN ALL DOORS AND WINDOWS.

EXPOSURES ABOVE THE TLV OR PEL REQUIRE A NIOSH APPROVED RESPIRATOR EQUIPPED FOR THE EXPOSURE OF SUITABLE RESPIRATORY PROTECTION PER 29 CFR 1910.134

VENTILATION

LOCAL EXHAUST - IF AVAILABLE SPECIAL - NONE

MECHANICAL - IF AVAILABLE

OTHER - NONE

PROTECTIVE GLOVES: RUBBER/PLASTIC EYE PROTECTION: GLAZZES/GOGGLES

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: NONE

WORK HYGENIC PRACTICES: USE COMMON SENSE AND CARE AROUND CHEMICALS. NEVER MIX CHEMICALS. CONSULT YOUR SUPERVISOR FOR OTHER PRACTICES. ALL PRACTICES DEPEND ON YOUR SPECIFIC BUSINESS. DIRECTIONS FOR USE ARE NORMALLY FOUND ON LABEL WHICH WILL DICTATE ENGINEERING AND CONTROL MEASURES.

OTHER SPECIAL REQUIREMENTS: NONE