

Safety Data Sheet
acc. to OSHA HCS

Printing Date 04/17/2015

Revision Number 3

Revision Date 04/17/2015

1 Identification

- **Product identifier**
- **Product name:** Ultra Flex Seam Sealer (Beige)
- **Part number:** 4157
- **Relevant identified uses of the substance or mixture.** Sealant. For Professional and Industrial Use Only.
- **Application of the substance / the mixture** Sealant
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Transtar Autobody Technologies
2040 Heiserman Drive,
Brighton, MI 48114
Information Phone Number: 810 360 1600
- **Emergency telephone number:**
Chemtrec: Day or Night within USA and Canada: 1-800-424-9300.
Chemtrec Int'l: Outside USA and Canada: +001 703-527-3887 (collect calls accepted)

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Sol. 1 H228 Flammable solid.



GHS08 Health hazard

Carc. 1B H350 May cause cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Eye Irrit. 2B H320 Causes eye irritation.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 04/17/2015

Revision Number 3

Revision Date 04/17/2015

Part number: 4157

(Contd. of page 1)

· Hazard pictograms**· Signal word Danger****· Hazard statements***Flammable solid.**Causes skin and eye irritation.**May cause an allergic skin reaction.**May cause cancer.**Suspected of damaging fertility or the unborn child.**May cause damage to organs through prolonged or repeated exposure.***· Precautionary statements***If medical advice is needed, have product container or label at hand.**Keep out of reach of children.**Read label before use.**Keep away from heat/sparks/open flames/hot surfaces. - No smoking.**Use explosion-proof electrical/ventilating/lighting/equipment.**Do not breathe dust/fume/gas/mist/vapors/spray.**Wear protective gloves / eye protection / face protection.**Wear protective gloves.**Ground/bond container and receiving equipment.**Wash thoroughly after handling.**Contaminated work clothing must not be allowed out of the workplace.**Obtain special instructions before use.**Do not handle until all safety precautions have been read and understood.**If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.**Continue rinsing.**Specific treatment (see on this label).**Wash contaminated clothing before reuse.**IF exposed or concerned: Get medical advice/attention.**If skin irritation or rash occurs: Get medical advice/attention.**If eye irritation persists: Get medical advice/attention.**Get medical advice/attention if you feel unwell.**In case of fire: Use for extinction: CO₂, powder or water spray.**If on skin: Wash with plenty of water.**Take off contaminated clothing and wash it before reuse.**Store locked up.**Dispose of contents/container in accordance with local/regional/national/international regulations.***· Additional information:***1.3 percent of the mixture consists of ingredient(s) of unknown toxicity.***· Classification system:****· NFPA ratings (scale 0 - 4)**

Health = 2

Fire = 3

Reactivity = 0

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 04/17/2015

Revision Number 3

Revision Date 04/17/2015

Part number: 4157

(Contd. of page 2)

· HMIS-ratings (scale 0 - 4)

HEALTH	2	Health = 2
FIRE	3	Fire = 3
PHYSICAL HAZARD	0	Physical Hazard = 0

· Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· Hazardous components:

471-34-1	calcium carbonate	25-50%
108-88-3	toluene	5-20%
1332-58-7	Kaolin	2.5-10%
546-93-0	Magnesite	2.5-10%
64742-89-8	Solvent naphtha (petroleum), light aliph.(VM&P)	≤2.5%
13463-67-7	titanium dioxide	≤1.0%
	Binding Agent	≤0.5%

· Additional information:

It is highly unlikely the powders and pigments compounded within this product would pose a hazardous risk from inhalation as they are no longer a respirable particulate. Exposure to these ingredients as used in sealants, putties, bedding compounds and other non-sprayable products is highly unlikely. The concentrations listed in the composition section are percent by weight unless a gas. Gas concentrations are expressed in percent by volume.

4 First-aid measures

· Description of first aid measures

· **After inhalation:** Overexposure, remove to fresh air and seek medical attention.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for 20 minutes under running water. If eye becomes irritated, obtain medical treatment.

· **After swallowing:** Seek medical treatment.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed:** Can cause skin sensitization and allergic reaction.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

· Extinguishing media

· **Suitable extinguishing agents:** CO₂, extinguishing powder or water spray. Fight larger fires with water spray.

· Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 04/17/2015

Revision Number 3

Revision Date 04/17/2015

Part number: 4157

(Contd. of page 3)

- **Advice for firefighters**
- **Protective equipment:** Protective clothing and respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Dispose of contaminated material as waste in accordance with federal state and local regulations.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Avoid prolonged or repeated contact with skin.
Avoid contact with eyes.
Wash thoroughly after handling.
Persons with history of skin sensitization problems should not work around any process that uses this product.
- **Information about protection against explosions and fires:** Keep container closed when not in use.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Keep away from open flames and high temperatures.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

471-34-1 calcium carbonate

PEL	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV	TLV withdrawn

108-88-3 toluene

PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm
TLV	Long-term value: 75 mg/m ³ , 20 ppm BEI

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 04/17/2015

Revision Number 3

Revision Date 04/17/2015

Part number: 4157

(Contd. of page 4)

1332-58-7 Kaolin

PEL	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV	Long-term value: 2* mg/m ³ E; as respirable fraction

546-93-0 Magnesite

PEL	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV	TLV withdrawn

13463-67-7 titanium dioxide

PEL	Long-term value: 15* mg/m ³ *total dust
REL	See Pocket Guide App. A
TLV	Long-term value: 10 mg/m ³ withdrawn from NIC

· Ingredients with biological limit values:**108-88-3 toluene**

BEI	0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene
	0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene
	0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment (see listings below)**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.

· **Breathing equipment:**

Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 04/17/2015

Revision Number 3

Revision Date 04/17/2015

Part number: 4157

(Contd. of page 5)

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

· Material of gloves

Nitrile rubber, NBR

Chloroprene rubber, CR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Safety glasses with side shields.



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Pasty Solid
Color:	Beige
Odor:	Like aromatic solvents
Odour threshold:	Not determined.

· pH-value: Not applicable.

· Change in condition

Melting point:	Undetermined.
Boiling point:	Undetermined

· Flash point: 4 °C (39 °F)

· Flammability (solid, gaseous): Not determined.

· Ignition temperature:

Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of flammable air/vapor mixtures are possible.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 04/17/2015

Revision Number 3

Revision Date 04/17/2015

Part number: 4157

(Contd. of page 6)

· Flammable limits:	
Lower:	1.3%
Upper:	6.7%
· Vapor pressure:	22mm Hg @ 20C
· Specific gravity at 20 °C (68 °F):	1.3 g/cm ³ (10.849 lbs/gal)
· Relative density	Not determined.
· Vapour density	<1 @ 101 kPa
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with Water:	Not soluble
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not applicable.
Kinematic:	>20.5 cSt
· Solvent content:	
Organic solvents:	<25 %
· Solids content:	>75 %
· Other information	VOC content = 254 g/L Non-compliant to SCAQMD 1168

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Heat, flames, sparks, hot surfaces, ignition sources.
- **Incompatible materials:** Reacts with oxidizing agents.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

- **Primary irritant effect:**
- **on the skin:** May irritate the skin.
- **on the eye:** May irritate the eye.
- **Sensitization:** Skin Contact - Sensitization possible through skin contact.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 04/17/2015

Revision Number 3

Revision Date 04/17/2015

Part number: 4157

(Contd. of page 7)

· **Additional toxicological information:**

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

108-88-3	toluene	3
13463-67-7	titanium dioxide	2B

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:** Not expected to be harmful to aquatic organisms

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Additional ecological information:**

· **General notes:** At present there are no ecotoxicological assessments.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

Small amounts can be disposed of with household waste after the product has cured or skinned over. Larger quantities should be disposed of according to state and local regulation.

· **Uncleaned packagings:**

· **Recommendation:** Disposal must be made according to official regulations.

· **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

· **DOT, ADR, IMDG, IATA**

UN1325

· **UN proper shipping name**

· **DOT**

Flammable solids, organic, n.o.s. (Toluene)

· **ADR**

1325 Flammable solids, organic, n.o.s.

· **IMDG, IATA**

FLAMMABLE SOLID, ORGANIC, N.O.S

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 04/17/2015

Revision Number 3

Revision Date 04/17/2015

Part number: 4157

(Contd. of page 8)

· **Transport hazard class(es)**· **DOT,ADR,IMDG,IATA**

4.1 Flammable solids, self-reactive substances and solid desensitised explosives

· **Packing group**· **DOT, ADR, IMDG, IATA**

II

· **Environmental hazards:**

Not applicable.

· **Special precautions for user**Warning: flammable solids, self reactive substances and solid desensitised explosives
Limited quantity or Consumer Commodity, ORM-D if 5L or less per inner container.· **EMS Number**

F-A,S-G

· **Transport in bulk according to Annex II of
MARPOL 73/78 and the IBC Code**

Not applicable.

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**· **Sara**· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

108-88-3 toluene

· **TSCA (Toxic Substances Control Act):**

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

· **Proposition 65**· **Chemicals known to cause cancer:**

64742-89-8 Solvent naphtha (petroleum), light aliph. (VM&P)

13463-67-7 titanium dioxide

· **Chemicals known to cause reproductive toxicity:**

108-88-3 toluene

· **(DSL) Canada Domestic Substance List**

All components of this product are on the DSL (Canada Domestic Substance list) or are exempt from DSL requirements.

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing Date 04/17/2015

Revision Number 3

Revision Date 04/17/2015

Part number: 4157

(Contd. of page 9)

· **Cancerogenity categories**

· **EPA (Environmental Protection Agency)**

108-88-3	toluene	II
----------	---------	----

· **TLV (Threshold Limit Value established by ACGIH)**

108-88-3	toluene	A4
1332-58-7	Kaolin	A4
13463-67-7	titanium dioxide	A4

· **MAK (German Maximum Workplace Concentration)**

13463-67-7	titanium dioxide	3A
------------	------------------	----

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	titanium dioxide	
------------	------------------	--

· **National regulations:**

· **Information about limitation of use:** Use by properly trained workers recommended.

· **Water hazard class:** Generally not hazardous for water.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, Transtar Autobody Technologies makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Transtar Autobody Technologies or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

· **SDS prepared by:** Transtar Autobody Technologies

· **Creation Date:** 03/31/2015

· **Date of preparation / last revision** 04/17/2015 / 2

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Sol. 1: Flammable solids, Hazard Category 1

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2B: Serious eye damage/eye irritation, Hazard Category 2B

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Carc. 1B: Carcinogenicity, Hazard Category 1B

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2