AGS COMPANY Sil-Glyde Grease

### **MATERIAL SAFETY DATA SHEET**

# SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product:765-1346, 765-1351Trade Name:Sil-Glyde GreaseManufacturer:AGS CompanyCommon Name:Non-Petroleum Grease

Street Address: 2651 Hoyt St

City/State/Zip Muskegon Hts., MI 49444

Phone: 800-253-0403
Phone: 231-733-2101

 Phone:
 231-733-2101
 Original Issue Date:
 4/20/1992

 FAX:
 231-733-1784
 Revision No
 7
 Date
 7/31/2007

**Transportation Emergency**: CHEM-TEL **Phone**: 800-255-3924

# SECTION 2 - COMPOSITION/ INFORMATION ON INGREDIENTS

ITEM		CAS NUMBER	WT/WT %
	1 Polypropylene Glycol	25322-69-4	30-60
	2 Methylated Silica	67762-90-7	7-13
	3 Phenyl - Alpha-Naphthylamine	90-30-2	0.1-1
	4 N-Cis-Octadecenoyl Sarcosine	110-25-8	0.1-1
	5 Oleoyl Sarcosine	Mixture	0.1-1
	6 Diethyl Phthalate	84-66-2	0.1-1

#### **EXPOSURE LIMITS**

		ACGIH		OSHA	
ITEM	TLV-T\	WA	TLV-STEL	PEL-TWA	PEL-CEILING
	1 N.E.		N.E.	N.E.	N.E.
	2	10 mg/m <sup>3</sup>	N.E.	6 mg/m <sup>3</sup>	N.E.
	3 N.E.		N.E.	N.E.	N.E.
	4 None		None	None	None
	5 N.E.		N.E.	N.E.	N.E.
	6	5 mg/m <sup>3</sup>	N.E.	5 mg/m <sup>3</sup>	N.E.
			(See Section 16 for abbreviation legend)		

### **SECTION 3 - HAZARDS IDENTIFICATION**

EYE CONTACT: May be irritating and can cause pain, tearing, reddening and swelling.

SKIN CONTACT: Prolonged contact may result in irritation.

INHALATION: None expected.

INGESTION: This material may be harmful if swallowed.

CHRONIC HAZARDS: There are no foreseeable uses of the product that would lead to chronic exposure.

Primary Route(s) of Entry Skin and eye contact or ingestion.

### **SECTION 4 - FIRST AID MEASURES**

EYE CONTACT: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists

SKIN CONTACT: Immediately flush with plenty of water. Remove clothing. Get medical attention immediately. Wash clothing separately before reuse.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

INGESTION: Get medical attention immediately. If swallowed, DO NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

# **SECTION 5 - FIRE FIGHTING MEASURES**

Page 1 of 4 Printed 4/2/2008

**AGS COMPANY** Sil-Glyde Grease

## **MATERIAL SAFETY DATA SHEET**

FLASH POINT: 425°F 218°C LOWER EXPLOSIVE LIMIT: N.A. %

**UPPER EXPLOSIVE LIMIT:** N.A.

**AUTOGNITION TEMPERATURE:** N.D.

**EXTINGUISHING MEDIA:** CO<sub>2</sub>, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS: Product can produce dense smoke from oils burning.

Wear NIOSH/MSHA approved self-contained breathing apparatus and SPECIAL FIREFIGHTING PROCEDURES:

protective gear.

### SECTION 6 - ACCIDENTAL RELEASE MEASURES

RECOVERY PROCEDURES: Scrape up material and place in a chemical waste container.

## SECTION 7 - HANDLING AND STORAGE

HANDLING: Wash thoroughly after handling

STORAGE: Store in cool dry environment.

## SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

**ENGINEERING CONTROLS:** No special controls needed when used in supplied form.

RESPIRATORY PROTECTION: For most conditions, no respiratory protection should be needed, however, if high vapor concentration should develop, use a NIOSH approved organic vapor respirator.

SKIN PROTECTION: Where contact is likely, wear chemical resistant gloves.

EYE PROTECTION: Wear safety glasses with side shields or goggles.

OTHER PROTECTIVE EQUIPMENT: Eye wash in work area.

HYGIENIC PRACTICES: Wash hands before eating. Remove contaminated clothing and wash before reuse. Use only in a well ventilated area. Follow all MSDS / label precautions even after container is emptied because

they may retain product residues. Avoid prolonged or repeated contact with eyes, skin, and clothing.

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

**BOILING RANGE** N.A. VAPOR DENSITY: Is heavier than air

**ODOR** Odorless ODOR THRESHOLD N.D.

EVAPORATION RATE Is slower than Butyl Acetate **APPEARANCE** Opaque Semi Solid

SOLUBILITY IN H<sub>2</sub>O Negligible

FREEZE POINT N.D. SPECIFIC GRAVITY 1.0764 **VAPOR PRESSURE** Negligible pH @ 0.0% N.A. PHYSICAL STATE VISCOSITY: N.D. Semi-Solid

COEFFICIENT OF WATER / OIL DISTRIBUTION: Negligible

(See Section 16 for abbreviation legend)

### **SECTION 10 - STABILITY AND REACTIVITY**

CONDITIONS TO AVOID: Sources of ignition.

INCOMPATIBILITY: Strong acid or alkali, oxidizers and amines.

HAZARDOUS DECOMPOSITION PRODUCTS Oxides of carbon and nitrogen.

Page 2 of 4 Printed 4/2/2008 **AGS COMPANY** Sil-Glyde Grease

## **MATERIAL SAFETY DATA SHEET**

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions

STABILITY: This product is stable under normal storage conditions.

#### **SECTION 11 - TOXICOLOGICAL PROPERTIES**

PRODUCT LD-50 3750 mg/kg PRODUCT LC-50 N.D.

COMPONENT TOXICOLOGICAL INFORMATION:

CHEMICAL NAME LD50 LC50 Polypropylene Glycol 3750 mg/kg/rat N.E.

N.E. Castor Oil N.E. Methylated Silica TCLO 30 mg/m<sup>3</sup> 6h/rat N.D.

Dimethylpolysiloxane 20000 mg/kg/rat N.E. Phenyl - Alpha-Naphthylamine 1625 mg/kg/rat N.E. N-Cis-Octadecenoyl Sarcosine N.E. N.E. Oleoyl Sarcosine N.E. N.E. Fragrance Neutralizer N.E. N.E.

**SECTION 12 - ECOLOGICAL INFORMATION** 

**ECOLOGICAL INFORMATION:** No information

**SECTION 13 - DISPOSAL CONSIDERATIONS** 

DISPOSAL METHOD: Dispose of in accordance with federal, state and local regulations.

### **SECTION 14 - TRANSPORTATION INFORMATION**

DOT PROPER SHIPPING NAME Not regulated

DOT TECHNICAL NAME

DOT HAZARD CLASS HAZARD SUBCLASS:

DOT UN / NA NUMBER: PACKING GROUP: NA RESP. GUIDE PAGE

**SECTION 15 - REGULATORY INFORMATION** 

U.S FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 cfr 1910.1200)

CERCLA - SARA HAZARD CATEGORY:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD CHRONIC HEALTH HAZARD

**SARA SECTION 313** 

This product contains the following substance subject to the reporting requirements of Section 313 of Title of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

**CHEMICAL NAME CAS NUMBER** WT /WT % IS LESS THAN %

No SARA Section 313 components exist in this product

TOXIC SUBSTANCE CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12 (B) if exported from the United States:

> Page 3 of 4 Printed 4/2/2008

**AGS COMPANY** Sil-Glyde Grease

**MATERIAL SAFETY DATA SHEET** 

CHEMICAL NAME

**CAS NUMBER** 

Dimethylpolysiloxane

63148-62-9

**U.S. STATE REGULATIONS:** 

AS FOLLOWS -

**NEW JERSEY RIGHT-TO-KNOW:** 

The following materials are non-hazardous, but are among the top five components in this product:

**CHEMICAL NAME CAS NUMBER** 

Castor Oil 8001-79-4 Methylated Silica 67762-90-7 Dimethylpolysiloxane 63148-62-9

PENNSYLVANIA RIGHT-TO-Know

The following non-hazardous ingredients are present in the product at greater than 3%:

CHEMICAL NAME **CAS NUMBER** 

Castor Oil 8001-79-4 67762-90-7 Methylated Silica

**CALIFORNIA PROPOSITION 65:** 

WARNING: The chemical(s) noted below and contained in this product, are know to the state of California

to causes cancer, birth defects or other reproductive harm.

**CHEMICAL NAME CAS NUMBER** 

No Proposition 65 chemicals exist in this product

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations

except for use of the 16 headings.

CANADIAN WHMIS CLASS: No information available.

**SECTION 16 - OTHER INFORMATION** 

PPE HMIS RATINGS: Health 0 Flammability 1 Phys. Haz. 0 Α

**NFPA** 0 Flammability Reactivity Health 1

VOLATILE ORGANIC COMPOUNDS (VOCs): 0.00 lbs / gal 0 grams / liter

LEGEND: N.A. Not Applicable N.E. Not Established

Not Determined N.D.

> Page 4 of 4 Printed 4/2/2008

0