

SAFETY DATA SHEET

This safety data sheet complies with the requirements of: OSHA Hazard Communication Standard (29 CFR 1910.1200)

Product Name: Toyota Suspension Fluid AHC, 2.5L x 6 Case

Revision Date: 20-Jul-2021 Product Code: 34060030-79500C020 **Revision Number: 4**

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE

COMPANY/UNDERTAKING

1.1 Product identifier

Product Name: Toyota Suspension Fluid AHC, 2.5L x 6 Case

Other means of identification

Product Code: 34060030-79500C020

1.2 Recommended use of the chemical and restrictions on use

Recommended Use: Automotive Lubricant

1.3 Details of the supplier of the safety data sheet

Supplied by: Idemitsu Lubricants America Corporation

701 Port Rd., Jeffersonville, IN. 47130

Telephone: 1-(812) 284-3300 Business hours: 8am-4:30pm est

Email: Ila.sds@idemitsu.com

Manufactured by: Idemitsu Kosan Co., Ltd

2-1, Otemachi 1-chome

Chiyoda-ku, Tokyo, Japan 100-8321

24 Hour Emergency Phone Number: Within USA and Canada: 1800-424-9300

Outside USA and Canada: + 1 703-741-5970

(collect calls accepted)

2. HAZARDS IDENTIFICATION

2.1 Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

Reproductive toxicity	Category 2
Aspiration toxicity	Category 1

2.2 Label elements



Signal word Danger

Hazard Statements

H304 - May be fatal if swallowed and enters airways

H361 - Suspected of damaging fertility or the unborn child

Precautionary Statements - Prevention P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read

Revision Date: 20-Jul-2021

and understood

P280 - Wear protective gloves/protective clothing and eye/face

protection

Precautionary Statements - Response P308 + P313 - IF exposed or concerned: Get medical

advice/attention

Ingestion P301 + P310 - IF SWALLOWED: Immediately call a POISON

CENTER or doctor/physician P331 - Do NOT induce vomiting

Precautionary Statements - Storage P405 - Store locked up

Precautionary Statements - Disposal P501 - Dispose of contents/ container to an approved waste

disposal plant

2.3 Other information

Hazards not otherwise classified (HNOC): Not applicable

Other hazards May be harmful in contact with skin

Harmful to aquatic life with long lasting effects

Harmful to aquatic life

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Not applicable

3.2 Mixture

Hazardous Components

Chemical name	CAS-No	weight-%	US GHS Classification	Notes
Petroleum distillates, hydrotreated light paraffinic	64742-55-8	50-60	Asp. Tox. 1 (H304)	L
Petroleum distillates, solvent-refined light paraffinic	64741-89-5	40-50	Asp. Tox. 1 (H304)	L
Tricresylphosphate	1330-78-5	<1	Acute Tox. 4 (H302) Acute Tox. 4 (H312) Reproductive 2 (H361) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)	

L - The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 "Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions - Dimethyl sulphoxide extraction refractive index method", Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3

4. FIRST AID MEASURES

4.1 First Aid Measures

General Advice If symptoms persist, call a physician. Take a copy of the Safety Data Sheet when going for

medical treatment.

Skin Contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. Wash contaminated clothing before re-use. Call a physician

immediately.

Eye Contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If eye irritation persists: Get medical advice or attention. IF exposed or concerned: Get medical advice.

In case of inadequate ventilation wear respiratory protection. If breathing difficulties

develop, move victim away from source of exposure and into fresh air in a position comfortable for breathing. If unconscious place in recovery position and seek medical advice. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Call a

physician immediately.

Ingestion Call a physician or poison control center immediately. Do not induce vomiting. If vomiting

occurs naturally, have casualty lean forward to reduce the risk of aspiration.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms See Section 11 for additional Toxicological information.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flammable Properties NFPA: Class IIIB Combustible Liquid

5.1 Suitable extinguishing media

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment

Unsuitable Extinguishing Media: Do not use a solid water stream as it may scatter and spread fire.

5.2 Specific Hazards Arising from the Chemical Keep product and empty container away from heat and sources

of ignition.

Hazardous combustion products

During a fire, smoke may contain the original material in addition

to combustion products of varying composition which may be toxic and / or irritating. Combustion products may include and

Revision Date: 20-Jul-2021

are not limited to: Carbon oxides Oxides of Phosphorus Nitrogen oxides (NOx)

5.3 Protective Equipment and Precautions for Firefighters: As in any fire, wear self-contained breathing apparatus

pressure-demand, MSHA/NIOSH (approved or equivalent) and

full protective gear.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists. Use personal

protection recommended in Section 8. Ensure adequate ventilation. Remove all sources of

ignition.

6.2. Environmental precautions

Environmental Precautions See section 12 for additional ecological information. Prevent further leakage or spillage if

safe to do so. Prevent product from entering drains. Do not allow into any sewer, on the ground or into any body of water. Do not flush into surface water or sanitary sewer system. Large Spills: Dike far ahead of liquid spill for later recovery and disposal. Prevent entry into

waterways, sewers, basements or confined areas.

6.3 Methods and material for containment and cleaning up

Methods for Clean-up Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth,

diatomaceus earth, vermiculite) and place in container for disposal according to local /

national regulations (see section 13).

Spill Management

LARGE SPILLS Eliminate sources of ignition. Prevent additional discharge of material if possible to do so

without hazard. For small spills implement cleanup procedures; for large spills implement

cleanup procedures and, if in public area, keep public away and advise authorities.

WATER SPILLS Prevent liquid entering sewers, watercourses, or low areas. Contain spilled liquid with sand

or earth. Recover by pumping or with suitable absorbent. If liquid is too viscous for pumping, scrape up. Consult an expert on disposal of recovered material and ensure

conformity to local disposal regulations.

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Handling Obtain special instructions before use. Do not breathe vapors,

spray, or mist. Do not handle until all safety precautions have

been read and understood. Avoid contact with eyes, skin and clothing. Use personal protection recommended in the SDS. Wear protective gloves, protective clothing, eye protection, and face protection. Wash hands thoroughly after handling. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. Should not be released into the environment.

Revision Date: 20-Jul-2021

Safe Handling Advice

Handle in accordance with good industrial hygiene and safety practices. Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities

Storage Keep in properly labeled containers. Keep container tightly closed

in a dry and well-ventilated place.

Technical measures/PrecautionsEnsure adequate ventilation. To avoid ignition of vapors by static

electricity discharge, all metal parts of the equipment must be

grounded.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure Guidelines

Chemical name	OSHA PEL	ACGIH TLV	ACGIH OEL (STEL)	NIOSHT REL TWA	ILA IHG	ILA ROEG	ILA Internal Exposure Limit
Oil mist, mineral	TWA: 5 mg/m³	TWA: 5 mg/m³	-	TWA 5 mg/m ³ ST 10 mg/m ³			

8.2 Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal Protective Equipment

Eye/face protection Safety glasses equipped with side shields are recommended as minimum protection in

industrial settings. If splashes are likely to occur wear tight fitting safety goggles and/or

face-shield.

Skin protection Choose the appropriate protective clothing and gloves based on the tasks being performed

to avoid exposed skin surfaces. Glove Type: Neoprene, Nitriles

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

General Hygiene Considerations When using, do not eat, drink or smoke. Clean equipment, work area and clothing regularly.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance Red
Physical state Liquid
Odor Mild

Odor Threshold No information available

pH Not applicable
Melting point / melting range Not applicable

Boiling point / boiling range No information available

Flash Point > 140 °C / > 284 °F COC ASTM D92
Evaporation Rate No information available

Evaporation Rate

Flammability Limit in Air

No information available
Explosion Limits

No information available
Vapor pressure @20 °C (kPa)

Vapor density

Density

Solubility(ies)

Partition coefficient

No information available
No information available
No information available
No information available

Autoignition Temperature

No information available

No information available

No information available

No information available

Kinematic viscosity @40C = 10.03 cSt; @100C = 2.83 cSt

9.2. Other information

DMSO extract by IP346Less than 3.0 wt% (mineral oil component only)

10. STABILITY AND REACTIVITY

10.1. Reactivity

Reactivity The product is chemically stable.

10.2. Chemical stability

Chemical Stability Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

Possibility of Hazardous Reactions None under normal processing.

10.4. Conditions to avoid

Conditions to Avoid Heat, flames and sparks.

10.5. Incompatible materials

Incompatible Materials Strong acids, Strong bases

10.6. Hazardous decomposition products

Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and

vapors.

11. TOXICOLOGICAL INFORMATION

11.1 Information on likely routes of exposure

Inhalation May cause respiratory irritation.

Eye contact May cause slight irritation.

Skin Contact May cause skin irritation and/or dermatitis.

Ingestion May be fatal if swallowed and enters airways.

11.2 Information on toxicological effects

Symptoms No information available

11.3 Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Not classified.

Serious eye damage/eye

irritation

Not classified.

Sensitization Not classified.

Mutagenic effects Not classified.

Reproductive Toxicity Suspected of damaging fertility or the unborn child

Developmental Effects Testes Exposure route Oral

STOT - single exposure Not classified.

STOT - repeated exposure Not classified

Aspiration hazard May be fatal if swallowed and enters airways.

11.4 Carcinogenicity

Carcinogenicity: No component of this product present at levels greater than or equal to 0.1% is identified as

a known or anticipated carcinogen by NTP, IARC, OSHA or ACGIH.

Legend: NTP (National Toxicology Program), IARC (International Agency for Research on Cancer),

OSHA (Occupational Safety and Health Administration of the US Department of Labor),

ACGIH (American Conference of Governmental Industrial Hygienists)

11.5 Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

Product Information (Estimated):

 ATEmix (oral)
 > 5,000 mg/kg

 ATEmix (dermal)
 > 5,000 mg/kg

 ATEmix (inhalation-dust/mist)
 > 5 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum distillates,	> 5,000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.01 mg/L (Rat) 4 h
hydrotreated light paraffinic			

34060030-79500C020 - Toyota Suspension Fluid AHC, 2.5L x 6 Case

64742-55-8			
Petroleum distillates, solvent-refined light paraffinic 64741-89-5	> 15 g/kg (Rat)	> 5 g/kg (Rabbit)	5.2 mg/L
Tricresylphosphate 1330-78-5	> 20000 mg/kg (Rat)	> 10000 mg/kg (Rabbit)	> 5.2 mg/L (Rat)4 h

12. ECOLOGICAL INFORMATION

12.1 Ecotoxicity

Ecotoxicity effects

Harmful to aquatic life with long lasting effects. Plants and animals may experience harmful or fatal effects when coated with petroleum products. Petroleum-based (mineral) lubricating oils normally will float on water. In stagnant or slow-flowing waterways, an oil layer can cover a large surface area. As a result, this oil layer might limit or eliminate natural atmospheric oxygen transport into the water. With time, if not removed, oxygen depletion in the waterway may be sufficient to cause a fish kill or create an anaerobic environment.

Revision Date: 20-Jul-2021

12.2 Persistence and degradabilityNo information available.

12.3. Bioaccumulative potential No information available.

12.4 Mobility in Environmental Media No information available.

12.5 Other adverse effects:No information available.

PBT and vPvB assessment No information available

13. DISPOSAL CONSIDERATIONS

Hazard characteristic and regulatory waste stream classification can change with product use. Accordingly, it is the responsibility of the user to determine the proper storage, transportation, treatment and/or disposal methodologies for spent materials and residues at the time of disposition.

Waste Disposal Method This material, as supplied, is not a hazardous waste according to Federal regulations (40

CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local

regulations for additional requirements.

Contaminated packaging Dispose of in accordance with local regulations.

14.TRANSPORT INFORMATION

DOT Not regulated

IATA Not regulated

IMDG Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA	All ingredients are on the inventory or exempt from listing					
DSL/NDSL	All ingredients are on the inventory or exempt from listing					
	There are ingredients listed on the NDSL Inventory List					
Chemical name	NDSL	CAS-No	weight-%			
Phosphonic acid, di-9-octadecenyl ester	X	64051-29-2	<1			
EINECS	All ingredients are o	on the inventory or exempt from	listing			
ENCS	All ingredients are on the inventory or exempt from listing					
IECSC	All ingredients are on the inventory or exempt from listing					
KECL	All ingredients are on the inventory or exempt from listing					
PICCS		on the inventory or exempt from				
AICS	All ingredients are on the inventory or exempt from listing					
NZIoC	All ingredients are on the inventory or exempt from listing					
REACH	All ingredients are of	on the inventory or exempt from	listing			

ш	e	۸	
u	J	-	١

Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazardous Categorization

Acute health hazard Reproductive Toxicity, Aspiration hazard

Chronic Health Hazard Reproductive Toxicity

Fire hazard No
Sudden Release of Pressure Hazard No
Reactive Hazard No

CERCLA/SARA 302 & 304

Section 302 & 304 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 355.

Chemical name	CAS-No	weight-%	RQ	TPQ
Methyl methacrylate	80-62-6	<0.01	RQ 1000lb final RQ	
			RQ 454kg final RQ	
Xylenes (o-, m-, p- isomers)	1330-20-7	<0.0001	RQ 100lb final RQ	
			RQ 45.4kg final RQ	
Ethyl benzene	100-41-4	<0.00001	RQ 1000lb final RQ	
			RQ 454kg final RQ	

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

Chemical name	CAS-No	weight-%	HAPS data
Methyl methacrylate	80-62-6	<0.01	X
Xylenes (o-, m-, p- isomers)	1330-20-7	<0.0001	X
Ethyl benzene	100-41-4	<0.0001	X

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CAS-No	weight-%	U.S CWA (Clean Water

34060030-79500C020 - Toyota Suspension Fluid AHC,

2.5L x 6 Case

			Act)
Methyl methacrylate	80-62-6	<0.01	X
Xylenes (o-, m-, p- isomers)	1330-20-7	<0.0001	X
Ethyl benzene	100-41-4	<0.0001	X

State Regulations

California Proposition 65

Label:

<u>^</u>

WARNING Cancer - www.P65Warnings.ca.gov

Chemical name	CAS-No	weight-%	California Prop. 65	Maximum Allowable Dose for Reproductive Toxicity (MADLS)	Safe Harbor Limits for Cancer-causing Chemicals (NSRLs)
Ethyl benzene	100-41-4	<0.00001	Carcinogen		54 μg/day inhalation 41 μg/day oral

State Right-to-Know

This product does not contain any substances regulated by state right-to-know regulations

New Jersey Worker and Community Right-to-Know Act:

Under the New Jersey Right-to-Know Act L. 1983 Chapter 315 N.J.S.A. 34:5A-1 et. seq., the product is to be identified as follows: PETROLEUM OIL (Lubricating Oil)

16. OTHER INFORMATION



<u>NFPA</u>

Health hazards: 1

Flammability: 1

Instability: 0

Revision Date: 20-Jul-2021

Prepared By: Latoya Walker

Revision Date: 20-Jul-2021

Revision Summary: Appearance

Disclaimer:

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet