Permatex.

SAFETY DATA SHEET

Revision Date 21-Apr-2023 Version 10

1. IDENTIFICATION

Product identifier

Product Name SENSOR SAFE ULTRA GREY RTV 3 OZ

Other means of identification

Product Code 82194

Recommended use of the chemical and restrictions on use

Recommended Use Sealant

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address
ITW Permatex, Inc.
6875 Parkland Blvd.
Solon, Ohio 44139 USA
Telephone: 1-87-Permatex

(866) 732-9502

24-hour emergency phone number

Chem-Tel: 800-255-3924 International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address: mail@permatex.com

May Also Be Distributed by:

ITW Permatex Canada 101-2360 Bristol Circle

Oakville, ON Canada L6H 6M5 Telephone: (800) 924-6994

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Carcinogenicity	Category 2

Label elements

Emergency Overview

Signal word Warning

Causes serious eye irritation May cause an allergic skin reaction Suspected of causing cancer



Appearance Gray Physical state Paste / Gel Liquid Odor Mild

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing must not be allowed out of the workplace

Wear protective clothing, gloves, and eye protection or face shield

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

Precautionary Statements - Storage

Protect from sunlight. Store in a well-ventilated place Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

Not applicable.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
CALCIUM CARBONATE	471-34-1	10 - 30
Almandite-Ferric Aluminum Silicate	1302-62-1	10 - 30
STEARIC ACID	57-11-4	1 - 5
2-BUTANONE OXIME	96-29-7	1 - 5

4. FIRST AID MEASURES

Description of first aid measures

General advice If symptoms persist, call a physician.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms

persist, call a physician.

Skin contact IF ON SKIN:. Wash skin with soap and water. If skin irritation or rash occurs: Get medical

advice/attention. Wash contaminated clothing before reuse. Immediate medical attention is not required. Wash off immediately with soap and plenty of water while removing all

contaminated clothes and shoes. If skin irritation persists, call a physician.

Inhalation Immediate medical attention is not required. If symptoms persist, call a physician. Move to

fresh air in case of accidental inhalation of vapors or decomposition products.

Ingestion Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth

to an unconscious person. Call a physician. Do NOT induce vomiting.

Self-protection of the first aiderUse personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms May cause allergic skin reaction.

Indication of any immediate medical attention and special treatment needed

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use, Use dry chemical, Carbon dioxide (CO2), Water spray (fog), Alcohol resistant foam

Unsuitable extinguishing media

None

Specific hazards arising from the chemical

Keep product and empty container away from heat and sources of ignition. Risk of ignition.

Explosion data

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. Remove all sources of ignition. Evacuate

personnel to safe areas. Keep people away from and upwind of spill/leak. Pay attention to

flashback. Take precautionary measures against static discharges.

Environmental precautions

Environmental precautions See section 12 for additional ecological information. Do not flush into surface water or

sanitary sewer system. Prevent further leakage or spillage if safe to do so. Prevent product

from entering drains.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Ensure adequate ventilation. Flood with water to complete polymerization and scrape off

floor. Sweep up and shovel into suitable containers for disposal. Slippery, can cause falls if

walked on. Soak up with inert absorbent material. Dam up. Pick up and transfer to properly labeled containers. Take precautionary measures against static discharges.

Prevention of secondary hazards

Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Use with local exhaust ventilation. All equipment used when handling the product must be

grounded. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a cool, well-ventilated place. Protect from moisture. Keep

away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors

and static electricity). Keep away from heat. Keep in properly labeled containers.

Incompatible materials Strong oxidizing agents, Acids, Water

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
CALCIUM CARBONATE	-	-	TWA: 10 mg/m ³ total dust
471-34-1			TWA: 5 mg/m ³ respirable dust
STEARIC ACID	TWA: 10 mg/m ³ inhalable	-	-
57-11-4	particulate matter		
	TWA: 3 mg/m ³ respirable		
	particulate matter		

NIOSH IDLH Immediately Dangerous to Life or Health

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Skin and body protection Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

appropriate.

General Hygiene Considerations When using do not eat, drink or smoke. Regular cleaning of equipment, work area and

clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state Paste / Gel Liquid

AppearanceGrayOdorMild

Odor threshold No information available

No information available

Remarks • Method

Polymerization

Tag Closed Cup

Butyl acetate = 1

Air = 1

<u>Property</u> <u>Values</u>

pH No information available

Melting point / freezing point

Boiling point / boiling range
Flash point

No information available
No information available
> 93 °C / > 199 °F

Evaporation rate < 1

Flammability (solid, gas) Flammability Limit in Air

Upper flammability limit:

Lower flammability limit:

Vapor pressure

No information available
No information available
<5 mm Hg @ 70°F

Vapor density >1 Relative density 1.47

Water solubility
Solubility(ies)
Partition coefficient
Autoignition temperature
Hyphen
No information available

Kinematic viscosity

Dynamic viscosity

Explosive properties

No information available

Other Information

Softening point No information available Molecular weight No information available

VOC content < 2%

Density

Bulk density

SADT (self-accelerating decomposition temperature)

No information available No information available decomposition temperature)

10. STABILITY AND REACTIVITY

Reactivity

No information available

Chemical stability

Stable under normal conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents, Acids, Water

Hazardous Decomposition Products

Carbon oxides

Nitrogen oxides (NOx)

Formaldehyde

May release 2-butanone oxime (ethyl methyl ketoxime) at elevated temperature

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation May cause irritation of respiratory tract.

Eye contact Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

Skin contact May cause sensitization by skin contact. May cause skin irritation and/or dermatitis.

Ingestion Ingestion may cause irritation to mucous membranes.

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
CALCIUM CARBONATE	= 6450 mg/kg (Rat)	> 2000 mg/kg (Rat)	> 3 mg/L (Rat)4 h
471-34-1			
STEARIC ACID	= 4600 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-
57-11-4			
2-BUTANONE OXIME	= 930 mg/kg (Rat)	1000 - 1800 mg/kg (Rabbit)	> 4.83 mg/L (Rat) 4 h
96-29-7			- ' '

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization May cause sensitization by skin contact.

Germ cell mutagenicityNo information available.CarcinogenicityNo information available.Target organ effectsEyes, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 13208 mg/kg ATEmix (dermal) 62179 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

0.0344 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical name	Partition coefficient
2-BUTANONE OXIME	0.65
96-29-7	

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number Not applicable

This product contains one or more substances that are listed with the State of California as a hazardous waste.

14. TRANSPORT INFORMATION

DOT

Proper shipping name Not regulated

IATA

Proper shipping name Not regulated

MDG

Proper shipping name Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies **DSL/NDSL** Complies Does not comply **EINECS/ELINCS** Does not comply **ENCS** Complies **IECSC** Complies **KECL** Complies **PICCS** Complies **AICS**

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

<u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard No
Fire hazard Yes
Sudden release of pressure hazard No
Reactive Hazard No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
ALUMINIUM POWDER	X	X	X
7429-90-5			

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

D2B - Toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 2 Instability 0

HMIS Health hazards 2 Flammability 2 Physical hazards 0 Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date 21-Apr-2023

Disclaimer

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

End of Safety Data Sheet