

SAFETY DATA SHEET



Car Brite™ PURPLE DRESSING High Gloss Tire Dressing

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
5.4	04/10/2024	600000000718	Date of first issue: 05/23/2016

SECTION 1. IDENTIFICATION

Product name : CB PURPLE DRSG 5 GA

Product code : CBOOC008F05-S5

Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC

Address : 720 Vaiden Drive, Hernando, MS 38632

Email Address : EHS@niteoproducts.com

Telephone : 1-844-696-4836

Emergency telephone number : 1-800-424-9300 / 1-703-741-5970

Recommended use of the chemical and restrictions on use

Recommended use : TIRE SHINE / DRESSING

Restrictions on use : Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 2

Skin irritation : Category 2

Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : Highly flammable liquid and vapour.
May be fatal if swallowed and enters airways.
Causes skin irritation.

SAFETY DATA SHEET



Car Brite™ PURPLE DRESSING High Gloss Tire Dressing

Version 5.4 Revision Date: 04/10/2024 SDS Number: 600000000718 Date of last issue: 04/09/2024
Date of first issue: 05/23/2016

May cause drowsiness or dizziness.

Precautionary statements

:

Prevention:

Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ ventilating/ lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
Wash skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/ eye protection/ face protection.

Response:

IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
Do NOT induce vomiting.
If skin irritation occurs: Get medical advice/ attention.
Take off contaminated clothing and wash before reuse.
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

Static-accumulating flammable liquid.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Heptane, branched, cyclic and linear	426260-76-6	>= 70 - < 90
n-Heptane	142-82-5	>= 1 - < 5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

**Car Brite™ PURPLE DRESSING High Gloss
Tire Dressing**

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
5.4	04/10/2024	600000000718	Date of first issue: 05/23/2016

- | | |
|---|--|
| General advice | : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended. |
| If inhaled | : Consult a physician after significant exposure.
If unconscious, place in recovery position and seek medical advice. |
| In case of skin contact | : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes. |
| In case of eye contact | : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist. |
| If swallowed | : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital. |
| Most important symptoms and effects, both acute and delayed | : May be fatal if swallowed and enters airways.
Causes skin irritation.
May cause drowsiness or dizziness. |
| Notes to physician | : Treat symptomatically. |

SECTION 5. FIREFIGHTING MEASURES

- | | |
|---------------------------------------|---|
| Suitable extinguishing media | : Alcohol-resistant foam
Carbon dioxide (CO ₂)
Dry chemical |
| Unsuitable extinguishing media | : High volume water jet |
| Specific hazards during fire-fighting | : Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products | : Carbon oxides
Silicon oxides |
| Further information | : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers. |

**Car Brite™ PURPLE DRESSING High Gloss
Tire Dressing**

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
5.4	04/10/2024	600000000718	Date of first issue: 05/23/2016

Special protective equipment : Wear self-contained breathing apparatus for firefighting if necessary for firefighters

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Use only explosion-proof equipment.
Keep away from open flames, hot surfaces and sources of ignition.

Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

SAFETY DATA SHEET



Car Brite™ PURPLE DRESSING High Gloss Tire Dressing

Version 5.4 Revision Date: 04/10/2024 SDS Number: 600000000718 Date of last issue: 04/09/2024
Date of first issue: 05/23/2016

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Heptane, branched, cyclic and linear	426260-76-6	TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH
n-Heptane	142-82-5	TWA	85 ppm 350 mg/m3	NIOSH REL
		C	440 ppm 1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
		STEL	500 ppm 2,000 mg/m3	OSHA P0
		TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH

Personal protective equipment

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid
Colour : purple
Odour : fruity
Odour Threshold : not determined

SAFETY DATA SHEET



Car Brite™ PURPLE DRESSING High Gloss Tire Dressing

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
5.4	04/10/2024	600000000718	Date of first issue: 05/23/2016

pH	:	not determined
Melting point/freezing point	:	not determined
Boiling point/boiling range	:	> 65 °C (1,013 hPa) The value is calculated
Flash point	:	< 20.5 °C Method: Pensky-Martens closed cup
Evaporation rate	:	not determined
Flammability (solid, gas)	:	not determined
Flammability (liquids)	:	Static-accumulating flammable liquid.
Self-ignition	:	450 °C
Upper explosion limit / Upper flammability limit	:	7 %(V) The value is calculated
Lower explosion limit / Lower flammability limit	:	0.6 %(V) The value is calculated
Vapour pressure	:	35 hPa (25 °C) The value is calculated
Relative vapour density	:	not determined
Density	:	0.7488 g/cm3
Solubility(ies) Water solubility	:	partly soluble
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	not determined
Viscosity Viscosity, dynamic	:	not determined
Viscosity, kinematic	:	18.6 mm2/s (40 °C)
Oxidizing properties	:	No data available
Molecular weight	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use. No decomposition if stored and applied as directed.
------------	---	--

**Car Brite™ PURPLE DRESSING High Gloss
Tire Dressing**

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
5.4	04/10/2024	600000000718	Date of first issue: 05/23/2016

Chemical stability	:	Stable under normal conditions. No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed. Vapours may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Strong oxidizing agents Not applicable
Hazardous decomposition products	:	Carbon oxides Silicon oxides

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Eye contact
Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity	:	Acute toxicity estimate: > 200 mg/l Exposure time: 4 h Test atmosphere: vapour Method: Calculation method
---------------------------	---	--

Acute dermal toxicity	:	Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method
-----------------------	---	--

Components:**n-Heptane:**

Acute oral toxicity	:	LD50 (Rat): Expected > 5,000 mg/kg Remarks: Information given is based on data obtained from similar substances.
Acute inhalation toxicity	:	LC50 (Rat, male and female): > 29.29 mg/l Exposure time: 4 h Test atmosphere: vapour Method: OECD Test Guideline 403 Assessment: No adverse effect has been observed in acute inhalation toxicity tests.
Acute dermal toxicity	:	LD50 (Rabbit): Expected > 2,000 mg/kg Assessment: No adverse effect has been observed in acute

**Car Brite™ PURPLE DRESSING High Gloss
Tire Dressing**

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
5.4	04/10/2024	600000000718	Date of first issue: 05/23/2016

dermal toxicity tests.

Remarks: Information given is based on data obtained from similar substances.

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks: May cause skin irritation in susceptible persons.

Components:**Heptane, branched, cyclic and linear:**

Result: Irritating to skin.

n-Heptane:

Result: Irritating to skin.

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:**Heptane, branched, cyclic and linear:**

Result: Possibly irritating to eyes

n-Heptane:

Result: Possibly irritating to eyes

Respiratory or skin sensitisation**Skin sensitisation**

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:**Heptane, branched, cyclic and linear:**

Result: Substance is not considered to be potential skin sensitiser.

n-Heptane:

Test Type: Maximisation Test

Species: Guinea pig

Result: Did not cause sensitisation on laboratory animals.

Remarks: Information given is based on data obtained from similar substances.

SAFETY DATA SHEET



Car Brite™ PURPLE DRESSING High Gloss Tire Dressing

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
5.4	04/10/2024	600000000718	Date of first issue: 05/23/2016

Germ cell mutagenicity

Not classified based on available information.

Components:

n-Heptane:

Genotoxicity in vitro : Remarks: In vitro tests did not show mutagenic effects

Carcinogenicity

Not classified based on available information.

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Heptane, branched, cyclic and linear:

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness.

n-Heptane:

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

May be fatal if swallowed and enters airways.

Components:

Heptane, branched, cyclic and linear:

May be fatal if swallowed and enters airways.

**Car Brite™ PURPLE DRESSING High Gloss
Tire Dressing**

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
5.4	04/10/2024	600000000718	Date of first issue: 05/23/2016

n-Heptane:

May be fatal if swallowed and enters airways.

Further information**Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Concentrations substantially above the TLV value may cause narcotic effects.

Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION**Toxicity**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations**IATA-DGR**

UN/ID No.	: UN 1993
Proper shipping name	: Flammable liquid, n.o.s. (Heptane)
Class	: 3
Packing group	: II
Labels	: 3
Packing instruction (cargo aircraft)	: 364
Packing instruction	: 353

SAFETY DATA SHEET



Car Brite™ PURPLE DRESSING High Gloss Tire Dressing

Version 5.4 Revision Date: 04/10/2024 SDS Number: 600000000718 Date of last issue: 04/09/2024
Date of first issue: 05/23/2016

(passenger aircraft)

IMDG-Code

UN number : UN 1993
Proper shipping name : FLAMMABLE LIQUID, N.O.S.
(Heptane)
Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

UN/ID/NA number : UN 1993
Proper shipping name : Flammable liquids, n.o.s.
(Heptane)
Class : 3
Packing group : II
Labels : 3
ERG Code : 128
Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Ethyl acetate	141-78-6	100	100 (F003)
Ethyl acetate	141-78-6	5000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Hazard not otherwise classified (physical hazards)
Aspiration hazard
Skin corrosion or irritation
Specific target organ toxicity (single or repeated exposure)

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SAFETY DATA SHEET



Car Brite™ PURPLE DRESSING High Gloss Tire Dressing

Version	Revision Date:	SDS Number:	Date of last issue: 04/09/2024
5.4	04/10/2024	600000000718	Date of first issue: 05/23/2016


California Prop. 65

WARNING: This product can expose you to chemicals including n-Hexane, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Revision Date : 04/10/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN