

ZEP M L LUBRICANT AERO

Version 2.3

Revision Date 05/09/2018

Print Date 05/12/2018

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : ZEP M L LUBRICANT AERO

Material number : 00000000000731300

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE
Emerson, GA 30137

Telephone : 404-352-1680

Emergency telephone numbers**For SDS Information** : Compliance Services 1-877-428-9937**For a Medical Emergency** : 877-541-2016 Toll Free - All Calls Recorded**For a Transportation** : CHEMTREC: 800-424-9300 - All Calls Recorded.**Emergency** : In the District of Columbia 202-483-7616**Recommended use of the chemical and restrictions on use**

Recommended use : Lubricant

SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

| | |
|------------|------------------------------------|
| Appearance | Aerosol containing a liquefied gas |
| Colour | black |
| Odour | solvent-like |

GHS Classification

Flammable aerosols : Category 1

Gases under pressure : Liquefied gas

Skin irritation : Category 2

Eye irritation : Category 2A

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames

ZEP M L LUBRICANT AERO

Version 2.3

Revision Date 05/09/2018

Print Date 05/12/2018

and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse.

Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

| Chemical name | CAS-No. | Concentration [%] |
|--|------------|-------------------|
| asphalt | 8052-42-4 | >= 30 - < 50 |
| propane | 74-98-6 | >= 5 - < 10 |
| alkanes, C12-14-iso- | 68551-19-9 | >= 5 - < 10 |
| butane | 106-97-8 | >= 5 - < 10 |
| Distillates (petroleum), hydrotreated heavy naphthenic | 64742-52-5 | >= 5 - < 10 |

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.
Wash off immediately with plenty of water for at least 15 minutes.
If on clothes, remove clothes.
- In case of eye contact : Remove contact lenses.
Protect unharmed eye.

ZEP M L LUBRICANT AERO

Version 2.3

Revision Date 05/09/2018

Print Date 05/12/2018

- Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
If in eyes, rinse with water for 15 minutes.
- If swallowed : Keep respiratory tract clear.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
DO NOT induce vomiting unless directed to do so by a physician or poison control center.
- Most important symptoms and effects, both acute and delayed : Effects are immediate and delayed.
Symptoms may include irritation, redness, pain, and rash.
Causes skin irritation.
Causes serious eye irritation.
Review section 2 of SDS to see all potential hazards.
- Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon dioxide (CO₂)
Carbon monoxide
Smoke
Phosphorus compounds
Sulphur oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use water spray to cool unopened containers.
For safety reasons in case of fire, cans should be stored separately in closed containments.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and : Use personal protective equipment.
Ensure adequate ventilation.

ZEP M L LUBRICANT AERO

Version 2.3

Revision Date 05/09/2018

Print Date 05/12/2018

- emergency procedures Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Sweep up or vacuum up spillage and collect in suitable container for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
In case of insufficient ventilation, wear suitable respiratory equipment.
Do not breathe vapours or spray mist.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Always replace cap after use.
- Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
No smoking.
Keep in a dry, cool and well-ventilated place.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : Oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|------------|-----------|--------------------------------|--|-------|
| asphalt | 8052-42-4 | TWA (Fume, inhalable fraction) | 0.5 mg/m ³ | ACGIH |

ZEP M L LUBRICANT AERO

Version 2.3

Revision Date 05/09/2018

Print Date 05/12/2018

| | | | | |
|---|------------|--------------------------------|--------------------------------------|-----------|
| | | C (Fumes) | 5 mg/m ³ | NIOSH REL |
| | | PEL (Fumes) | 5 mg/m ³ | CAL PEL |
| propane | 74-98-6 | TWA | 1,000 ppm | ACGIH |
| | | TWA | 1,000 ppm 1,800 mg/m ³ | NIOSH REL |
| | | TWA | 1,000 ppm 1,800 mg/m ³ | OSHA Z-1 |
| | | TWA | 1,000 ppm 1,800 mg/m ³ | OSHA P0 |
| | | PEL | 1,000 ppm 1,800 mg/m ³ | CAL PEL |
| butane | 106-97-8 | TWA | 800 ppm 1,900 mg/m ³ | NIOSH REL |
| | | TWA | 800 ppm 1,900 mg/m ³ | OSHA P0 |
| | | PEL | 800 ppm 1,900 mg/m ³ | CAL PEL |
| Distillates (petroleum), hydrotreated heavy naphthenic | 64742-52-5 | TWA (Mist) | 5 mg/m ³ | OSHA Z-1 |
| | | TWA (Inhalable fraction) | 5 mg/m ³ | ACGIH |

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material

Remarks

: Protective gloves
: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Tightly fitting safety goggles
Ensure that eyewash stations and safety showers are close to the workstation location.

Skin and body protection

: Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures

: When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a liquefied gas

ZEP M L LUBRICANT AERO

Version 2.3

Revision Date 05/09/2018

Print Date 05/12/2018

| | |
|--|--------------------------------|
| Colour | : black |
| Odour | : solvent-like |
| Odour Threshold | : No data available |
| pH | : Not applicable |
| Melting point/freezing point | : No data available |
| Boiling point | : No data available |
| Flash point | : Not applicable |
| Evaporation rate | : No data available |
| Flammability (solid, gas) | : Extremely flammable aerosol. |
| Upper explosion limit | : No data available |
| Lower explosion limit | : No data available |
| Vapour pressure | : No data available |
| Relative vapour density | : No data available |
| Density | : No data available |
| Solubility(ies) | |
| Water solubility | : insoluble |
| Solubility in other solvents | : not determined |
| Partition coefficient: n-octanol/water | : No data available |
| Auto-ignition temperature | : not determined |
| Thermal decomposition | : No data available |
| Viscosity | |
| Viscosity, kinematic | : No data available |
| Heat of combustion | : > 20 kJ/g |

SECTION 10. STABILITY AND REACTIVITY

| | |
|------------------------------------|---|
| Reactivity | : Stable |
| Chemical stability | : Stable under normal conditions. |
| Possibility of hazardous reactions | : Vapours may form explosive mixture with air. No decomposition if stored and applied as directed. |
| Conditions to avoid | : Heat, flames and sparks. Extremes of temperature and direct sunlight. |
| Incompatible materials | : Oxidizing agents |

ZEP M L LUBRICANT AERO

Version 2.3

Revision Date 05/09/2018

Print Date 05/12/2018

Hazardous decomposition products : Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION**Potential Health Effects**

Aggravated Medical Condition : None known.
Symptoms of Overexposure : Effects are immediate and delayed.
Symptoms may include irritation, redness, pain, and rash.

Carcinogenicity:

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Acute toxicity**Components:****Distillates (petroleum), hydrotreated heavy naphthenic:**

Acute oral toxicity : LD50 Rat: > 5,000 mg/kg
Acute inhalation toxicity : LC50 Rat: > 5 mg/l
Exposure time: 4 h
Acute dermal toxicity : LD50 Rabbit: > 5,000 mg/kg

Skin corrosion/irritation**Product:**

Remarks: Irritating to skin.

Serious eye damage/eye irritation**Product:**

Remarks: Severe eye irritation

Respiratory or skin sensitisation

No data available

ZEP M L LUBRICANT AERO

Version 2.3

Revision Date 05/09/2018

Print Date 05/12/2018

Germ cell mutagenicity

No data available

Carcinogenicity

No data available

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information**Product:**

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential**Product:**

Partition coefficient: n-octanol/water : Remarks: No data available

Components:**butane :**

Partition coefficient: n-octanol/water : Pow: 2.89

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I

ZEP M L LUBRICANT AERO

Version 2.3

Revision Date 05/09/2018

Print Date 05/12/2018

| | |
|-----------------------------------|---|
| Remarks | Substances This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B). |
| Additional ecological information | : No data available |

SECTION 13. DISPOSAL CONSIDERATIONS
Disposal methods

| | |
|------------------------|--|
| Waste from residues | : The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of in accordance with local regulations. |
| Contaminated packaging | : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum. |

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA):
ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel):
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air):
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air):
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada):
UN1950, AEROSOLS, FLAMMABLE, 2.1, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

ZEP M L LUBRICANT AERO

Version 2.3

Revision Date 05/09/2018

Print Date 05/12/2018

TSCA list : No substances are subject to a Significant New Use Rule.
No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act**CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Gases under pressure
Skin corrosion or irritation
Serious eye damage or eye irritation

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

DSL All components of this product are on the Canadian DSL
TSCA On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

ZEP M L LUBRICANT AERO


Version 2.3

Revision Date 05/09/2018

Print Date 05/12/2018

Further information

NFPA:



HMIS III:

| | |
|------------------------|----------|
| HEALTH | 2 |
| FLAMMABILITY | 2 |
| PHYSICAL HAZARD | 3 |

0 = not significant, 1 =Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms :



Signal word :

Danger:

Hazard statements :

Extremely flammable aerosol. Contains gas under pressure; may explode if heated.
Causes skin irritation. Causes serious eye irritation.

Precautionary statements :

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use. Wash skin thoroughly after handling. Wear protective gloves/ eye protection/ face protection.
Response: IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse.
Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

| | |
|----------------|------------|
| Version: | 2.3 |
| Revision Date: | 05/09/2018 |
| Print Date: | 05/12/2018 |

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®,

ZEP M L LUBRICANT AERO

Version 2.3

Revision Date 05/09/2018

Print Date 05/12/2018

Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal™, and a number of private labeled brands.