

Safety Data Sheet

Revision Date 02-02-2017
Revision Number 18



SECTION 1 Identification of the substance/mixture and of the company/undertaking

Product identification used on label

Product identifier	4008 NOX-RUST® X-210
Details of the supplier of the safety data sheet	Daubert Chemical Company 4700 S. Central Avenue Chicago, IL 60638 708-496-7350
Emergency telephone number	Chemtrec: (800) 424-9300
Relevant identified uses of the substance or mixture and uses advised against	Corrosion Preventive Compound

SECTION 2 Hazards identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols



GHS Classification	Aspiration Hazard Category 1 Skin Corrosion/Irritation Category 2 Serious Eye Damage/Eye Irritation Category 2A Flammable Liquid Category 3 Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3
Signal Word	Danger
Hazard Statements	Flammable liquid and vapor May be fatal if swallowed and enters airways Causes skin irritation Causes serious eye irritation May cause respiratory irritation May cause drowsiness or dizziness
Unclassified Hazards (HNOC):	None Identified
Precautionary Statements	
Prevention	Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Ground/bond container and receiving equipment. Use explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling.

Safety Data Sheet

Revision Date 02-02-2017
Revision Number 18

Response	Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. IF ON SKIN: Wash with plenty of soap and water. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER or doctor/physician if you feel unwell. Specific treatment: None known Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.
Storage	Use dry chemical, water fog, CO2, foam or sand/earth for extinction. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.

SECTION 3 Composition/information on ingredients

Chemical Name	CAS #	%
Hydrotreated light distillate (Petroleum)	64742-47-8	70 - 100
Diethylene glycol mono-n-butyl ether	112-34-5	1 - 5

Note: Specific chemical identities and/or exact percentages have been withheld as a trade secret.

SECTION 4 First aid measures

Inhalation	If symptoms are experienced remove source of contamination or move victim to fresh air and obtain medical advice.
Eyes	Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician.
Skin Contact	Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.
Ingestion	Do not induce vomiting and seek medical attention immediately. Provide medical care provider with this SDS. If vomiting occurs, lean victim forward to reduce risk of aspiration into lungs.
Most important symptoms/effects, acute and delayed	See Section 11
Indication of immediate medical attention and special treatment needed	Treat symptomatically.

Safety Data Sheet

Revision Date 02-02-2017
Revision Number 18

SECTION 5 Firefighting measures

Suitable extinguishing media:	Use alcohol resistant foam, carbon dioxide, dry chemical, or water spray when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the fire.
Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.
Fire and/or Explosion Hazards	Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. Empty containers that retain product residue (liquid, solid/sludge, or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury or death.
Fire Fighting Methods and Protection	Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Use appropriate methods for the surrounding fire.
Hazardous Combustion Products	Oxides of carbon, Aldehydes, Smoke, Sulfur oxides, Barium oxides, Peroxides, Hydrocarbons

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures	Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.
Methods and materials for containment and cleaning up	Absorb or cover with dry earth, sand or other non-combustible material and transfer to appropriate waste containers. Use clean, non-sparking tools to collect absorbed material. Collect and discard in accordance with local, state and national regulations.

SECTION 7 Handling and storage

Precautions for safe handling	Avoid contacting and avoid breathing the material. Use only in a well ventilated area. As with all chemicals, good industrial hygiene practices should be followed when handling this material. Wash thoroughly after handling. Do not get in eyes, on skin and clothing. Ground and bond containers when transferring material. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. When heated, the vapor/fumes given off may cause respiratory tract irritation.
Conditions for safe storage, including any incompatibilities	Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed. Keep away from heat, sparks, and flame. Do not store in direct sunlight. Store away from sources of heat and light.
Incompatible materials	Strong oxidizing agents

Safety Data Sheet

Revision Date 02-02-2017
Revision Number 18

SECTION 8 Exposure controls/personal protection

Control parameters

<u>Chemical Name</u>	<u>ACGIH TLV</u>	<u>ACGIH STEL</u>	<u>OSHA PEL</u>
Hydrotreated light distillate (Petroleum)	200 mg/m ³		
Diethylene glycol mono-n-butyl ether	10 ppm		

This product contains mineral oils having recommended exposure limits of 5 mg/m³ in mist form. Because the viscosity of this product is ≤ 20.5 cSt, mists can be formed in certain applications. If mists do form, use appropriate controls to maintain exposure below the stated limits.

Engineering Measures	Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure. Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits
Respiratory Protection	Proper ventilation (at a minimum) will be required when handling this product. Use respirators (NIOSH approved) only if ventilation cannot be used to eliminate symptoms or reduce the exposure to below acceptable levels. Follow a respiratory protection program that meets 29 CFR 1910.134 and ANSI Z88.2 requirements whenever work place conditions warrant the use of a respirator.
Eye Protection	Wear chemical splash goggles when handling this product. Additionally, wear a face shield when the possibility of splashing of liquid exists. Do not wear contact lenses. Have an eye wash station available.
Skin Protection	Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. When handling material that has been heated, wear chemically resistant thermally insulating gloves, chemical resistant apron, long sleeves and other clothing as necessary to protect against thermal burns.
Gloves	Chemically resistant gloves Heat insulating chemically resistant gloves

SECTION 9 Physical and chemical properties (Typical, not specification)

Physical State	Liquid
Color	Amber
Odor	Mild Hydrocarbon Solvent
Odor Threshold	No data available
pH	No data available
Melting Point/freezing point, °C	No data available
Initial boiling point and boiling range, °C	No data available
Flash Point	105 °F(41 °C)
Evaporation Rate	<1 (n-Butyl Acetate=1)
Flammability (Solid, Gas)	No data available
Lower Flammable/Explosive Limit, % in air	No data available

Safety Data Sheet

Revision Date 02-02-2017
Revision Number 18

Upper Flammable/Explosive Limit, % in air	No data available
Vapor Pressure	3.4 mmHg
Vapor Density	>1 (Air=1)
Specific Gravity @ 25°C	0.79
Solubility in Water	Negligible; 0-1%
Octanol/Water Partition Coefficient	No data available
Autoignition Temperature	No data available
Decomposition Temperature	No data available
Viscosity	1.3 cSt @ 40°C
Volatiles, % by weight	90.0
VOC, Material, lb/gal	5.93
VOC, Material, grams/liter	711.3

SECTION 10 Stability and reactivity

Reactivity	No data available
Chemical stability	Stable under normal conditions. Hazardous polymerization will not occur. May form explosive peroxides
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	Contamination. Elevated temperatures.
Incompatible materials	Strong oxidizing agents
Hazardous decomposition products	Under normal conditions of use & storage, decomposition and hazardous decomposition products are unlikely.

SECTION 11 Toxicological information

Likely Routes of Entry	Inhalation, Skin contact, Eye contact
Target Organs Potentially Affected by Exposure	Central Nervous System
Chemical Interactions That Change Toxicity	No chemical interaction known to affect toxicity.
Medical Conditions Aggravated	Skin contact may aggravate existing skin disease, Respiratory disease including asthma and bronchitis

Immediate (Acute) Health Effects by Route of Exposure

Inhalation Irritation	Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache. Other possible symptoms include; wheezing and coughing due to pulmonary edema (fluid build-up in lungs).
Inhalation Toxicity	Non-Toxic. Not known to cause systemic damage.
Skin Contact	Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.
Skin Absorption	May cause irritation and minor systemic damage.
Eye Contact	Contact with the eyes may cause moderate to severe eye injury. Eye contact may result in tearing and reddening, but not likely to permanently injure eye tissue. Temporary vision impairment (cloudy or blurred vision) is possible.
Ingestion Irritation	Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.
Ingestion Toxicity	Harmful if swallowed.

Safety Data Sheet

Revision Date 02-02-2017
Revision Number 18

Long-Term (Chronic) Health Effects

Carcinogenicity	There are no carcinogenic ingredients present at or over 0.1%.
Inhalation	Upon prolonged and/or repeated exposure, can cause severe respiratory irritation, dizziness, weakness, fatigue, nausea, headache and possible unconsciousness.
Skin Contact	Upon prolonged or repeated contact, can cause minor skin irritation, defatting, and dermatitis.
Skin Absorption	Upon prolonged or repeated exposure, harmful if absorbed through the skin. May cause minor systemic damage.
Ingestion	Under normal industrial usage conditions, ingestion is highly unlikely.
Eyes (Draize score)	This material is estimated to be non-irritating eyes (Draize score <15 [rabbits]).

Component Toxicology Data

Chemical Name	CAS Number	LD50/LC50
Hydrotreated light distillate (Petroleum)	64742-47-8	Dermal LD50 Rabbit > 2000 mg/kg Oral LD50 Rat > 5000 mg/kg Inhalation LC50 (4h) Rat > 20 mg/L
Diethylene glycol mono-n-butyl ether	112-34-5	Dermal LD50 Rabbit = 2764 mg/kg Oral LD50 Rat = 4500 mg/kg

SECTION 12 Ecological information

Overview	No ecological information available
Mobility	No data
Persistence	No data
Bioaccumulation	No data
Degradability	No data

Ecotoxicity Data

Chemical Name	CAS Number	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
Diethylene glycol mono-n-butyl ether	112-34-5	EC50 (48 hr) Daphnia > 100 mg/L	EC50 (96 hr) Algae > 100 mg/L	LC50 (96 hr) Fish = 1300 mg/L

SECTION 13 Disposal considerations

Waste Description for Spent Product	Spent or discarded material may be a hazardous waste.
Disposal Methods	Dispose of by incineration following Federal, State, Local, or Provincial regulations.
Waste Disposal Code(s)	D001

SECTION 14 Transport information

Full shipping name for Export, Air, Sea (any quantity unless flash pt. >150°F) or vessels of 119 GL or more Domestic Ground in vessels < 119 gal.	UN1268, PETROLEUM DISTILLATES, N.O.S., (Naphtha Solvent), 3, PG III, Non-Regulated
--	--

Safety Data Sheet

Revision Date 02-02-2017
Revision Number 18

SECTION 15 Regulatory information

Status of formula components on selected national regulatory inventories:

LIST	STATUS
TSCA	All components in this product are on the TSCA Inventory or exempt.
Canadian DSL	All chemical substances in this material are included on or exempted from listing on the Canadian DSL.

Chemical Name	CAS #	Regulation	Percent
No CERCLA-listed chemicals in this product.		CERCLA	
Glycol ether (N230)	112-34-5	SARA 313	1 - 5
Barium compounds	61790-48-5	SARA 313	1 - 5
No SARA 302 EHS-listed chemicals in this product.		SARA EHS	

SECTION 16 Other information

Revision 02-02-2017

Date

Disclaimer Although the information contained herein is believed to be reliable, it is furnished without warranty of any kind. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, and storage.

Version Reviewed

Comments Approved: M. Duncan