



### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: High Temp. RTV Silicone Sensor-Safe Gasket Item No.: 81422 / IDH No. 235331

Maker

Product Use:Silicone Rubber SealantRegion:CanadaCompany address:Contact Information:Henkel Canada CorporationTelephone: (905) 814-6511

2225 Meadowpine Boulevard Emergency telephone: (905) 814-6511

Mississauga, Ontario L5N 7P2 Internet: www.henkelna.com

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components Silica, amorphous (fumed) 7631-86-9	<u>%</u> 5-10	ACGIH TLV 6 mg/m³ TWA	<u>OSHA PEL</u> 10 mg/m³ TWA	OTHER 3 mg/m³ TWA respirable dus	
Iron oxide 1309-37-1	1-5	1 mg/m³ TWA as Fe 5 mg/m³ TWA dust and fume, as Fe	10 mg/m³ TWA	None	
Ethyltriacetoxysilane 17689-77-9	1-5	None	None	None	
Methyltriacetoxysilane 4253-34-3	1-5	None	None	None	

Exposure to moisture during cure will release 1-5% acetic acid. The above components are hazardous as defined in 29 CFR 1910.1200.

# 3. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

Physical state: Paste WHMIS hazard class: D.2.B

Color: Red
Odor: Acetic Acid

**CAUTION:** MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Skin contact, Eye contact, Inhalation

**Potential Health Effects** 

**Inhalation:** Acetic acid produced during cure may irrritate eyes, nose and throat. When heated to temperatures

exceeding 300° F (150° C) in the presence of air, silicones may form formaldehyde vapors.

Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate the eyes, nose and throat. Safe handling conditions may be maintained by keeping formaldehyde

vapor concentrations below the OSHA permissible limt.

**Skin contact:** May cause skin irritation.

**Eye contact:** Vapors may irritate eyes. Contact with eyes will cause irritation.

**Ingestion:** Not expected to be harmful by ingestion.

Existing conditions aggravated by

exposure:

Eye, skin, and respiratory disorders.

See Section 11 for additional toxicological information.

Item No.: 81422 / IDH No. 235331 Product name: High Temp. RTV Silicone Sensor-Safe Gasket Maker

1 of 5

#### 4. FIRST AID MEASURES

**Inhalation:** Remove to fresh air. If discomfort persists seek medical attention.

**Skin contact:** Wipe off paste with paper towel or cloth. Wash with soap and water.

Eye contact: Rinse thoroughly with plenty of water, also under the eyelids. If eye irritation persists, consult a

specialist.

**Ingestion:** Do not induce vomiting. If a person feels unwell or symptoms of skin irritation appear, consult a

physician.

Notes to physician: Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

Flash point: Greater than 93°C (200°F) Tagliabue closed cup

Autoignition temperature: Not available

Flammable/Explosive limits-lower %: Acetic acid: 4%

Flammable/Explosive limits-upper %: Acetic acid: 19.9%@ 200®F

**Extinguishing media:** Foam, dry chemical or carbon dioxide.

Special fire fighting procedures: None

Unusual fire or explosion hazards: None

**Hazardous combustion products:** Formaldehyde. Silica Mist. Acrid smoke and fumes.

Sensitivity to mechanical impact: Not available.

Sensitivity to static discharge: Not available.

## **6. ACCIDENTAL RELEASE MEASURES**

**Environmental precautions:** Prevent product from entering drains or open waters.

Clean-up methods: Scrape up as much material as possible. Spilled material will solidify. Store in a closed container until

ready for disposal. Maintain good ventilation for large spills.

#### 7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Do not get in eyes. Do not get on skin or clothing. Do not

wear contact lenses.

**Storage:** Store in a dry area below 90° F Keep container closed.

**Incompatible products:** Avoid contact with water. Acids. Oxidizing agents.

For information on product shelf life contact Henkel Canada Customer Service at (905) 814-6511.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Engineering controls:** Ensure adequate ventilation.

Respiratory protection: No personal respiratory protective equipment normally required. Use NIOSH approved respirator if

there is potential to exceed exposure limit(s).

**Skin protection:** Chemical resistant, impermeable gloves.

**Eye/face protection:** Chemical splash goggles or safety glasses with side shields.

Item No.: 81422 / IDH No. 235331 Product name: High Temp. RTV Silicone Sensor-Safe Gasket Maker

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Paste
Color: Red
Odor: Acetic Acid
Odor Threshold: Not available

Vapor pressure: <10 mmHg @20°C (68° F)

pH: Not applicable
Boiling point/range: Not available
Melting point/range: Not available
Specific gravity: 1.01 at 20 deg. C
Vapor density: Heavier than air
Evaporation rate: Not available

**Solubility in water:** Insoluble Polymerizes in presence of water

Partition coefficient (n-octanol/water): Not available

VOC content: 4.7%; 47.47 grams/liter

### 10. STABILITY AND REACTIVITY

Stability: Stable.

Hazardous polymerization: Will not occur.

Hazardous decomposition products: Acetic acid is liberated slowly upon contact with moisture. Formaldehyde.

**Incompatability:** Acids. Bases. Oxidizing agents. Water.

Conditions to avoid: Prolonged heating at temperatures above 150°C °C. Exposure to moisture.

### 11. TOXICOLOGICAL INFORMATION

Product toxicity data: Not available

Toxicologically synergistic products: Not available.

81422 / IDH No. 235331

Item No.:

Refer to the following for Irritancy of Product, Sensitization to Product, Carcinogenicity, Reproductive Toxicity, Teratogenicity, and Mutagenicity.

### **Ingredient Toxicity Data & Carcinogen Status**

Hazardous components	LD50s & LC50s	Other LD50s and LC50s	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen	ACGIH - Carcinogens
Silica, amorphous (fumed) 7631-86-9	Dermal LD50 (Rabbit) > 2000 mg/kg Oral LD50 (Rat) > 5000 mg/kg	None	No	No	No	No
Iron oxide 1309-37-1	Oral LD50 (Rat) = 984 mg/kg Oral LD50 (Rat) > 10000 mg/kg	None	No	No	No	A4 - Not Classifiable as a Human Carcinogen (dust and fume)
Ethyltriacetoxysilane 17689-77-9	None	None	No	No	No	No
Methyltriacetoxysilane 4253-34-3	Oral LD50 (Rat) = 2060 mg/kg	None	No	No	No	No

# Literature Referenced Target Organ & Other Health Effects

Hazardous components	Health Effects/Target Organs
Silica, amorphous (fumed) 7631-86-9	Nuisance dust
Iron oxide 1309-37-1	Lung, Liver, Kidney, Irritant, Central nervous system, Cardiac, Allergen
Ethyltriacetoxysilane 17689-77-9	No Target Organs
Methyltriacetoxysilane 4253-34-3	Allergen, Irritant

### 12. ECOLOGICAL INFORMATION

**Ecological information:** 

No specific studies have been conducted by Henkel on the ecotoxicity or environmental fate of this material; however, commonly available data on the material indicate that uncontrolled releases to soil, groundwater, or surface waters could entail acute and/or chronic ecological effects, depending on the quantity and concentration of such releases. Releases of volatile components to the atmosphere are not believed to entail significant ecological consequences provided such releases are within the exposure levels set forth in this document. Accordingly, all appropriate measures should be taken to avoid uncontrolled releases to the environment, and any spills or other uncontrolled releases which may occur should be contained and cleaned up immediately in accordance with Section 6.

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Dispose of in accordance with federal and local regulations.

## 14. TRANSPORT INFORMATION

### Canada Transportation of Dangerous Goods - Ground:

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

### International Air Transportation (ICAO/IATA):

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

## WaterTransportation (IMO/IMDG):

Proper shipping name: Not regulated Hazard class or division: None Identification number: None

Item No.: 81422 / IDH No. 235331 Product name: High Temp. RTV Silicone Sensor-Safe Gasket Maker

Packing group: None Marine pollutant: None known

### 15. REGULATORY INFORMATION

**Canada Regulatory Information** 

Item No.:

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Domestic Substances List.

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

### **16. OTHER INFORMATION**

This material safety data sheet contains changes from the previous version in sections: Reviewed MSDS. Reissued with new date

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Product Regulations.

Prepared by: Regulatory Affairs

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

81422 / IDH No. 235331 Product name: High Temp. RTV Silicone Sensor-Safe Gasket Maker