

SAFETY DATA SHEET



Car Brite™ Metallic Fallout Remover

Version	Revision Date:	SDS Number:	Date of last issue: 04/29/2018
2.0	09/06/2018	600000000764	Date of first issue: 05/23/2016

SECTION 1. IDENTIFICATION

Product name : CB E038E METALLIC FALLOUT REMOVER BULK

Product code : 691720

Manufacturer or supplier's details

Company name of supplier : Niteo Products, LLC

Address : Dallas TX 75225

Email Address : EHS@niteoproducts.com

Telephone : 1-844-696-4836

Emergency telephone number : 1-800-424-9300 / 1-703-741-5970

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Skin corrosion : Category 1

Serious eye damage : Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : Causes severe skin burns and eye damage.

Precautionary statements :

Prevention:

Wash skin thoroughly after handling.
Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

Car Brite™ Metallic Fallout Remover

Version	Revision Date:	SDS Number:	Date of last issue: 04/29/2018
2.0	09/06/2018	600000000764	Date of first issue: 05/23/2016

Wash contaminated clothing before reuse.

Storage:

Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Oxalic acid	144-62-7	$\geq 5 - < 10$
Alcohols, C9-11, ethoxylated	68439-46-3	$\geq 1 - < 3$

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
If on skin, rinse well with water.
Wash contaminated clothing before re-use.
If skin irritation persists, call a physician.
- In case of eye contact : In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
- If swallowed : Get medical attention immediately.
Do NOT induce vomiting.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

SAFETY DATA SHEET



Car Brite™ Metallic Fallout Remover

Version	Revision Date:	SDS Number:	Date of last issue:
2.0	09/06/2018	600000000764	04/29/2018
			Date of first issue: 05/23/2016

- Most important symptoms and effects, both acute and delayed : Causes serious eye damage.
Causes severe burns.
- Notes to physician : This product contains oxalic acid. Following ingestion, inactivate oxalate by giving calcium as a dilute solution of calcium lactate, lime water, finely pulverized chalk, plaster, and/or milk. Gastric lavage is controversial due to possible corrosion in the esophagus or stomach. Systemic effects may be due to formation of a complex between oxalic acid and calcium which is insoluble at physiological pH and can be deposited in the brain and renal tubules, causing nervous system disturbances and kidney damage. Resultant hypocalcemia may be responsible for the muscular and cardiovascular effects, although hypovolemic shock from gastroenteritis or hemorrhage may also cause cardiovascular collapse. Intravenous administration of calcium gluconate or calcium chloride may be required if hypocalcemia or hypocalcemic tetany occur.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray
Carbon dioxide (CO₂)
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon oxides
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Avoid breathing dust.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
Prevent product from entering drains.
Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform

SAFETY DATA SHEET



Car Brite™ Metallic Fallout Remover

Version 2.0 Revision Date: 09/06/2018 SDS Number: 600000000764 Date of last issue: 04/29/2018
Date of first issue: 05/23/2016

respective authorities.

Methods and materials for containment and cleaning up : Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapours/dust.
Avoid contact with skin and eyes.
When diluting, always add the product to water. Never add water to the product.
Dispose of rinse water in accordance with local and national regulations.
Container hazardous when empty.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Observe label precautions.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Oxalic acid	144-62-7	TWA	1 mg/m3	ACGIH
		STEL	2 mg/m3	ACGIH
		TWA	1 mg/m3	NIOSH REL
		ST	2 mg/m3	NIOSH REL
		TWA	1 mg/m3	OSHA Z-1
		TWA	1 mg/m3	OSHA P0
		STEL	2 mg/m3	OSHA P0

Hazardous components without workplace control parameters

Components	CAS-No.
Alcohols, C9-11, ethoxylated	68439-46-3

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Hand protection

Car Brite™ Metallic Fallout Remover

Version	Revision Date:	SDS Number:	Date of last issue: 04/29/2018
2.0	09/06/2018	600000000764	Date of first issue: 05/23/2016

- | | |
|--------------------------|---|
| Remarks | : Wear resistant gloves (consult your safety equipment supplier). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard gloves that show tears, pinholes, or signs of wear. |
| Eye protection | : Wear chemical splash goggles and face shield when there is potential for exposure of the eyes or face to liquid, vapor or mist. |
| Skin and body protection | : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Wear as appropriate:
Impervious clothing
Safety shoes
Remove and wash contaminated clothing before re-use. |
| Hygiene measures | : Handle in accordance with good industrial hygiene and safety practice.
When using do not smoke.
When using do not eat or drink. |
-

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- | | |
|--|---|
| Appearance | : liquid |
| Colour | : colourless |
| Odour | : mild |
| pH | : 0.5 |
| Melting point/freezing point | : No data available |
| Boiling point/boiling range | : 100 °C
(1,013 hPa)
The value is calculated |
| Flash point | : Not applicable |
| Evaporation rate | : No data available |
| Flammability (solid, gas) | : No data available |
| Self-ignition | : No data available |
| Upper explosion limit / Upper flammability limit | : No data available |
| Lower explosion limit / Lower flammability limit | : No data available |
| Vapour pressure | : 23.3333333 hPa (20 °C)
The value is calculated |
| Density | : 1.027 g/cm3 |

SAFETY DATA SHEET



Car Brite™ Metallic Fallout Remover

Version	Revision Date:	SDS Number:	Date of last issue: 04/29/2018
2.0	09/06/2018	600000000764	Date of first issue: 05/23/2016

Solubility(ies)	
Water solubility	: soluble
Partition coefficient: n-octanol/water	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Oxidizing properties	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed. Hazardous polymerisation does not occur.
Conditions to avoid	: No data available
Incompatible materials	: Aluminium halogens Copper Copper alloys Silver Strong bases Strong oxidizing agents Do not use with aluminum equipment at temperatures above 49C or 120 degrees F.
Hazardous decomposition products	: Carbon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Eye contact
Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity	: Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method
---------------------	--

Remarks: Causes digestive tract burns.

Car Brite™ Metallic Fallout Remover

Version	Revision Date:	SDS Number:	Date of last issue: 04/29/2018
2.0	09/06/2018	600000000764	Date of first issue: 05/23/2016

Components:**Oxalic acid:**

Acute oral toxicity : LD50 (Rat): 1,080 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 20,000 mg/kg

Alcohols, C9-11, ethoxylated:

Acute oral toxicity : LD50 (Rat): 500 - 2,000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Skin corrosion/irritation

Causes severe burns.

Product:

Remarks: Causes severe skin burns and eye damage.

Components:**Oxalic acid:**

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Alcohols, C9-11, ethoxylated:

Result: Mild skin irritation

Serious eye damage/eye irritation

Causes serious eye damage.

Product:

Remarks: May cause irreversible eye damage.

Components:**Oxalic acid:**

Result: Irreversible effects on the eye

Alcohols, C9-11, ethoxylated:

Result: Irreversible effects on the eye

Respiratory or skin sensitisation**Skin sensitisation**

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

SAFETY DATA SHEET



Car Brite™ Metallic Fallout Remover

Version	Revision Date:	SDS Number:	Date of last issue: 04/29/2018
2.0	09/06/2018	600000000764	Date of first issue: 05/23/2016

Components:

Oxalic acid:

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

Carcinogenicity

Not classified based on available information.

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SAFETY DATA SHEET



Car Brite™ Metallic Fallout Remover

Version	Revision Date:	SDS Number:	Date of last issue: 04/29/2018
2.0	09/06/2018	600000000764	Date of first issue: 05/23/2016

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations

IATA-DGR

UN/ID No.	: UN 1760
Proper shipping name	: Corrosive liquid, n.o.s. (OXALIC ACID)
Class	: 8
Packing group	: III
Labels	: 8
Packing instruction (cargo aircraft)	: 856

IMDG-Code

UN number	: UN 1760
Proper shipping name	: CORROSIVE LIQUID, N.O.S. (OXALIC ACID)
Class	: 8
Packing group	: III
Labels	: 8
EmS Code	: F-A, S-B
Marine pollutant	: no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

UN/ID/NA number	: UN 1760
Proper shipping name	: Corrosive liquids, n.o.s. (OXALIC ACID)
Class	: 8
Packing group	: III
Labels	: 8
ERG Code	: 154
Marine pollutant	: no

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SAFETY DATA SHEET



Car Brite™ Metallic Fallout Remover

Version	Revision Date:	SDS Number:	Date of last issue: 04/29/2018
2.0	09/06/2018	600000000764	Date of first issue: 05/23/2016

SARA 311/312 Hazards : Skin corrosion or irritation
Serious eye damage or eye irritation

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.


California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Revision Date : 09/06/2018

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN