CR@

SAFETY DATA SHEET

1. Identification

Product identifier Silaramic® Brake System Grease - 5 oz

Other means of identification

Product Code No. 05361 (Item# 1003793)

Recommended use Brake system grease

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.

Warminster, PA 18974 US

Telephone

 General Information
 215-674-4300

 Technical Assistance
 800-521-3168

 Customer Service
 800-272-4620

 24-Hour Emergency
 800-424-9300 (US)

(CHEMTREC)

Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Not classified.
Health hazards Not classified.

Environmental hazards Hazardous to the aquatic environment, Category 3

long-term hazard

OSHA defined hazards Not classified.

Label elements

Hazard symbol None.
Signal word None.

Hazard statement The mixture does not meet the criteria for classification.

Precautionary statement

Prevention Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air

supply during use and while product is drying.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
polydimethylsiloxane		63148-62-9	70 - 80
talc (not containing asbestos fibers)		14807-96-6	10 - 20
amorphous fumed silica		112945-52-5	5 - 10
distillates (petroleum), hydrotreated heavy naphthenic		64742-52-5	1 - 3

Material name: Silaramic® Brake System Grease - 5 oz
No. 05361 (Item# 1003793) Version #: 02 Revision date: 09-18-2020 Issue date: 12-13-2019

Chemical name Common name and synonyms **CAS** number 2,6-di-tert-butyl-p-cresol 128-37-0

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. If breathing is difficult, trained personnel should give oxygen. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if symptoms persist. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

For skin contact flush with large amounts of water. Get medical attention if symptoms occur. Remove and isolate contaminated clothing and shoes. Wash contaminated clothing before reuse.

Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if symptoms occur.

Ingestion

Rinse mouth. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. If symptoms persist, get medical attention. Never give anything by mouth to a victim who is unconscious or is having convulsions. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special treatment needed

Treat symptomatically. If ingestion of a large amount does occur, call a poison control center immediately. If inhalation of a large amount does occur, call a physician immediately.

General information

media

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). None known.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire-fighting equipment/instructions

Immediately evacuate personnel to safe areas. Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Evacuate the area promptly. Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Ensure adequate ventilation. Wear appropriate protective equipment and clothing during clean-up. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up The product is immiscible with water and will sediment in water systems. Prevent product from entering drains. Stop the flow of material, if this is without risk. Following product recovery, flush area with water. Sweep up or vacuum up spillage and collect in suitable container for disposal. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground. Prevent further leakage or spillage if safe to do so. Inform appropriate managerial or supervisory personnel of all environmental releases. Avoid release to the environment.

No. 05361 (Item# 1003793) Version #: 02 Revision date: 09-18-2020 Issue date: 12-13-2019

7. Handling and storage

Precautions for safe handling

Wear appropriate personal protective equipment. When using, do not eat, drink or smoke. Do not ingest. Wash hands after handling and before eating. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Avoid release to the environment. Keep in original container. Do not re-use empty containers. Observe good industrial hygiene practices. For product usage instructions, see the product label.

Conditions for safe storage, including any incompatibilities

Store in accordance with local/regional/national/international regulation. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Keep away from food, drink and animal feedingstuffs. Use appropriate container to avoid environmental contamination. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components Type Value Form distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) PEL 5 mg/m3 Mist. Value (CAS 64742-52-5) 2000 mg/m3 500 ppm US. OSHA Table Z-3 (29 CFR 1910.1000) Type Value Form Components TWA 0.8 mg/m3 Form (CAS 112945-52-5) 20 mppcf 20 mppcf 40 mppcf talc (not containing asbestos fibers) (CAS 14807-96-6) TWA 0.1 mg/m3 Respirable. US. ACGIH Threshold Limit Values Type Value Form Components Type Value Form 2.6-di-tert-butyl-p-cresol (CAS 128-37-0) TWA 2 mg/m3 Inhalable fraction and vapor. distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) TWA 2 mg/m3 Respirable fraction. US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form 2.6-di-tert-butyl-p-cresol (CAS 128-37-0) TWA 10 mg/m3 Respirable fraction. US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form	US. OSHA Table Z-1 Limits for A	ir Contaminants (29 CFR 1910.	1000)	
hydrotreated heavy naphthenic (CAS 64742-52-5) US. OSHA Table Z-3 (29 CFR 1910.1000) Components Type Value Form TWA 0.8 mg/m3 (CAS 112945-52-5) 100 mppof talc (not containing asbestos fibers) (CAS 14807-96-6) TWA 0.1 mg/m3 Respirable. 20 mppof 2.4 mppof 2.4 mppof Respirable. US. ACGIH Threshold Limit Values Components Type Value Form TWA 2 mg/m3 Inhalable fraction and vapor. 2.6-di-tert-butyl-p-cresol (CAS 128-37-0) distillates (petroleum), hydrotreated heavy naphthenic (CAS 14807-96-6) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form TWA 2 mg/m3 Respirable fraction. Promitive Value Form TWA 2 mg/m3 Respirable fraction. 1 WA 2 mg/m3 Respirable fraction. 2 6-di-tert-butyl-p-cresol (CAS 64742-52-5) 4 807-96-6) Ceiling 1800 mg/m3 Mist.	Components	•	•	Form
US. OSHA Table Z-3 (29 CFR 1910.1000) Components Type Value TWA 0.8 mg/m3 (CAS 112945-52-5) 10 mppcf talc (not containing asbestos fibers) (CAS 14807-96-6) US. ACGIH Threshold Limit Values Components Type Value Form 2.6-di-tert-butyl-p-cresol (CAS 128-37-0) talc (not containing asbestos fibers) TWA 2 mg/m3 Inhalable fraction and vapor. distillates (petroleum), hydrotreated heavy naphthenic (CAS 14807-96-6) US. NIOSH: Pocket Guide to Chemical Hazards Components TWA 1 mg/m3 Respirable. Form 1 WA 2 mg/m3 Inhalable fraction and vapor. Inhalable fraction. Provide Taction. Separable fraction. 1 mg/m3 Inhalable fraction. Provide Taction. Respirable fraction. 1 mg/m3 Respirable.	distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	PEL	5 mg/m3	Mist.
US. OSHA Table Z-3 (29 CFR 1910.1000) Components Type TWA 0.8 mg/m3 20 mppcf talc (not containing asbestos fibers) (CAS 112945-52-5) TWA 20 mppcf talc (not containing asbestos fibers) (CAS 14807-96-6) US. ACGIH Threshold Limit Values Components Type Value Form 2.6-di-tert-butyl-p-cresol (CAS 128-37-0) distillates (petroleum), hydrotreated heavy naphthenic (CAS 14807-96-6) US. NIOSH: Pocket Guide to Chemical Hazards Components TWA 2 mg/m3 Inhalable fraction. Proma Respirable Form 1 WA 2 mg/m3 Inhalable fraction. Proma Respirable fraction and vapor. Inhalable fraction. Proma 1 WA 2 mg/m3 Respirable fraction. Proma Respirable fraction. 1 WA 1 mg/m3 Respirable fraction. 1 malable fraction. 1 mg/m3 Respirable fraction. 1 mg/m3 Respirable.			2000 mg/m3	
Components Type Value Form amorphous furned silica (CAS 112945-52-5) TWA 0.8 mg/m3 Respirable. talc (not containing asbestos fibers) (CAS 14807-96-6) TWA 0.1 mg/m3 Respirable. US. ACGIH Threshold Limit Values Components Type Value Form 2,6-di-lert-butyl-p-cresol (CAS 128-37-0) TWA 2 mg/m3 Inhalable fraction and vapor. distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) TWA 2 mg/m3 Respirable fraction. US. NIOSH: Pocket Guide to Chemical Hazards Components TWA 2 mg/m3 Respirable fraction. US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form 2,6-di-tert-butyl-p-cresol (CAS 128-37-0) TWA 10 mg/m3 2,6-di-tert-butyl-p-cresol (CAS 1128-37-0) TWA 6 mg/m3 (CAS 128-37-0) TWA 1800 mg/m3 distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) STEL 10 mg/m3 Mist.			500 ppm	
amorphous furned silica (CAS 112945-52-5) talc (not containing asbestos fibers) (CAS 14807-96-6) US. ACGIH Threshold Limit Values Components Type Value Form 2.6-di-tert-butyl-p-cresol distillates (petroleum), hydrotreated heavy naphthenic (CAS 128-37-0) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form 1 WA 2 mg/m3 Inhalable fraction and vapor. Allonging Respirable. Form 1 WA 2 mg/m3 Inhalable fraction and vapor. Inhalable fraction. Form 1 WA 2 mg/m3 Respirable fraction. 1 WA 3 mg/m3 Respirable fraction. 1 WA 4 mg/m3 Respirable fraction. 2 mg/m3 Respirable fraction. 2 mg/m3 Respirable fraction. 3 mg/m3 Respirable fraction. 4 mg/m3 Respirable fraction. 4 mg/m3 Respirable fraction. 4 mg/m3 Respirable fraction. 5 mg/m3 Respirable fraction. 5 mg/m3 Respirable fraction. 5 mg/m3 Respirable fraction. 5 mg/m3 Respirable fraction. 6 mg/m3 Respirable fraction. 6 mg/m3 Respirable fraction. 6 mg/m3 Respirable fraction. 7 mg/m3 Respirable fraction. 7 mg/m3 Respirable fraction. 8 mg/m3 Respirable. 9 mg/m3 Respirable.	US. OSHA Table Z-3 (29 CFR 191	0.1000)		
CAS 112945-52-5 talc (not containing asbestos fibers) (CAS 14807-96-6)	Components	Туре	Value	Form
talc (not containing asbestos fibers) (CAS 14807-96-6) TWA 2.0 mppcf 2.4 mppcf Respirable. US. ACGIH Threshold Limit Values Components Type Value Form 2.6-di-tert-butyl-p-cresol (CAS 128-37-0) distillates (petroleum), hydrotreated heavy naphthenic (CAS 128-37-0) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form TWA 2 mg/m3 Inhalable fraction and vapor. TWA 5 mg/m3 Inhalable fraction. Provide the deavy naphthenic (CAS 14807-96-6) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form TWA 10 mg/m3 (CAS 112945-52-5) distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) STEL 10 mg/m3 Mist.	amorphous fumed silica (CAS 112945-52-5)	TWA	0.8 mg/m3	
asbestos fibers) (CAS 14807-96-6) US. ACGIH Threshold Limit Values Components Type Value Form 2.6-di-tert-butyl-p-cresol (CAS 128-37-0) distillates (petroleum), hydrotreated heavy naphthenic (CAS 188-37-0) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form 2 mg/m3 Inhalable fraction and vapor. 5 mg/m3 Inhalable fraction. Proma 2 mg/m3 Inhalable fraction. 8 pg/m3 Respirable fraction. Proma 2 mg/m3 Respirable fraction. 1 TWA 2 mg/m3 Respirable fraction. 1 TWA 2 mg/m3 Respirable fraction. 1 TWA 1 0 mg/m3			20 mppcf	
US. ACGIH Threshold Limit Values Components Type Value Form 2.6-di-tert-butyl-p-cresol (CAS 128-37-0) distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form TWA 2 mg/m3 Inhalable fraction and vapor. distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) talc (not containing asbestos fibers) (CAS 14807-96-6) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form TWA 10 mg/m3 (CAS 128-37-0) distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) STEL 10 mg/m3 Mist.	talc (not containing asbestos fibers) (CAS 14807-96-6)	TWA	0.1 mg/m3	Respirable.
US. ACGIH Threshold Limit Values Components Type Value Form 2.6-di-tert-butyl-p-cresol (CAS 128-37-0) distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) talc (not containing asbestos fibers) (CAS 128-37-0) TWA TWA TWA TWA TWA TWA TWA TW			20 mppcf	
US. ACGIH Threshold Limit Values Components Type Value Form 2,6-di-tert-butyl-p-cresol (CAS 128-37-0) distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) talc (not containing asbestos fibers) (CAS 14807-96-6) US. NIOSH: Pocket Guide to Chemical Hazards Components TWA 2 mg/m3 Inhalable fraction. Form Respirable fraction. Porm Value Form TWA 10 mg/m3 (CAS 112945-52-5) distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) STEL 10 mg/m3 Mist.				Respirable.
ComponentsTypeValueForm2.6-di-tert-butyl-p-cresol (CAS 128-37-0)TWA2 mg/m3Inhalable fraction and vapor.distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) talc (not containing asbestos fibers) (CAS 14807-96-6)TWA2 mg/m3Respirable fraction.US. NIOSH: Pocket Guide to Chemical Hazards ComponentsTypeValueForm2.6-di-tert-butyl-p-cresol (CAS 128-37-0) amorphous fumed silica (CAS 112945-52-5) distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)TWA6 mg/m3STEL10 mg/m3Mist.	US ACGIH Throshold Limit Valu	oe.	••	·
(CAS 128-37-0) distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) talc (not containing asbestos fibers) (CAS 14807-96-6) US. NIOSH: Pocket Guide to Chemical Hazards Components TWA 2 mg/m3 Respirable fraction. Form Value Form 10 mg/m3 (CAS 128-37-0) amorphous fumed silica (CAS 112945-52-5) distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) STEL 10 mg/m3 Mist.	Components		Value	Form
hydrotreated heavy naphthenic (CAS 64742-52-5) talc (not containing asbestos fibers) (CAS 14807-96-6) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form 7WA 2 mg/m3 Respirable fraction. Prom 10 mg/m3 (CAS 128-37-0) amorphous fumed silica (CAS 112945-52-5) distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) STEL 10 mg/m3 Mist.	2,6-di-tert-butyl-p-cresol (CAS 128-37-0)	TWA	2 mg/m3	
asbestos fibers) (ČAS 14807-96-6) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Form 2,6-di-tert-butyl-p-cresol (CAS 128-37-0) amorphous fumed silica (CAS 112945-52-5) distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) STEL 10 mg/m3 Mist.	distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
ComponentsTypeValueForm2,6-di-tert-butyl-p-cresol (CAS 128-37-0)TWA10 mg/m3amorphous fumed silica (CAS 112945-52-5)TWA6 mg/m3distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)Ceiling1800 mg/m3STEL10 mg/m3Mist.	talc (not containing asbestos fibers) (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
2,6-di-tert-butyl-p-cresol (CAS 128-37-0) amorphous fumed silica (CAS 112945-52-5) distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) STEL TWA 10 mg/m3 6 mg/m3 1800 mg/m3 Mist.	US. NIOSH: Pocket Guide to Che	emical Hazards		
(CAS 128-37-0) amorphous fumed silica (CAS 112945-52-5) distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5) STEL TWA 6 mg/m3 1800 mg/m3 Mist.	Components	Туре	Value	Form
(CAS 112945-52-5) distillates (petroleum),	2,6-di-tert-butyl-p-cresol (CAS 128-37-0)	TWA	10 mg/m3	
hydrotreated heavy naphthenic (CAS 64742-52-5) STEL 10 mg/m3 Mist.	amorphous fumed silica (CAS 112945-52-5)	TWA	6 mg/m3	
STEL 10 mg/m3 Mist.	distillates (petroleum), hydrotreated heavy naphthenic (CAS	Ceiling	1800 mg/m3	
TWA 5 mg/m3 Mist.	•	STEL	10 mg/m3	Mist.
		TWA	5 mg/m3	Mist.

Material name: Silaramic® Brake System Grease - 5 oz

SDS US

US. NIOSH: Pocket Guide to Chemical Hazards

Components Value **Form Type** TWA talc (not containing 2 mg/m3 Respirable.

asbestos fibers) (CAS 14807-96-6)

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear protective gloves such as: Neoprene. Nitrile.

Wear suitable protective clothing. Other

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a Respiratory protection

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Solid. Grease. **Form** Off-white. Color Odor Mild.

Odor threshold Not available. Not available.

3110 °F (1710 °C) estimated Melting point/freezing point Initial boiling point and boiling 680 °F (360 °C) estimated

range

Flash point 550.0 °F (287.8 °C) Cleveland Open Cup

Evaporation rate Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits Flammability limit - lower

Not available.

Flammability limit - upper

Not available.

(%)

0.0002 hPa estimated Vapor pressure

Vapor density Not available.

1.1 Relative density

Solubility(ies)

Solubility (water) Insoluble. Partition coefficient Not available.

(n-octanol/water)

500 °F (260 °C) estimated **Auto-ignition temperature**

Decomposition temperature Not available. Not available. **Viscosity**

Percent volatile Not available.

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Oxidizing agents. Acids.

Hazardous decomposition

products

Carbon oxides. Halogenated compounds. Metal oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contactBased on available data, the classification criteria are not met.Eye contactBased on available data, the classification criteria are not met.IngestionBased on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Not known.

Components Species Test Results

amorphous fumed silica (CAS 112945-52-5)

Acute Oral

L DEO

LD50 Rat > 5000 mg/kg

distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)

Acute

Dermal

LD50 Rabbit > 2000 mg/kg

Oral

LD50 Rat > 5000 mg/kg

polydimethylsiloxane (CAS 63148-62-9)

Acute Dermal

LD50 Rabbit > 2000 mg/kg

Oral

LD50 Rat > 10000 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

2,6-di-tert-butyl-p-cresol (CAS 128-37-0) 3 I amorphous fumed silica (CAS 112945-52-5) 3 I

3 Not classifiable as to carcinogenicity to humans. 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

EC50

Components Species Test Results

2,6-di-tert-butyl-p-cresol (CAS 128-37-0)

Aquatic

Acute

Crustacea

Water flea (Daphnia pulex)

1440 µg/l, 48 hours

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential Mobility in soil

No data available.

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33). Empty

containers may be recycled. Collect and reclaim or dispose in sealed containers at licensed waste

disposal site.

Hazardous waste code

Not regulated.

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

15. Regulatory information

US federal regulations This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Material name: Silaramic® Brake System Grease - 5 oz

SDS US

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Food and Drug

Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Classified hazard

Reproductive toxicity

categories

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

US state regulations

US. New Jersey Worker and Community Right-to-Know Act

2,6-di-tert-butyl-p-cresol (CAS 128-37-0)

talc (not containing asbestos fibers) (CAS 14807-96-6)

US. Massachusetts RTK - Substance List

2,6-di-tert-butyl-p-cresol (CAS 128-37-0)

amorphous fumed silica (CAS 112945-52-5)

talc (not containing asbestos fibers) (CAS 14807-96-6)

US. Pennsylvania Worker and Community Right-to-Know Law

2,6-di-tert-butyl-p-cresol (CAS 128-37-0)

amorphous fumed silica (CAS 112945-52-5)

talc (not containing asbestos fibers) (CAS 14807-96-6)

US. Rhode Island RTK

2,6-di-tert-butyl-p-cresol (CAS 128-37-0)

distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)

talc (not containing asbestos fibers) (CAS 14807-96-6)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 2016 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)

talc (not containing asbestos fibers) (CAS 14807-96-6)

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR

> 80.3 %

51.100(s))

Consumer products (40 CFR 59, Subpt. C)

Not regulated

State

Consumer products

Not regulated

VOC content (CA) < 0.3 %

VOC content (OTC) < 0.3 %

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical	No

Substances (EINECS)

Europe European List of Notified Chemical Substances (ELINCS) No Japan Inventory of Existing and New Chemical Substances (ENCS) No Korea Existing Chemicals List (ECL) Yes New Zealand New Zealand Inventory Yes Philippines Yes

Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI) Yes United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

16. Other information, including date of preparation or last revision

Issue date 12-13-2019 **Revision date** 09-18-2020 Danica Fulmer Prepared by

Version # 02

Disclaimer The information contained in this document applies to this specific material as supplied. It may not

be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety

professional, or CRC Industries, Inc..

Revision information This document has undergone significant changes and should be reviewed in its entirety.

Material name: Silaramic® Brake System Grease - 5 oz

8/8 No. 05361 (Item# 1003793) Version #: 02 Revision date: 09-18-2020 Issue date: 12-13-2019

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).